

DIN 3764-2:2024-12 (E)

Compression seals made of elastomer for sealing or covering joints in concrete and masonry - Part 2: Rectangular profiles

Contents

Page

Foreword	4
1 Scope	5
2 Normative references	5
3 Terms and definitions.....	6
4 Form and dimensions	6
5 Material	7
5.1 Base polymer.....	7
5.2 Material properties.....	8
6 Testing	9
6.1 Test piece preparation	9
6.2 Tensile strength at break and elongation at break.....	9
6.3 Hardness	9
6.4 Behaviour after conditioning in ozone	9
6.5 Compression set.....	9
6.6 Change in hardness after cold storage.....	9
6.7 Testing after exposure.....	9
6.7.1 General	9
6.7.2 Wastewater (EF 1), groundwater (EF 2), drinking water (EF 3)	9
6.7.3 Sea water (EF4)	9
6.7.4 Ozone loads (EF 5).....	10
7 Installation and connections.....	10
8 Designation	11
9 Marking.....	11
Annex A (informative) Table of exposure classes for base polymers	12
Annex B (informative) Application examples — Sealing joints with a compression seal with a rectangular profile	13
Annex C (informative) Marking example — Nameplate.....	15
Bibliography	16

Figures

Figure 1 — Example of the cross-section	7
Figure 2 — Diagram of installation, a) prior to and b) after installation.....	10
Figure 3 — Installation diagram	10
Figure B.1 — Internal rectangular compression seal with support.....	13
Figure B.2 — External rectangular compression seal without support	14

Tables

Table 1 — Tolerances	7
Table 2 — Material properties and requirements.....	8
Table 3 — Exposure, area of application and requirements.....	8
Table A.1 — Informative exposure table	12