

ISO 4209-1:2001-09 (E)

Truck and bus tyres and rims (metric series) - Part 1: Tyres

Contents		Page
Foreword		v
1	Scope	1
2	Normative reference	1
3	Terms and definitions	1
4	Tyre designation	1
4.1	Content	1
4.2	Size and construction	2
4.2.1	Marking	2
4.2.2	Nominal section width	2
4.2.3	Nominal aspect ratio	2
4.2.4	Tyre construction code	2
4.2.5	Nominal rim diameter	2
4.3	Service condition characteristics	2
4.3.1	Marking	2
4.3.2	Load index	3
4.3.3	Speed symbol	3
4.4	Other service characteristics	3
4.5	Example	3
5	Tyre dimensions	4
5.1	Calculation of "design" tyre dimensions	4
5.1.1	Coefficients	4
5.1.2	Theoretical rim width, R_{th}	4
5.1.3	Measuring rim width, R_m	4
5.1.4	Design tyre section width, S	4
5.1.5	Design tyre section height, H	4
5.1.6	Design tyre overall diameter, D_o	4
5.1.7	Values	5
5.2	Calculation of "maximum overall tyre dimensions in service"	5
5.2.1	Maximum overall width in service, W_{max}	5
5.2.2	Maximum overall diameter in service, $D_{o,max}$	5
5.3	Minimum dual spacing (MDS)	5
5.4	Approved rim widths	7
6	Tyre dimension tables	8
7	Method of measurement of tyre dimensions	8
8	Service characteristics	8
8.1	Tyre load-carrying capacity	8
8.2	Speed symbol	8
8.3	Load-carrying capacity at various speeds	9
Annex A (informative)	Guideline values for metric series, 5° rims	12
Annex B (informative)	Guideline values for metric series, 15° rims	15
Annex C (informative)	Tyre dimension tables	19