

# ISO 5290:2001-09 (E)

## Belt drives - Grooved pulleys for narrow V-belts - Groove sections 9N/J, 15N/J and 25N/J (effective system)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Specifications .....</b>	<b>1</b>
<b>4.1</b>	<b>Groove profiles .....</b>	<b>1</b>
<b>4.1.1</b>	<b>Groove angle, .....</b>	<b>1</b>
<b>4.1.2</b>	<b>Profile dimensions .....</b>	<b>2</b>
<b>4.2</b>	<b>Effective diameter, <math>d_e</math> .....</b>	<b>2</b>
<b>4.2.1</b>	<b>Series of effective diameters .....</b>	<b>2</b>
<b>4.2.2</b>	<b>Groove angles in relation to given effective diameters .....</b>	<b>2</b>
<b>4.2.3</b>	<b>Smallest effective diameters in relation to given groove sections .....</b>	<b>2</b>
<b>5</b>	<b>Geometrical inspection of grooves .....</b>	<b>6</b>
<b>5.1</b>	<b>Groove profile .....</b>	<b>6</b>
<b>5.2</b>	<b>Groove spacing .....</b>	<b>6</b>
<b>5.3</b>	<b>Effective diameter .....</b>	<b>6</b>
<b>5.4</b>	<b>Run-out tolerances .....</b>	<b>6</b>
<b>6</b>	<b>Quality, surface finish and balancing of pulleys .....</b>	<b>6</b>
<b>Annex A (informative) Background information .....</b>		<b>9</b>
<b>Bibliography .....</b>		<b>10</b>