

# ISO 4250-1:2006-08 (E)

## Earth-mover tyres and rims - Part 1: Tyre designation and dimensions

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Tyre designation .....</b>	<b>1</b>
4.1	General .....	1
4.2	Tyre size and construction .....	2
4.2.1	General .....	2
4.2.2	Nominal section width .....	2
4.2.3	Normal aspect ratio .....	2
4.2.4	Tyre construction code .....	2
4.2.5	Nominal rim diameter code .....	2
4.2.6	Tubeless tyres .....	2
4.3	Index of tyre strength .....	2
4.3.1	General .....	2
4.3.2	Diagonal tyres .....	2
4.3.3	Radial tyres .....	2
4.4	Service condition characteristics .....	3
4.4.1	General .....	3
4.4.2	Load index .....	3
4.4.3	Speed symbol .....	5
4.4.4	Service description .....	5
4.5	Other service characteristics .....	6
4.5.1	Preferred direction of rotation .....	6
4.5.2	Code for usage .....	6
<b>5</b>	<b>Tyre dimensions .....</b>	<b>7</b>
<b>6</b>	<b>Dual spacing .....</b>	<b>7</b>
<b>7</b>	<b>Approved rims .....</b>	<b>7</b>
<b>8</b>	<b>Method of measurement of tyre dimensions .....</b>	<b>7</b>
Bibliography .....		20