

DIN EN 12490:2010-11 (E)

Durability of wood and wood-based products - Preservative-treated solid wood - Determination of the penetration and retention of creosote in treated wood

| Contents | | Page |
|-----------------------|--|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Sampling of creosote-treated wood for the determination of penetration and retention | 5 |
| 4.1 | General requirements | 5 |
| 4.2 | Specific requirements for test samples for the determination of penetration | 6 |
| 4.3 | Specific requirements for test samples for the determination of retention | 6 |
| 5 | Determination of the penetration of creosote in treated wood | 6 |
| 6 | Determination of the retention of creosote in treated wood | 7 |
| 6.1 | Reagents | 7 |
| 6.2 | Apparatus | 7 |
| 6.3 | Preparation of the water trap and the condenser before the extraction | 9 |
| 6.4 | Procedure for the extraction of creosote from the composite sample | 9 |
| 6.5 | Expression of results | 10 |
| 7 | Test report | 10 |
| Annex A (informative) | Sapwood/heartwood boundary determination | 12 |
| A.1 | Scope | 12 |
| A.2 | Pines | 12 |
| A.2.1 | Reagents | 12 |
| A.2.2 | Procedure | 12 |
| A.3 | Douglas fir | 13 |
| A.3.1 | Reagents | 13 |
| A.3.2 | Procedure | 13 |
| Annex B (normative) | Density of some selected timber species that are commonly treated with creosote | 14 |
| Bibliography | | 15 |