DIN EN 14975:2010-12 (E)

Loft ladders - Requirements, marking and testing (includes Amendment A1:2010)

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Maximum load 7

5 Test methods 7
5.1 General 7
5.1.1 Tolerances 7
5.1.2 Test sequence 8
5.1.3 Test temperature 8
5.2 Static load test 8
5.3 Fatigue test 9
5.4 Torsion test of rungs or treads 9
5.5 Handrail test 9
5.6 Ladder stops test 11
5.7 Rungs or treads bending test 11

6 Ladder construction and design 11
6.1 General 11
6.2 Climbing angle 13
6.3 Bearing surface 13
6.4 Handrails 13
6.5 Anti-slip surface 13
6.6 Tread or rung pitch 13
6.7 Free width between stiles 13
6.8 Depth of bearing surface 14
6.9 Distance between the floor and the top of the first rung or tread 14
6.10 Distance between the last rung or tread and the loft floor 14
6.11 Distance between a rung or tread and the trapdoor 14
6.12 Operability 15
6.12.1 Upward pressure 15
6.12.2 Descent control 15
6.13 Sharp edges 15
6.14 Surface finish 15
6.15 Feet 15
6.16 Unintentional opening 15
6.17 Insulating and/or sealing values 16

7 Marking 16

8 User instructions 16