DIN EN 330:2015-01 (E)

Wood preservatives - Determination of the relative protective effectiveness of a wood preservati ve for use under a coating and exposed out-of-ground contact - Field test: L-joint method

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Principle 6

5 Materials 7
5.1 End-seal compounds 7
5.2 Reference coating 7
5.3 Reference preservative 7
5.4 Wood test specimens 7

6 Apparatus and Equipment 10
6.1 Wood working equipment 10
6.2 Conditioning area 10
6.3 Application equipment 10
6.4 Balance 10
6.5 Safety equipment and protective clothing 10
6.6 Labels / tags 10
6.7 Exposure site 11
6.8 Weathering racks 11

7 Sampling 11

8 Treatment and handling of test L-joints 12
8.1 General 12
8.2 End-sealing 12
8.3 Process 12
8.4 Retention of preservative 12
8.5 Post-treatment handling of the L-joints 12

9 Reference L-joints 13

10 Untreated test control L-joints 14

11 Exposure test site 14
11.1 Number of test sites 14
11.2 Installation of the L-joints at the test site 14

12 Inspections 14
12.1 L-joints for non- destructive inspection 14
12.2 L-joints for destructive inspection 15

13 Evaluation 16
13.1 General 16
13.2 Assessment of decay 16

14 Duration of the test 17

15 Validity of the test 17

16 Test report 17

Annex A (informative) Flow chart for the preparation and exposure of L-joints for test 19

Annex B (informative) Information on treatment processes, reference and alternative preservatives and materials 20

Annex C (informative) Example of a Test Report 22

Annex D (informative) Environmental, health and safety precautions within chemical / biological laboratory 24

Bibliography 25