

# DIN EN 15425:2017-05 (E)

## Adhesives - One component polyurethane (PUR) for load-bearing timber structures - Classification and performance requirements

---

| <b>Contents</b>  |  | <b>Page</b> |
|--|--|-------------|
| European foreword .....  |  | 3           |
| Introduction .....   |  | 5           |
| 1  | Scope .....  | 6           |
| 2  | Normative references .....   | 6           |
| 3  | Terms and definitions .....  | 7           |
| 4  | Classification .....   | 8           |
| 5  | Requirements .....   | 11          |
| 5.1  | General .....  | 11          |
| 5.2  | Bond strength in longitudinal tensile shear test .....   | 11          |
| 5.3  | Resistance to delamination .....   | 12          |
| 5.4  | Tensile strength perpendicular to the glue line after climatic treatment (acid damage test) .....  | 13          |
| 5.5  | Effect of wood shrinkage on the shear strength .....   | 13          |
| 5.6  | Static load test of multiple glue line specimens in compression shear .....  | 13          |
| 5.7  | Creep deformation test at cyclic climate conditions with specimens loaded in bending shear .....   | 13          |
| 5.8  | Long-term sustained load test at cyclic climate conditions with specimens loaded perpendicular to the glue line ("Glass house test") ..... | 14          |
| 6  | Test methods .....   | 14          |
| 6.1  | General .....  | 14          |
| 6.2  | Determination of longitudinal tensile shear strength .....   | 14          |
| 6.3  | Determination of resistance to delamination .....  | 14          |
| 6.4  | Determination of tensile strength perpendicular to the glue line after climatic treatment (acid damaged test) .....                        | 14          |
| 6.5  | Determination of the effect of wood shrinkage on the shear strength .....  | 14          |
| 6.6  | Static load test of multiple glue line specimens in compression shear .....  | 14          |
| 6.7  | Creep deformation test with specimens loaded in bending shear .....  | 15          |
| 6.8  | Long-term sustained load test at cyclic climate conditions with specimens loaded perpendicular to the glue line ("Glass house test") ..... | 15          |
| 7  | Working properties of the adhesive .....   | 15          |
| 7.1  | General .....  | 15          |
| 7.2  | Determination of initial viscosity under reference conditions .....  | 15          |
| 7.3  | Determination of open assembly time under reference conditions .....   | 15          |
| 7.4  | Determination of pressing time under reference conditions .....  | 15          |
| 8  | Marking and labelling .....  | 15          |
| Annex A (normative) Climatic treatment prior to shear test ..... |  | 16          |
| Bibliography .....   |  | 17          |