

DIN EN 15534-1:2018-02 (E)

Compo sites made from cellulose-based materials and thermoplastics (usually called wood-polymer composites (WPC) or natural fibre composites (NFC)) - Part 1: Test methods for characterisation of compounds and products (includes Amendment A1:2017)

Contents

| | Page |
|---|------|
| European foreword..... | 5 |
| Introduction | 7 |
| 1 Scope..... | 8 |
| 2 Normative references..... | 8 |
| 3 Terms and definitions | 10 |
| 4 Test specimens..... | 11 |
| 5 Conditioning of test specimens | 11 |
| 5.1 General..... | 11 |
| 5.2 Reference conditioning..... | 11 |
| 5.3 Conditioning for factory production control and testing under other conditions | 12 |
| 5.4 Conditioning for tests performed by third-parties | 12 |
| 6 Physical properties..... | 12 |
| 6.1 Appearance (applicable to products) | 12 |
| 6.2 Density | 12 |
| 6.3 Moisture content | 12 |
| 6.4 Slipperiness..... | 13 |
| 6.4.1 General..... | 13 |
| 6.4.2 Pendulum test | 13 |
| 6.4.3 Inclination plan test | 13 |
| 6.4.4 Dynamic coefficient of friction | 14 |
| 6.5 Linear mass (applicable to profiles) | 14 |
| 6.5.1 Apparatus..... | 14 |
| 6.5.2 Test specimens..... | 15 |
| 6.5.3 Procedure..... | 15 |
| 6.5.4 Calculation and expression of results | 15 |
| 6.6 Dimensional characteristics..... | 15 |
| 6.6.1 Conditioning..... | 15 |
| 6.6.2 Thickness, width and length (applicable to profiles, only)..... | 15 |
| 6.6.3 Deviation from straightness (applicable to profiles, only) | 15 |
| 6.6.4 Cupping | 16 |
| 7 Mechanical properties..... | 16 |
| 7.1 Impact resistance | 16 |
| 7.1.1 Impact resistance (applicable to compounds) | 16 |
| 7.1.2 Falling mass impact resistance (applicable to products) | 17 |
| 7.1.3 Extreme temperatures | 20 |
| 7.2 Tensile properties (applicable to compounds)..... | 20 |
| 7.3 Flexural properties..... | 20 |
| 7.3.1 Flexural properties (applicable to compounds) | 20 |
| 7.3.2 Flexural properties (applicable to non-load bearing products)..... | 20 |
| 7.4 Creep behaviour (applicable to finished products for non-load bearing applications).... | 20 |
| 7.4.1 Known span in use..... | 20 |
| 7.4.2 Unknown span in use..... | 22 |
| 7.5 Resistance to indentation..... | 23 |

| | | |
|-----------|---|----|
| 7.5.1 | Principle | 23 |
| 7.5.2 | Apparatus | 23 |
| 7.5.3 | Test specimens | 23 |
| 7.5.4 | Test method | 23 |
| 7.6 | Nail and screw withdrawal | 24 |
| 7.7 | Pull through resistance | 24 |
| 8 | Durability | 25 |
| 8.1 | Resistance to artificial weathering | 25 |
| 8.1.1 | Test methods for artificial weathering | 25 |
| 8.1.2 | Methods for assessing of the resistance to artificial weathering | 25 |
| 8.1.3 | [A1] Determination of colorimetric coordinates [A1] | 25 |
| 8.2 | Resistance to natural ageing (external use) | 25 |
| 8.2.1 | Test methods for natural ageing | 25 |
| 8.2.2 | Methods for assessing the resistance to natural ageing | 26 |
| 8.3 | Moisture resistance | 26 |
| 8.3.1 | Swelling and water absorption | 26 |
| 8.3.2 | Moisture resistance under cyclic conditions | 28 |
| 8.3.3 | Moisture resistance – Boiling test | 29 |
| 8.4 | Resistance against termites | 29 |
| 8.5 | Resistance against biological agents | 30 |
| 8.5.1 | Pre-treatment | 30 |
| 8.5.2 | Resistance against basidiomycetes | 30 |
| 8.5.3 | Resistance against soft rotting micro-fungi | 33 |
| 8.5.4 | Resistance against discolouring micro-fungi according to ASTM D 3273 | 34 |
| 8.5.5 | Resistance against discolouring micro-fungi according to ISO 16869 | 36 |
| 8.5.6 | Resistance against discolouring algae | 37 |
| 8.6 | Resistance to salt spray | 38 |
| 9 | Thermal properties | 38 |
| 9.1 | Heat deflection temperature (HDT) | 38 |
| 9.2 | Linear thermal expansion | 38 |
| 9.3 | Heat reversion | 38 |
| 9.4 | Heat build-up (applicable to products) | 38 |
| 9.4.1 | Principle | 38 |
| 9.4.2 | Apparatus | 39 |
| 9.4.3 | Test specimens | 40 |
| 9.4.4 | Procedure | 40 |
| 9.4.5 | Expression of results | 40 |
| 9.4.6 | Test report | 41 |
| 9.5 | Oxygen index (OI) | 42 |
| 9.6 | Reaction to fire | 42 |
| 9.6.1 | Single flame source test | 42 |
| 9.6.2 | Single burning item (SBI) test (applicable to cladding only) | 42 |
| 9.6.3 | Radiant heat source test (floorings) | 48 |
| 10 | Other properties | 48 |
| 10.1 | Degree of chalking (applicable to coated products, only) | 48 |
| 10.2 | Change of gloss | 48 |
| 10.3 | Peel strength (applicable to profiles with laminated foil) | 48 |
| 10.3.1 | Principle | 48 |
| 10.3.2 | Apparatus | 49 |
| 10.3.3 | Preparation of test pieces | 49 |
| 10.3.4 | Conditioning | 50 |
| 10.3.5 | Procedure | 50 |

| | |
|---|-----------|
| 10.3.6 Test report..... | 50 |
| Annex A (normative) Determination of the modulus of elasticity in bending and bending strength of profiles | 52 |
| A.1 Principle | 52 |
| A.2 Apparatus..... | 52 |
| A.3 Test specimens..... | 53 |
| A.4 Atmosphere for conditioning and testing | 54 |
| A.5 Procedure..... | 54 |
| A.6 Expression of results..... | 55 |
| A.6.1 Modulus of elasticity in bending | 55 |
| A.6.2 Bending strength..... | 57 |
| A.7 Test report..... | 58 |
| Bibliography..... | 60 |