

ISO 24338:2022-03 (E)

Laminate floor coverings - Determination of abrasion resistance

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Apparatus	2
4.1	Testing machine (for method A and B) (see Figure 1)	2
4.1.1	Test specimen holder (for method A and B)	2
4.1.2	Holding and lifting device (for method A and B)	2
4.1.3	Rubber covered abrasive wheels (for method A)	2
4.1.4	Abrasive paper strips (for method A)	2
4.1.5	Calibration plates (for method A)	3
4.1.6	Suction device (for method A)	3
4.1.7	Revolution-counter (for method A and B)	3
4.2	Grit feeder and accessories (only for method B)	3
4.2.1	General	3
4.2.2	Vacuum cleaning device	4
4.2.3	Abrading material	6
4.2.4	Leather abrading wheels	6
4.2.5	Stopwatch	6
4.2.6	Grit collection container	6
4.2.7	Calibration plates	7
4.2.8	Transparent template to evaluate the wear of the abraded area	7
4.3	Additional material or equipment (method A and B)	7
4.3.1	Weighing equipment	7
4.3.2	Conditioning chamber	7
5	Test specimens	7
6	Procedure of method A	8
6.1	General	8
6.2	Preparation of test specimens and abrasive papers	8
6.3	Preparation of abrasive wheels	9
6.4	Determination of the abrasion rate of abrasive paper	9
6.5	Abrasion of test specimen	9
6.5.1	General	9
6.5.2	Abrasion evaluation method A - octants	9
6.6	Expression of results	10
6.7	Test report	10
7	Procedure of method B	10
7.1	General	10
7.2	Maintenance of the abrading wheels	10
7.3	Operation of the abrader	11
7.3.1	To start the wear test:	11
7.3.2	To halt the wear test:	11
7.4	Calibration	11
7.4.1	Rate of grit flow	11
7.4.2	Abrading capacity	11

7.5	Abrasion of test specimen	12
7.6	Expression of results	12
7.7	Test report	13
Annex A (normative) Calibration and maintenance of abrasion equipment		14
Annex B (normative) Measurement of shore A hardness		18
Bibliography		19