

# DIN EN 13141-10:2008-10 (E)

## Ventilation for buildings - Performance testing of components/products for residential ventilation - Part 10: Humidity controlled extract air terminal device

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>4</b>	<b>Symbols and abbreviations .....</b>	<b>5</b>
<b>5</b>	<b>Performance testing of aerodynamic and hygro-dynamic characteristics .....</b>	<b>6</b>
<b>5.1</b>	<b>Aero and hygro-dynamic performances .....</b>	<b>6</b>
<b>5.1.1</b>	<b>Principle .....</b>	<b>6</b>
<b>5.1.2</b>	<b>Test installation, conditions and uncertainty of measurement .....</b>	<b>6</b>
<b>5.1.3</b>	<b>Test procedure .....</b>	<b>8</b>
<b>5.1.4</b>	<b>Analysis of results .....</b>	<b>14</b>
<b>5.1.5</b>	<b>Test report .....</b>	<b>14</b>
<b>5.2</b>	<b>Other tests .....</b>	<b>14</b>
<b>5.2.1</b>	<b>Time response test .....</b>	<b>14</b>
<b>5.2.2</b>	<b>Performance testing of acoustic characteristics .....</b>	<b>15</b>
<b>Bibliography .....</b>		<b>16</b>