

DIN EN 15316-3-2:2008-06 (E)

Heating systems in buildings - Method for calculation of system energy requirements and system efficiencies - Part 3-2: Domestic hot water systems, distribution

Contents		Page
Foreword		4
Introduction		6
1	Scope	7
2	Normative references	7
3	Terms and definitions	7
4	Symbols, units and indices	10
5	Domestic hot water system characteristics	11
5.1	General	11
5.2	Single zone and single system	12
5.3	Single zone and multiple systems	12
5.4	Multiple zones with single system	13
6	Distribution thermal losses	13
6.1	Total distribution thermal losses	13
6.2	Thermal losses from individual distribution pipe section	14
6.2.1	General	14
6.2.2	Thermal losses from pipes based on dwelling area	14
6.2.3	Thermal losses from pipes based on pipe lengths and number of tappings per day	15
6.2.4	Thermal losses from pipes based on pipe lengths and distribution efficiencies	15
6.2.5	Thermal losses from pipes based on pipe lengths and tapping profiles	16
6.2.6	Thermal losses from pipes based on pipe lengths and average temperature	16
6.2.7	Heat energy lost due to wasted hot water	16
6.2.8	Time periods	16
6.3	Thermal losses from circulation loop	16
6.3.1	General	16
6.3.2	Thermal losses from circulation loop based on pipe length and a fixed value of heat loss	16
6.3.3	Thermal losses from circulation loop based on a physical approach	17
6.3.4	Additional thermal losses from circulation loop during periods of no circulation	17
6.3.5	Total thermal loss from circulation loop	17
6.4	Thermal losses due to accessories	18
6.5	User outlets	18
7	Auxiliary energy	18
7.1	Total auxiliary energy consumption	18
7.2	Auxiliary energy consumption for ribbon heating	18
7.3	Auxiliary energy consumption for pumps	19
7.3.1	General	19
7.3.2	Simplified method	19
7.3.3	Detailed calculation method	20
8	Recoverable, recovered and unrecoverable system losses	20
Annex A (informative)	Calculation of thermal losses from pipes based on pipe lengths and the number of tappings per day	22

Annex B (informative) Calculation of thermal losses from pipes based on pipe lengths and distribution efficiencies	24
Annex C (informative) Calculation of thermal losses from pipes based on pipe lengths and tapping profiles	26
Annex D (informative) Calculation of thermal losses from circulation loop	28
D.1 Calculation of thermal losses based on pipe length	28
D.2 Thermal losses based on a detailed calculation method	28
D.2.1 General	28
D.2.2 Determination of length of pipe sections	28
D.2.3 Determination of heat transfer coefficients	31
D.2.4 Tabulated method for calculation of linear thermal transmittance	33
D.2.5 Determination of average ambient temperature	34
D.2.6 Determination of average hot water temperature of pipe section	34
Annex E (informative) Calculation of thermal losses from user outlets	35
Annex F (informative) Calculation of auxiliary energy requirement of a circulation pump	36
F.1 Simplified method for calculation of auxiliary energy requirement of a circulation pump .	36
F.2 Detailed method for calculation of auxiliary energy requirement of a circulation pump	36
F.2.1 Hydraulic energy requirement	36
F.2.2 Hydraulic power required by the pump	36
F.2.3 Duration of the provision of domestic hot water	37
F.2.4 Pump performance coefficient	38
F.2.5 Intermittent pump operation	39
F.2.6 Expenditure value coefficient	39
F.3 Auxiliary energy recoverable factor	40
Bibliography	41