

DIN EN 13757-5:2009-01 (E)

Communication systems for meters and remote reading of meters - Part 5: Wireless relaying; English version EN 13757-5:2008

| Inhalt | Seite |
|---|-------|
| Foreword | 4 |
| 1 Scope | 5 |
| 2 Normative references | 5 |
| 3 Terms and definitions | 5 |
| 4 Explanation | 7 |
| 4.1 General | 7 |
| 4.2 Introduction | 7 |
| 4.3 Relaying | 8 |
| 4.4 Use of routers | 10 |
| 4.5 Use of gateways | 10 |
| 4.5.1 General | 10 |
| 4.5.2 Data duplication | 11 |
| 4.6 Use of power strobed units | 12 |
| 4.7 Error handling | 13 |
| 4.8 Time synchronisation | 13 |
| 4.9 Protocol possibilities | 14 |
| 5 Mode P, protocol using routers | 15 |
| 5.1 General | 15 |
| 5.2 Physical layer protocol | 15 |
| 5.2.1 General | 15 |
| 5.2.2 Transmitter | 16 |
| 5.2.3 Receiver | 17 |
| 5.3 Data encoding | 17 |
| 5.3.1 Manchester encoding | 17 |
| 5.3.2 Order of transmission of the encoded data | 17 |
| 5.3.3 Wake up and preamble chip sequences | 18 |
| 5.4 Data link layer protocol | 18 |
| 5.4.1 General | 18 |
| 5.4.2 Frame format | 18 |
| 5.4.3 C-field | 19 |
| 5.4.4 M- and A-fields | 21 |
| 5.4.5 The CI-field | 21 |
| 5.4.6 Message handling | 21 |
| 5.4.7 Timing requirements | 22 |
| 5.5 Network layer protocol | 23 |
| 5.5.1 General | 23 |
| 5.5.2 Network layer format | 23 |
| 5.5.3 Relaying rules | 24 |
| 5.6 Application layer protocol | 25 |
| 5.6.1 CI-field | 25 |
| 5.6.2 Error reporting services | 25 |
| 5.6.3 Network management service | 27 |
| 6 Mode R2, protocol using gateways | 32 |
| 6.1 General | 32 |
| 6.2 Physical layer protocols | 33 |
| 6.3 Data link layer protocol | 33 |
| 6.3.1 General | 33 |
| 6.3.2 M- and A-field | 33 |

| | | |
|-------|--|----|
| 6.3.3 | C-field | 33 |
| 6.3.4 | Timing requirements | 38 |
| 6.3.5 | Error handling | 38 |
| 6.4 | Network layer functionality | 38 |
| 6.4.1 | General..... | 38 |
| 6.4.2 | Downstream transfer | 38 |
| 6.4.3 | Downstream relaying rules | 39 |
| 6.4.4 | Upstream transfer | 40 |
| 6.4.5 | Upstream relaying rules | 40 |
| 6.5 | Application layer | 40 |
| 6.5.1 | CI-field | 40 |
| 6.5.2 | Network management services | 41 |
| 7 | Mode Q, protocol supporting precision timing | 47 |
| 7.1 | General..... | 47 |
| 7.2 | Physical layer protocol | 47 |
| 7.2.1 | General..... | 47 |
| 7.2.2 | Transmitter | 48 |
| 7.2.3 | Receiver | 49 |
| 7.3 | Data encoding | 49 |
| 7.3.1 | NRZ encoding..... | 49 |
| 7.3.2 | Order of transmission of the encoded data | 50 |
| 7.3.3 | Wake up and preamble bit sequences | 50 |
| 7.4 | Data link layer protocol | 50 |
| 7.4.1 | General..... | 50 |
| 7.4.2 | Frame format..... | 51 |
| 7.4.3 | Normal data link layer frame handling..... | 53 |
| 7.4.4 | Search link layer frame handling | 55 |
| 7.5 | Mode Q, network layer protocol | 56 |
| 7.5.1 | General..... | 56 |
| 7.5.2 | Network layer format | 57 |
| 7.5.3 | Address conversion rules..... | 59 |
| 7.5.4 | Routing rules | 59 |
| 7.5.5 | Timing requirements | 62 |
| 7.6 | Mode Q, application layer protocol..... | 62 |
| 7.6.1 | General..... | 62 |
| 7.6.2 | EN 13757-1 Application layer..... | 63 |
| 7.6.3 | Error reporting | 63 |
| 7.6.4 | Alarm reporting..... | 65 |
| 7.6.5 | Network management service | 66 |
| 7.6.6 | Timing requirements | 72 |
| 7.6.7 | COSEM extension | 72 |
| | Bibliography | 74 |