

# ISO/IEC 14908-2:2012-02 (E)

## Information technology - Control network protocol - Part 2: Twisted pair communication

---

| <b>Contents</b>                    |   | <b>Page</b> |
|------------------------------------|---|-------------|
| Introduction .....                 |   | 5           |
| 1                                  | Scope .....   | 7           |
| 2                                  | Normative references .....                                | 7           |
| 3                                  | Network overview .....                                    | 7           |
| 4                                  | System specifications .....                               | 7           |
| 4.1                                | General aspects .....                                     | 7           |
| 4.2                                | Cable .....   | 8           |
| 4.3                                | Topology .....  | 8           |
| 4.3.1                              | Free or bus topology .....                                | 8           |
| 4.3.2                              | Repeater .....  | 8           |
| 4.4                                | Cable Termination .....                                   | 8           |
| 4.4.1                              | Free-topology segment .....                               | 8           |
| 4.4.2                              | Bus topology segment .....                                | 8           |
| 4.5                                | Segment configuration .....                               | 9           |
| 4.6                                | Power specifications .....                                | 9           |
| 5                                  | Link power .....  | 9           |
| 5.1                                | General .....   | 9           |
| 5.2                                | Source .....  | 10          |
| 5.3                                | Power supply requirements .....                           | 10          |
| 5.4                                | Passive coupler circuit .....                             | 13          |
| 6                                  | Node specifications .....                                 | 14          |
| 6.1                                | Link power .....  | 14          |
| 6.2                                | Hot plugging .....  | 14          |
| 6.3                                | Transmitter/receiver interface to the MAC sub-layer ..... | 14          |
| 6.3.1                              | Physical layer protocol data unit .....                   | 14          |
| 6.3.2                              | Frame format .....  | 15          |
| 6.3.3                              | Transmit waveform .....                                   | 16          |
| 6.4                                | Impedance .....   | 19          |
| 7                                  | Communication parameters .....                            | 20          |
| Annex A (informative) .....        |   | 21          |
| Environmental specifications ..... |   | 21          |
| Bibliography .....                 |   | 22          |

## Figures

|   |    |
|---|----|
| Figure 1 — Termination.....   | 8  |
| Figure 2 — Link Power Source.....   | 10 |
| Figure 3 — Power supply output ripple voltage requirement .....           | 11 |
| Figure 4 — Power supply startup interval behavior .....                   | 12 |
| Figure 5 — Coupler circuit schematic.....                                 | 13 |
| Figure 6 — Physical layer protocol data unit .....                        | 15 |
| Figure 7 — Frame format for compliant transmitter. ....                   | 15 |
| Figure 8 — Idealised transmit waveform - zero bit.....                    | 16 |
| Figure 9 — Idealised transmit waveform - one bit.....                     | 17 |
| Figure 10 — Maximum voltage spectrum over frequency relative to peak..... | 18 |
| Figure 11 — Minimum impedance – powered and unpowered node .....          | 19 |

## Tables

|   |    |
|---|----|
| Table 1 — Bus-Topology Distance Specifications .....                    | 9  |
| Table 2 — Free-Topology distance specifications .....                   | 9  |
| Table 3 — Power supply requirements.....                                | 11 |
| Table 4 — Coupler circuit bill of materials .....                       | 14 |
| Table 5 — Link power requirements.....                                  | 14 |
| Table 6 — Communication parameters for interoperable transceiver .....  | 20 |
| Table A. 1 —Representative environmental specifications for nodes ..... | 21 |