

DIN EN 12977-3:2012-06 (E)

Thermal solar systems and components - Custom built systems - Part 3: Performance test methods for solar water heater stores

Contents	Page
Foreword	5
Introduction	6
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Symbols and abbreviations	11
5 Store classification	12
6 Laboratory store testing	13
6.1 Requirements on the testing stand	13
6.1.1 General	13
6.1.2 Measured quantities and measuring procedure	16
6.2 Installation of the store	17
6.2.1 Mounting	17
6.2.2 Connection	17
6.3 Test and evaluation procedures	17
6.3.1 General	17
6.3.2 Test sequences	19
6.3.3 Data processing of the test sequences	30
7 Store test combined with a system test according to ISO 9459-5	31
8 Store test according to EN 12897	32
9 Test report	32
9.1 General	32
9.2 Description of the store	32
9.3 Test results	33
9.4 Parameters for the simulation	34
Annex A (normative) Store model benchmark tests	35
A.1 General	35
A.2 Temperature of the store during stand-by	35
A.3 Heat transfer from heat exchanger to store	35
Annex B (normative) Verification of store test results	37
B.1 General	37
B.2 Test sequences for verification of store test results	37
B.2.1 General	37
B.2.2 Verification sequences from measurements on a store testing stand	37
B.2.3 Test sequences obtained during a whole system test according to ISO 9459-5	44
B.3 Verification procedure	44
B.3.1 General	44

B.3.2	Error in transferred energies	44
B.3.3	Error in transferred power	45
Annex C (normative) Benchmarks for the parameter identification		46
Annex D (informative) Requirements for the numerical store model		47
D.1	General	47
D.2	Assumptions	47
D.3	Calculation of energy balance	47
Annex E (informative) Determination of store parameters by means of "up-scaling" and "down-scaling"		49
E.1	General	49
E.2	Requirements	49
E.3	Determination of store parameters	50
E.3.1	Thermal capacity of store	50
E.3.2	Height of store	50
E.3.3	Determination of heat loss capacity rate	50
E.3.4	Relative heights of the connections and the temperature sensors	50
E.3.5	Heat exchangers	50
E.3.6	Parameter describing the degradation of thermal stratification during stand-by	51
E.3.7	Parameter describing the quality of thermal stratification during direct discharge	51
Annex F (informative) Determination of hot water comfort		52
Bibliography		53
Tables		
Table 1 -- Classification of the stores	12	
Table 2 -- Measuring data	16	
Table 3 -- Compilation of the test sequences	19	
Table 4 -- Flow rates and store inlet temperatures for Test C (group 1)	20	
Table 5 -- Flow rates and store inlet temperatures for Test C (group 2)	21	
Table 6 -- Flow rates and store inlet temperatures for Test C (group 3)	21	
Table 7 -- Flow rates and store inlet temperatures for Test C (group 4)	22	
Table 8 -- Flow rates and store inlet temperatures for Test L (group 1)	23	
Table 9 -- Flow rates and storage device inlet temperatures for Test L (group 2)	24	
Table 10 -- Flow rates and store inlet temperatures for Test L (group 3)	24	
Table 11 -- Flow rates and store inlet temperatures for Test L (group 4)	25	
Table 12 -- Flow rates and store inlet temperatures for Test NiA (group 2 or 4)	26	
Table 13 -- Flow rates and store inlet temperatures for Test EiA	27	
Table 14 -- Flow rates and storage device inlet temperatures for Test NA (groups 1 and 3)	28	
Table 15 -- Flow rates and store inlet temperatures for Test NB (group 1 and 3)	28	
Table 16 -- Flow rates and store inlet temperatures for Test NB (groups 2 and 4)	29	
Table 17 -- Flow rates and store inlet temperatures for Test EB	30	

Table A.1 -- Results of the analytical solution	36
Table B.1 -- Compilation of the verification sequences	38
Table B.2 -- Flow rates and storage device inlet temperatures for Test V (group 1)	39
Table B.3 -- Flow rates and storage device inlet temperatures for Test V (group 2)	40
Table B.4 -- Flow rates and storage device inlet temperatures for Test V (group 3)	41
Table B.5 -- Flow rates and storage device inlet temperatures for Test V (group 4)	42
Table B.6 -- Flow rates and storage device inlet temperatures for Test NiA (group 2 or 4)	43
Table B.7 -- Flow rates and storage device inlet temperatures for Test EiV	44
Figures Page Figure 1 -- Charge circuit of the store-testing stand	14
Figure 2 -- Discharge circuit of the store-testing stand	15
Figure A.1 -- Store considered as a twin tube heat exchanger	36