

DIN EN 16830:2017-06 (E)

Safety and control devices for burners and appliances burning gaseous or liquid fuels - Control functions in electronic systems - Temperature Control function

| Contents | | Page |
|-----------------------------------|-------------------------------------------------------------------------------|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| Figure 1 -- Standards house | | 5 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms and definitions | 7 |
| 4 | Classification | 8 |
| 4.1 | Classes of control | 8 |
| 4.2 | Groups of control | 8 |
| 4.3 | Classes of control functions | 8 |
| 4.4 | Types of DC supplied controls | 8 |
| 5 | Test conditions and measurement tolerances | 8 |
| 6 | Construction requirements | 8 |
| 6.1 | General | 8 |
| 6.2 | Mechanical parts of the control | 8 |
| 6.3 | Materials | 9 |
| 6.4 | Gas Connections | 9 |
| 6.5 | Electrical parts of the control | 9 |
| 6.5.1 | General | 9 |
| 6.5.2 | Switching elements | 9 |
| 6.5.3 | Electrical components | 9 |
| 6.6 | Protection against internal faults for the purpose of functional safety | 10 |
| 6.6.1 | Design and construction requirements | 10 |
| 6.6.2 | Class A | 10 |
| 6.6.3 | Class B | 10 |
| 6.6.4 | Class C | 11 |
| 6.6.5 | Circuit and construction evaluation | 11 |
| 6.7 | TTB | 11 |
| 6.7.1 | General | 11 |
| 6.7.2 | Threshold value | 11 |
| 6.8 | TCF | 12 |
| 7 | Performance | 12 |
| 7.1 | General | 12 |
| 7.2 | Leak-tightness | 12 |
| 7.3 | Test for leak-tightness | 12 |
| 7.4 | Torsion and bending | 12 |
| 7.5 | Torsion and bending tests | 12 |
| 7.6 | Rated flow rate | 12 |
| 7.7 | Test for rated flow rate | 13 |
| 7.8 | Durability | 13 |
| 7.8.1 | Elastomers in contact with gas | 13 |
| 7.8.2 | Marking | 13 |

| | | |
|-----------------------|-------------------------------------------------------------------------------------------------------------------|----|
| 7.8.3 | Resistance to scratching | 13 |
| 7.8.4 | Resistance to humidity | 13 |
| 7.9 | Performance tests for electronic controls | 13 |
| 7.9.1 | At ambient temperature | 13 |
| 7.9.2 | At minimum temperature | 13 |
| 7.9.3 | At maximum temperature | 13 |
| 7.10 | Long-term performance for electronic controls | 13 |
| 7.10.1 | General | 13 |
| 7.10.2 | Stress test | 13 |
| 7.10.3 | Long term performance test | 14 |
| 7.10.101 | TCF Sensing element(s) assembly | 14 |
| 7.10.102 | TTB Sensing element(s) assembly | 14 |
| 7.11 | Data exchange | 14 |
| 8 | Electrical requirements | 14 |
| 9 | Electromagnetic compatibility (EMC) | 15 |
| 10 | Marking, installation and operating instructions | 15 |
| 10.1 | Marking | 15 |
| 10.2 | Installation and operating instructions | 15 |
| 10.3 | Warning Notice | 15 |
| Annex A (informative) | Abbreviations and Symbols | 16 |
| Annex B (informative) | Leak-tightness test for gas controls - volumetric method | 17 |
| Annex C (informative) | Leak-tightness test for gas controls - pressure loss method | 18 |
| Annex D (normative) | Conversion of pressure loss into leakage rate | 19 |
| Annex E (normative) | Electrical/electronic component fault modes | 20 |
| Annex F (normative) | Additional requirements for safety accessories and pressure accessories as defined in EU Directive 97/23/EC | 21 |
| Annex G (normative) | Materials for pressurized parts | 22 |
| Annex H (normative) | Additional materials for pressurized parts | 23 |
| Annex I (normative) | Requirements for controls used in DC supplied burners and appliances burning gaseous or liquid fuels | 24 |
| Annex J (normative) | Method for the determination of a Safety Integrity Level (SIL) | 25 |
| Annex K (normative) | Method for the determination of a Performance Level (PL) | 26 |
| Annex L (informative) | Relationship between Safety Integrity Level (SIL) and Performance Level (PL) | 27 |
| Annex M (normative) | Reset functions | 28 |
| Annex N (informative) | Guidance document on Environmental Aspects | 29 |
| Annex O (normative) | Seals of elastomer, cork and synthetic fibre mixtures | 30 |
| Bibliography | | 31 |