

DIN EN 16798-7:2017-11 (En glisch)

Energy performance of buildings - Ventilation for buildings - Part 7: Calculation methods for the determination of air flow rates in buildings including infiltration (Modules M5-5)

Contents	Page
European foreword	6
Introduction	9
1 Scope	11
Table 1 -- Position of this standard (in casu M5-1, M5-5, M5-6, M5-8) within the modular structure of the set of EPB standards	12
2 Normative references	13
3 Terms and definitions	14
4 Symbols and subscripts	15
4.1 Symbols	15
Table 2 -- Symbols and units	15
4.2 Subscripts	17
Table 3 -- Subscripts	17
5 Brief description of the methods	18
5.1 Output of the methods	18
5.2 General description of the methods	18
5.3 Selection criteria between the methods	19
6 Calculation method, method 1 -- Determination of air flow rates based on detailed building characteristics	19
6.1 Output data	19
Table 4 -- Output data of method 1	19
6.2 Calculation intervals	20
6.3 Input data	20
6.3.1 General	20
6.3.2 Product data	21
Table 5 -- Product technical input data list	21
6.3.3 System design data	22
Table 6 -- Identifiers for VENT_SYS_OP	22
Table 7 -- Process design input data list	22
Table 8 -- Identifiers for SUP_AIR_TEMP_CTRL	24
Table 9 -- Identifiers for SUP_AIR_FLW_CTRL	24
6.3.4 Operating conditions	24
Table 10 -- Operating conditions data list	24

6.3.5	Constants and physical data	26
Table 11 --	Constants and physical data	26
6.3.6	Input data from Annex A (Annex B)	26
6.4	Calculation procedure, method 1	26
6.4.1	Applicable time intervals and states of operation	26
6.4.2	Operating conditions calculation	26
6.4.3	Calculation of air flow rates	28
7	Method 2 -- Determination of air flow rates based on statistical approach	38
7.1	Output data	38
Table 12 --	Output data of method 2	39
7.2	Calculation intervals	39
7.3	Input data	39
7.4	Calculation procedure, method 2	39
7.4.1	General	39
7.4.2	Description of the statistically based simplified method	40
7.4.3	Justification of the method	40
8	Quality control	40
9	Compliance check	41
Annex A (normative)	Input and method selection data sheet - Template	42
A.1	General	42
A.2	References	43
Table A.1 --	References	43
A.3	Input data method 1	43
A.3.1	Product description data	43
A.3.2	Product technical data	43
A.3.2.1	Discharge coefficient for vents, air terminal devices, windows	43
A.3.2.2	Airflow exponent for vents, air terminal devices, windows	43
A.3.2.3	Combustion air flows factors	44
Table A.2 --	Data for appliance system factor	44
Table A.3 --	Data for fuel flow factor	44
A.3.2.4	Mechanical ventilation	44
Table A.4 --	Values for f_{ctrl}	45
Table A.5 --	Values for f_{sys}	45
A.3.3	System design data	45
A.3.3.1	Supply air temperature control	45
A.3.3.2	Exposure to wind	45
Table A.6 --	Identifiers for SHIELD_CLASS	45
A.3.3.3	Pressure coefficients associated to an air flow path	45
Table A.7 --	Dimensionless wind pressures coefficients	46
Table A.8 --	Dimensionless wind pressures coefficients for ventilation zone that cannot be cross-ventilated ($f_{cross} = 0$)	46
A.3.3.4	Difference of wind pressure coefficients	46
A.3.3.5	Pressure coefficient of the cowl at roof height	46
A.3.3.6	Correction coefficient for accounting for height of cowl above roof level	46
Table A.9 --	Examples of $C_{cowl; height}$ values	47
A.3.3.7	Ventilation effectiveness	47

A.3.3.8	Airing factor	47
A.3.3.9	Cross-ventilation factor	47
Table A.10 -- Cross-ventilation factor		47
A.3.3.10	Number of window divisions	48
A.3.3.11	Stack effect in passive and hybrid duct	48
A.3.3.12	Distribution of vents	48
Table A.11 -- Distribution of vents		48
A.3.3.13	Reference pressure for the envelope airtightness index	48
A.3.3.14	Flow exponent through leaks	48
A.3.3.15	Leakage coefficient of the ventilation zone	48
A.3.3.16	Envelope leakage distribution	48
Table A.12 -- Envelope leakage distribution		48
A.3.3.17	Typical internal doorway area	49
A.3.4	Operating conditions data	49
A.3.4.1	Maximum wind speed for cross-ventilation calculation	49
A.3.4.2	Wind speed correction factors	49
Table A.13 -- Correction factor $C_{rgh;10;site}$		49
A.3.4.3	Ventilation system operation	49
Table A.14 -- Identifiers for VENT_SYS_OP		49
A.4	Input data method 2	49
Annex B (informative) Input and method selection data sheet - Default choices		50
B.1	General	50
B.2	References	51
Table B.1 --References		51
B.3	Input data method 1	51
B.3.1	Product description data	51
B.3.2	Product technical data	51
B.3.2.1	Discharge coefficient for vents, air terminal devices, windows	51
B.3.2.2	Airflow exponent for vents, air terminal devices, windows	52
B.3.2.3	Combustion air flows factors	52
Table B.2 -- Data for appliance system factor		52
Table B.3 -- Data for fuel flow factor		52
B.3.2.4	Mechanical ventilation	53
Table B.4 -- Values for f_{ctrl}		53
Table B.5 -- Values for f_{sys}		53
B.3.3	System design data	53
B.3.3.1	Supply air temperature control	53
B.3.3.2	Exposure to wind	54
Table B.6 -- Identifiers for SHIELD_CLASS		54
B.3.3.3	Pressure coefficients associated to an air flow path	54
Table B.7 -- Dimensionless wind pressures coefficients		54
Table B.8 -- Dimensionless wind pressures for ventilation zone that cannot be cross-ventilated ($f_{cross} = 0$)		54
B.3.3.4	Difference of wind pressure coefficients	54
B.3.3.5	Pressure coefficient of the cowl at roof height	55
B.3.3.6	Correction coefficient for accounting for height of cowl above roof level	55

Table B.9 -- Examples of C _{cowl} ; height values	55
B.3.3.7 Ventilation effectiveness	55
B.3.3.8 Airing factor	55
B.3.3.9 Cross-ventilation factor	55
Table B.10 -- Cross-ventilation factor	56
B.3.3.10 Number of window divisions	56
B.3.3.11 Stack effect in passive and hybrid duct	56
B.3.3.12 Distribution of vents	56
Table B.11 -- Distribution of vents	56
B.3.3.13 Reference pressure for the envelope airtightness index	57
B.3.3.14 Flow exponent through leaks	57
B.3.3.15 Leakage coefficient of the ventilation zone	57
B.3.3.16 Envelope leakage distribution	57
Table B.12 -- Envelope leakage distribution	57
B.3.3.17 Typical internal doorway area	58
B.3.4 Operating conditions data	58
B.3.4.1 Maximum wind speed for cross-ventilation calculation	58
B.3.4.2 Wind speed correction factors	58
Table B.13 -- Correction factor C _{rg} ; site	58
B.3.4.3 Ventilation system operation	58
Table B.14 -- Identifiers for VENT_SYS_OP	58
B.4 Input data method 2	58
Bibliography	59