DIN EN 16798-5-1:2017-11 (E)

Energy performance of buildings - Venti lation for buildings - Part 5-1: Calculation methods for energy requirements of ventilation and air conditioning systems (Modules M5-6, M5-8, M6-5, M6-8, M7-5, M7-8) - Method 1: Distribution and generation

Contents

Page

European foreword 4

Introduction 7

1 Scope 9

2 Normative references 11

3 Terms and definitions 12

4 Symbols and subscripts 13
4.1 Symbols 13
4.2 Subscripts 14

5 Brief description of the method 14
5.1 Output of the method 14
5.2 General description of the method 14

6 Calculation method 15
6.1 Output data 15
6.2 Calculation time interval 18
6.3 Input data 18
6.3.1 Source of data, general 18
6.3.2 Product data 18
6.3.3 System design data 24
6.3.4 Operating conditions 29
6.3.5 Constants and physical data 30
6.3.6 Input data from Annex A (Annex B) 31
6.4 Calculation procedure 31
6.4.1 Applicable time intervals 31
6.4.2 Distribution calculation 31
6.4.3 Generation calculation 35

7 Quality control 54

8 Compliance check 54

Annex A (normative) Input and method selection data sheet -- Template 55

A.1 General 55
A.2 References 56
A.3 Product description data 56
A.4 Product technical data 56
A.4.1 Duct tightness class 56
A.4.2 Air handling unit tightness class 56
A.4.3 Heat recovery leakage and outdoor air factors 57
A.4.4 Nominal heat recovery temperature efficiency and constants for the velocity dependence 57
A.4.5 Humidity recovery efficiency and constants for the calculation 58

A.4.6 Value for adiabatic cooling humidifier efficiency 58
A.4.7 Values for cooling and heating coil calculation 58
A.4.8 Air handling unit related values 59
A.4.9 Specific pump energy for humidification 59
A.5 System design data 60
A.5.1 Qualitative process design data choices 60
A.5.2 Fan motor heat recovery factors 60
A.5.3 Quantitative process design data choices 60
A.5.4 Limit values for the defrost control 61
A.5.5 Process control options 61
A.5.6 Heat recovery control options 61

Annex B (informative) Input and method selection data sheet -- Default choices 62

B.1 General 62
B.2 References 62
B.3 Product description data 63
B.4 Product technical data 63
B.4.1 Duct tightness class 63
B.4.2 Air handling unit tightness class 64
B.4.3 Heat recovery leakage and outdoor air factors 64
B.4.4 Nominal heat recovery temperature efficiency and constants for the velocity dependence 64
B.4.5 Humidity recovery efficiency and constants for the calculation 65
B.4.6 Value for adiabatic cooling humidifier efficiency 65
B.4.7 Values for cooling and heating coil calculation 65
B.4.8 Air handling unit related default values 66
B.4.9 Specific pump energy for humidification 66
B.5 System design data 67
B.5.1 Qualitative process design data choices 67
B.5.2 Fan motor heat recovery factors 67
B.5.3 Quantitative process design data choices 67
B.5.4 Limit values for the defrost control 68
B.5.5 Control options 68
B.5.6 Heat recovery control options 68

Annex C (normative) Calculation method for ground preheating and -cooling 70

C.1 Calculation 70
C.1.1 Temperature difference 70
C.1.2 Moisture difference 71
C.1.3 Pressure losses of the heat exchanger 72
C.2 Data 72

Annex D (informative) Calculation method for rotary heat exchangers 73

D.1 Calculation 73
D.1.1 Heat recovery 73
D.1.2 Moisture recovery 73
D.2 Data 75

Bibliography 76