

DIN EN 16798-5-1:2017-11 (E)

Energy performance of buildings - Ventilation for buildings - Part 5-1: Calculation methods for energy requirements of ventilation and air conditioning systems (Modules M5-6, M5-8, M6-5, M6-8, M7-5, M7-8) - Method 1: Distribution and generation

Contents		Page
European foreword		4
Introduction		7
1	Scope	9
2	Normative references	11
3	Terms and definitions	12
4	Symbols and subscripts	13
4.1	Symbols	13
4.2	Subscripts	14
5	Brief description of the method	14
5.1	Output of the method	14
5.2	General description of the method	14
6	Calculation method	15
6.1	Output data	15
6.2	Calculation time interval	18
6.3	Input data	18
6.3.1	Source of data, general	18
6.3.2	Product data	18
6.3.3	System design data	24
6.3.4	Operating conditions	29
6.3.5	Constants and physical data	30
6.3.6	Input data from Annex A (Annex B)	31
6.4	Calculation procedure	31
6.4.1	Applicable time intervals	31
6.4.2	Distribution calculation	31
6.4.3	Generation calculation	35
7	Quality control	54
8	Compliance check	54
Annex A (normative) Input and method selection data sheet -- Template		55
A.1	General	55
A.2	References	56
A.3	Product description data	56
A.4	Product technical data	56
A.4.1	Duct tightness class	56
A.4.2	Air handling unit tightness class	56
A.4.3	Heat recovery leakage and outdoor air factors	57
A.4.4	Nominal heat recovery temperature efficiency and constants for the velocity dependence	57
A.4.5	Humidity recovery efficiency and constants for the calculation	58

A.4.6	Value for adiabatic cooling humidifier efficiency	58
A.4.7	Values for cooling and heating coil calculation	58
A.4.8	Air handling unit related values	59
A.4.9	Specific pump energy for humidification	59
A.5	System design data	60
A.5.1	Qualitative process design data choices	60
A.5.2	Fan motor heat recovery factors	60
A.5.3	Quantitative process design data choices	60
A.5.4	Limit values for the defrost control	61
A.5.5	Process control options	61
A.5.6	Heat recovery control options	61
Annex B (informative) Input and method selection data sheet -- Default choices		62
B.1	General	62
B.2	References	62
B.3	Product description data	63
B.4	Product technical data	63
B.4.1	Duct tightness class	63
B.4.2	Air handling unit tightness class	64
B.4.3	Heat recovery leakage and outdoor air factors	64
B.4.4	Nominal heat recovery temperature efficiency and constants for the velocity dependence	64
B.4.5	Humidity recovery efficiency and constants for the calculation	65
B.4.6	Value for adiabatic cooling humidifier efficiency	65
B.4.7	Values for cooling and heating coil calculation	65
B.4.8	Air handling unit related default values	66
B.4.9	Specific pump energy for humidification	66
B.5	System design data	67
B.5.1	Qualitative process design data choices	67
B.5.2	Fan motor heat recovery factors	67
B.5.3	Quantitative process design data choices	67
B.5.4	Limit values for the defrost control	68
B.5.5	Control options	68
B.5.6	Heat recovery control options	68
Annex C (normative) Calculation method for ground preheating and -cooling		70
C.1	Calculation	70
C.1.1	Temperature difference	70
C.1.2	Moisture difference	71
C.1.3	Pressure losses of the heat exchanger	72
C.2	Data	72
Annex D (informative) Calculation method for rotary heat exchangers		73
D.1	Calculation	73
D.1.1	Heat recovery	73
D.1.2	Moisture recovery	73
D.2	Data	75
Bibliography		76