DIN EN 12831-1:2017-09 (E)

Energy performance of buildings - Method for calculation of the design heat load - Part 1: Space heating load, Module M3-3

Contents

Page

European foreword 5

Introduction 6

1 Scope 8

2 Normative references 12

3 Terms and definitions 12

4 Symbols and abbreviations 15
4.1 Symbols 15
4.2 Subscripts 16

5 Description of the methods 19

6 Standard method - Heat load of rooms, building entities and buildings 20
6.1 Output data 20
6.2 Input data 21
6.3 Calculation procedure 27
6.3.1 Design heat load 27
6.3.2 Design transmission heat losses of a heated space (i) 29
6.3.3 Design ventilation heat loss 33
6.3.4 Additional heating-up power in intermittently heated spaces 41
6.3.5 Time constant 42
6.3.6 Heat transfer coefficients without temperature adjustment 43
6.3.7 External design temperature (climatic data) 44
6.3.8 Influence of the heat emission system in high rooms (ceiling height 4 m) 46

7 Simplified method for the calculation of the design heat load of a heated space (single rooms) 48
7.1 Output data 48
7.2 Input data 48
7.3 Calculation procedure 49
7.3.1 Design heat load of a heated space 49
7.3.2 Design transmission heat loss of a heated space 50
7.3.3 Design ventilation heat loss of a heated space 50

8 Simplified method for the calculation of the building design heat load 51
8.1 Output data 51
8.2 Input data 51
8.3 Calculation procedure 52
8.3.1 Building design heat load 52
8.3.2 Building design transmission heat loss 53
8.3.3 Design ventilation heat loss of a building 53

9 Compliance check 54
9.1 General 54
9.2 Dimensioning of heat emission systems 54
9.3 Dimensioning of heat generators 54

Annex A (normative) Input data, structure for default values 55

A.1 General 55
A.2 Input data for the standard method (6) 55
A.2.1 Consideration of thermal bridges 55
A.2.2 Correction of U-values for the influence of building element properties and meteorological conditions 55
A.2.3 Heat loss through the ground 55
A.2.4 Temperature adjustment for heat loss to unheated spaces 56
A.2.5 Internal temperatures of adjacent building entities 56
A.2.6 Influence of the heat emission system in high rooms 56
A.2.7 Specific thermal storage capacity ceff 57
A.2.8 Specific properties of air 57
A.2.9 Volume flow ratio between room (i) and zone (z) 58
A.2.10 Air tightness 58
A.2.11 Minimum air change rate 58
A.2.12 Coefficient for the volume flow ratio fqv,z 59
A.2.13 Estimation of design data of external ATDs 59
A.2.14 Pressure exponent for leakages 59
A.2.15 Adjustment factor for the orientation of the zone (orientation factor) 59
A.2.16 Adjustment factor for the number of exposed facades 60
A.2.17 Air volume flow through large openings 60
A.2.18 Additional heating-up power in intermittently heated spaces hu 60
A.2.19 Heat gains gain 60
A.3 Input data for the simplified methods (7, 8) 60
A.3.1 Ratio between external and internal surface areas 60
A.3.2 Thermal bridges 61
A.3.3 Temperature correction factor fx 61
A.3.4 Air change rate 61
A.4 Input data for the standard method and the simplified methods 61
A.4.1 Climatic data 61
A.4.2 Internal design temperature 64
A.4.3 Simplified determination of U-Values 64

Annex B (informative) Input data, default values 65

B.1 General 65
B.2 Input data for the standard method (6) 65
B.2.1 Consideration of thermal bridges 65
B.2.2 Correction of U-values for the influence of building element properties and meteorological conditions 65
B.2.3 Heat loss through the ground 65
B.2.4 Temperature adjustment for heat loss to unheated spaces 66
B.2.5 Internal temperatures of adjacent building entities 66
B.2.6 Influence of the heat emission system in high rooms 66
B.2.7 Specific thermal storage capacity ceff 67
B.2.8 Specific properties of air 68
B.2.9 Volume flow ratio between room (i) and zone (z) 68
B.2.10 Air tightness 68
B.2.11 Coefficient for the volume flow ratio fqv,z 69
B.2.12 Estimation of design data of external ATDs 70
B.2.13 Pressure exponent for leakages 71
B.2.14 Adjustment factor for the orientation of the zone (orientation factor) 71
B.2.15 Adjustment factor for the number of exposed facades 71
B.2.16 Air volume flow through large openings 71
B.2.17 Additional heating-up power in intermittently heated spaces hu 71
B.2.18 Heat gains gain 71
B.3 Input data for the simplified methods (7, 8) 71
B.3.1 Ratio between external and internal surface areas 71
B.3.2 Thermal bridges 72
B.3.3 Temperature correction factor fx 72
B.3.4 Air change rate 72

B.4 Input data for the standard method and the simplified methods 72
B.4.1 Climatic data 72
B.4.2 Internal design temperature 73
B.4.3 Simplified determination of U-Values 74

Annex C (informative) Detailed consideration of thermal bridges 77

Annex D (informative) Internal temperatures u of adjacent building entities or adjacent unheated spaces within the same building 78

Annex E (informative) Equivalent thermal transmittance of building elements against ground 81

Annex F (informative) Estimation of heating-up power in intermittently heated spaces (6.3.4) 84

F.1 General 84
F.2 Determination of the specific heating-up power hu,i based on the time of disuse 86
F.3 Determination of the specific heating-up power hu,i based on the internal temperature drop during setback 87

Annex G (informative) External air volume flow through large openings 89

Bibliography 94