

# ISO 21773:2021 (E)

## Methods of test and characterization of performance for energy recovery components

---

### Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	Metrics
5.1	General
5.2	Effectiveness
5.3	Pressure drop
5.3.1	Measured pressure drop
5.3.2	Standardized pressure drop
5.4	Recovery efficiency ratio
5.5	Outside air correction factor
5.6	Exhaust air transfer ratio
5.7	Sensible energy transfer rate for the supply airstream
5.8	Humidity transfer rate for the supply airstream
5.9	Total energy transfer rate for the supply airstream
6	General test requirements
6.1	Test apparatus
6.2	Installation
6.3	Static pressures
6.4	Instrument calibration
7	Effectiveness tests
7.1	Test requirements
7.2	Stability limits when testing effectiveness
7.3	Data collection period
7.4	Data sampling rates
7.5	Temperature and humidity conditions: inlets to exchanger
7.6	Test temperature limits
8	Pressure drop tests
9	Leakage tests
9.1	General test requirements
9.2	Outside air correction factor
9.3	Exhaust air transfer ratio
10	Uncertainty limits
10.1	General
10.2	Uncertainty limits for effectiveness tests
10.3	Uncertainty limits for RER
10.4	Uncertainty limits for measured pressure drop tests
10.5	Uncertainty limits for leakage tests
11	Inequality limits
11.1	General

- 11.2 Inequality limits for thermal tests
- 11.3 Inequality limits for leakage tests
- 12 Reporting of test results
  - 12.1 Pressure drop test results
  - 12.2 Leakage test results
  - 12.3 Thermal test results
  - 12.4 Uncertainties
- Annex A (informative) Example of test data collection and calculation of metrics
- Annex B (informative) Best practices
  - B.1 Measure test system duct leakage
  - B.2 Transitions between test system ducts and exchanger
  - B.3 Insulation of test system ducts and transitions
  - B.4 Mixing of outlet airstream
- Annex C (informative) Expression of performance metrics for use in calculation of system performance
  - C.1 General
  - C.2 Heat transfer effectiveness
  - C.3 Latent transfer effectiveness
  - C.4 measured pressure drop
  - C.5 Recovery efficiency ratio
  - C.6 Outside air correction factor and exhaust air transfer ratio
  - C.7 Sensible energy transfer rate
  - C.8 Humidity transfer rate
  - C.9 Energy transfer rate
  - C.10 Temperature change in the supply airstream
  - C.11 Humidity change in the supply airstream
- Annex D (informative) Inequality limits for use when condensate flow rate can be measured
- Annex E (informative) Expressions, used in other standards, related to effectiveness as defined in this document
  - E.1 Identification of similar metrics
  - E.2 Enthalpy recovery ratio
  - E.3 Temperature or humidity efficiency
  - E.4 Recovery efficiency ratio
  - E.5 Relationships between the metrics
  - E.6 Comparison of advantages of the metrics

Page count: 44