

DIN EN 15632-3:2022-08 (E)

District heating pipes - Factory made flexible pipe systems - Part 3: Non bonded system with plastic service pipes; requirements and test methods

| Contents | | Page |
|---|--|-------------|
| European foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 7 |
| 4 | Classification | 7 |
| 4.1 | Operating temperatures and service life | 7 |
| 4.2 | Design pressures | 7 |
| 5 | Requirements | 8 |
| 5.1 | General requirements | 8 |
| 5.2 | Service pipes, fittings and their connections | 8 |
| 5.2.1 | Quality of service pipes, fittings and their connections | 8 |
| 5.2.2 | Oxygen tightness of service pipes | 11 |
| 5.3 | Sealing in linear direction of pipe assemblies | 11 |
| 5.4 | Water vapour permeation of pipe assemblies | 11 |
| 6 | Test procedures | 11 |
| 6.1 | General | 11 |
| 6.2 | Thermal cycling test | 12 |
| Annex A (informative) Application of Miner's Rule - Calculation of the calculated design life of PB-H, PE-X and Multilayer piping systems | | 13 |
| A.1 | General | 13 |
| A.2 | Considerations for multilayer piping systems | 15 |
| Annex B (informative) Guideline for inspection and testing | | 16 |
| Bibliography | | 18 |