

DIN EN 1434-1:2023-03 (E)

Thermal energy meters - Part 1: General requirements

| Contents | | Page |
|-----------------|--|-------------|
| | European foreword | 4 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Types of instruments | 12 |
| 4.1 | General | 12 |
| 4.2 | Complete instrument | 12 |
| 4.3 | Combined instrument | 12 |
| 4.4 | Hybrid instrument | 12 |
| 4.5 | Sub-assemblies of a thermal energy meter, which is a combined instrument | 12 |
| 4.5.1 | General | 12 |
| 4.5.2 | Flow sensor | 12 |
| 4.5.3 | Temperature sensor pair | 12 |
| 4.5.4 | Calculator | 12 |
| 4.6 | Equipment under test (EUT) | 13 |
| 5 | Rated operating conditions | 13 |
| 5.1 | Limits of temperature range | 13 |
| 5.2 | Limits of temperature differences | 13 |
| 5.3 | Limits of flow rate | 13 |
| 5.4 | Limit of thermal power | 13 |
| 5.5 | Limits of working pressure (PS and Pmin) | 14 |
| 5.6 | Nominal pressure (PN) | 14 |
| 5.7 | Limits in ambient temperature | 14 |
| 5.8 | Limits in deviations in supply voltage | 14 |
| 5.9 | Maximum pressure loss | 14 |
| 5.10 | Specific requirements on registration devices | 14 |
| 5.10.1 | General | 14 |
| 5.10.2 | Suitability | 14 |
| 5.10.3 | Rated operated conditions | 15 |
| 5.10.4 | Indication | 15 |
| 5.10.5 | MPE for additional functionalities (smart metering functionality) | 16 |
| 6 | Technical characteristics | 16 |
| 6.1 | Materials and construction | 16 |
| 6.2 | Requirements outside the limiting values of the flow rate | 17 |
| 6.3 | Display | 17 |
| 6.4 | Protection against fraud | 18 |
| 6.5 | Supply voltage | 18 |
| 6.6 | Effect on temperature sensor pairs by mounting in pockets | 18 |
| 6.7 | Reproducibility | 18 |
| 6.8 | Repeatability | 19 |
| 6.9 | Software | 19 |
| 7 | Specified working range | 19 |
| 7.1 | General | 19 |
| 7.2 | Temperature difference | 19 |
| 7.3 | Flow rate | 19 |

| | | |
|------------------------|---|----|
| 8 | Heat transmission formula | 19 |
| 9 | Metrological characteristics (Maximum Permissible Error, MPE) | 20 |
| 9.1 | General | 20 |
| 9.2 | Values of maximum permissible errors | 20 |
| 9.2.1 | Maximum permissible relative errors of complete thermal energy meters | 20 |
| 9.2.2 | Maximum permissible relative error of sub-assemblies | 21 |
| 9.3 | Application of maximum permissible errors | 21 |
| 10 | Environmental classification | 22 |
| 10.1 | General | 22 |
| 10.2 | Environmental class A (Domestic use, indoor installations) | 22 |
| 10.3 | Environmental class B (Domestic use, outdoor installations) | 22 |
| 10.4 | Environmental class C (Industrial installations) | 22 |
| 10.5 | Mechanical classes M1 to M3 | 22 |
| 11 | Thermal energy meter specification | 23 |
| 11.1 | General | 23 |
| 11.2 | Flow sensor | 23 |
| 11.3 | Temperature sensor pair | 24 |
| 11.4 | Calculator | 25 |
| 11.5 | Complete meters | 26 |
| 12 | Information to be made available by the manufacturer or supplier | 28 |
| 12.1 | Installation instructions | 28 |
| 12.2 | Parameter setting instructions | 29 |
| 12.3 | Adjustment instructions | 30 |
| 12.4 | Maintenance instructions | 30 |
| 12.5 | Information required when a thermal energy meter is taken out of service for recycling and/or disposal | 31 |
| 12.5.1 | General | 31 |
| 12.5.2 | Disassembly | 31 |
| 12.5.3 | Recycling | 31 |
| 12.5.4 | Disposal | 31 |
| Annex A (normative) | Heat coefficient formulae | 32 |
| A.1 | Water | 32 |
| A.2 | Heat-conveying liquids other than water | 34 |
| Annex B (normative) | Flow conditioner package | 35 |
| Annex C (normative) | Fast response meters | 37 |
| Annex ZA (informative) | Relationship between this European Standard and the essential requirements of Directive 2014/32/EU aimed to be covered | 38 |
| Bibliography | | 42 |