

DIN EN 15698-2:2025-07 (E)

District heating pipes - Bonded twin pipe systems for directly buried hot water networks - Part 2: Factory made fitting and valve assemblies of steel service pipes, polyurethane thermal insulation and one casing of polyethylene

Contents		Page
European foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Requirements	7
4.1	General	7
4.2	Steel parts	7
4.2.1	Specification	7
4.2.2	Valves	7
4.2.3	Diameter and wall thickness	7
4.2.4	Surface condition	7
4.3	Welding of steel parts	8
4.3.1	Welding of steel service pipes and elements	8
4.3.2	Welding of fixing bars	8
4.3.3	Placing of the fixing bars	8
4.4	Casing	8
4.5	Polyurethane foam thermal insulation	8
4.6	Fitting and valve assemblies	8
4.6.1	General	8
4.6.2	Thermal insulation series	8
4.6.3	End alignment of flow and return steel service pipes	9
4.6.4	Distance between flow and return steel service pipes	9
4.6.5	End of fitting and valve assemblies	9
4.6.6	Polyethylene welding	10
4.6.7	End of stem construction	10
4.6.8	Tolerances of the main fitting and valve dimensions	10
4.7	Expected thermal life and long-term temperature resistance	10
4.8	Thermal conductivity	10
4.9	Surface conditions at delivery	10
4.10	Measuring wires for surveillance systems	10
4.11	Resistance of the valves to axial forces and bending moments	10
4.12	Installation, operation and maintenance	10
5	Test methods	11
6	Marking	11
6.1	General	11
6.2	Steel service pipe	11
6.3	Fitting	11
6.4	Casing	11
6.5	Fitting assembly	11
6.6	Valves and valve assembly	11
6.7	Service valves and service valve assemblies	11

Annex A (informative) Guidelines for inspection and testing	12
Annex B (informative) Waste treatment and recycling	14
Annex C (informative) Examples of twin pipe fitting assemblies	15
Bibliography	18