

DIN EN 15698-1:2025-07 (E)

District heating pipes - Bonded twin pipe systems for directly buried hot water networks - Part 1: Factory made twin pipe assembly of steel service pipes, polyurethane thermal insulation and one casing of polyethylene

| Contents | | Page |
|---|--|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Requirements | 6 |
| 4.1 | Steel service pipe | 6 |
| 4.1.1 | Specification | 6 |
| 4.1.2 | Diameter and wall thickness | 7 |
| 4.1.3 | Surface condition | 7 |
| 4.2 | Casing | 7 |
| 4.3 | Polyurethane foam thermal insulation | 7 |
| 4.4 | Twin pipe assembly | 7 |
| 4.4.1 | General | 7 |
| 4.4.2 | Thermal insulation series | 7 |
| Table 1 -- Casing diameters | | 8 |
| 4.4.3 | End alignment of flow and return steel service pipes | 8 |
| 4.4.4 | Distance between flow and return steel service pipes | 8 |
| Table 2 -- Distance between steel service pipes | | 9 |
| 4.4.5 | Twisting of steel service pipes | 9 |
| Figure 1 -- Twisting, w, and distance between steel service pipes, Lp | | 10 |
| 4.4.6 | Centre line deviation | 10 |
| Table 3 -- Centre line deviation related to nominal outside diameters | | 10 |
| 4.4.7 | Ends of twin pipe assembly | 10 |
| 4.4.8 | Expected thermal life and long-term temperature resistance | 11 |
| 4.4.9 | Axial shear strength | 11 |
| 4.4.10 | Thermal conductivity in unaged condition | 11 |
| 4.4.11 | Impact resistance | 11 |
| 4.4.12 | Surface conditions at delivery | 11 |
| 4.4.13 | Linear water tightness | 11 |
| 4.4.14 | Measuring wires for surveillance systems | 11 |
| 5 | Test methods | 11 |
| 5.1 | General | 11 |
| 5.2 | Test specimens | 11 |
| Figure 2 -- Areas for test specimens | | 12 |
| 5.3 | Polyurethane foam thermal insulation | 12 |
| 5.4 | Twin pipe assembly | 12 |
| 5.4.1 | Axial shear strength | 12 |

| | |
|---|-----------|
| Figure 3 -- Axial shear test arrangement | 13 |
| 5.4.2 Expected thermal life and long-term temperature resistance | 14 |
| 5.4.3 Thermal conductivity in unaged condition | 14 |
| 5.4.4 Thermal conductivity at artificially aged condition | 14 |
| 5.4.5 Impact resistance | 14 |
| 5.4.6 Linear water tightness | 14 |
| 6 Marking | 14 |
| Annex A (informative) Guidelines for inspection and testing | 15 |
| A.1 General | 15 |
| A.2 Manufacturer's type test | 15 |
| A.3 Manufacturer's quality control | 15 |
| A.4 Additional inspection | 15 |
| Table A.1 -- Twin pipe assembly inspection | 16 |
| Annex B (informative) Waste treatment and recycling | 17 |
| Bibliography | 18 |