

# DIN EN 253:2006-02 (E)

District heating pipes - Preinsulated bonded pipe systems for directly buried hot water networks - Pipe assembly of steel service pipe, polyurethane thermal insulation and outer casing of polyethylene

---

<b>Contents</b>		<b>Page</b>
Introduction .....		6
1	Scope .....	8
2	Normative references .....	8
3	Terms and definitions .....	9
4	Requirements .....	10
4.1	General .....	10
4.2	Steel service pipe .....	11
4.2.1	Quality .....	11
4.2.2	Diameter .....	11
4.2.3	Wall thickness .....	11
4.2.4	Surface condition .....	13
4.3	Casing .....	13
4.3.1	Material properties .....	13
4.3.2	Casing properties .....	14
4.4	Polyurethane rigid foam insulation (PUR) .....	16
4.4.1	Composition .....	16
4.4.2	Cell structure .....	16
4.4.3	Foam density .....	16
4.4.4	Compressive strength .....	17
4.4.5	Water absorption at elevated temperature .....	17
4.5	Pipe assembly .....	17
4.5.1	Pipe ends .....	17
4.5.2	Diameter and wall thickness of the casing .....	17
4.5.3	Centre line deviation .....	18
4.5.4	Expected thermal life and long term temperature resistance .....	18
4.5.5	Thermal conductivity in unaged condition .....	18
4.5.6	Impact resistance .....	18
4.5.7	Creep behaviour .....	19
4.5.8	Surface conditions at delivery .....	19
5	Test methods .....	19
5.1	General .....	19
5.1.1	Test specimens .....	19
5.2	Casing .....	19
5.2.1	Material density .....	19
5.2.2	Dimensions .....	20
5.2.3	Appearance and surface finish .....	20
5.2.4	Heat reversion .....	20
5.2.5	Long-term mechanical properties .....	20
5.2.6	Constant load tensile test (CLT) .....	20
5.2.7	Elongation at break .....	20
5.2.8	Carbon black dispersion, homogeneity .....	22
5.2.9	Notched constant load test .....	22
5.3	Polyurethane rigid foam insulation (PUR) .....	22
5.3.1	Composition .....	22

5.3.2	Cell structure .....	22
5.3.3	Foam density .....	23
5.3.4	Compressive strength .....	23
5.3.5	Water absorption .....	23
5.4	Pipe assembly .....	24
5.4.1	Axial shear strength .....	24
5.4.2	Tangential shear strength .....	25
5.4.3	Shear strength of the pipe assembly after ageing .....	26
5.4.4	Thermal conductivity .....	27
5.4.5	Impact resistance .....	27
5.4.6	Creep behaviour at 140 °C .....	27
6	Marking .....	30
6.1	General .....	30
6.2	Steel service pipe .....	30
6.3	Casing .....	30
6.4	Pipe assembly .....	30
Annex A (informative) Relation between actual continuous operating conditions and accelerated ageing test conditions .....		31
Annex B (informative) Calculation of the minimum expected thermal life with operation at various temperatures with respect to PUR foam performance .....		33
Annex C (normative) Calculated continuous operating temperature (CCOT) .....		34
C.1	General .....	34
C.2	Symbols .....	34
C.3	Ageing and shear strength determinations .....	34
C.4	Calculations .....	35
C.4.1	Determination of the thermal life at different ageing temperatures .....	35
C.4.2	Adoption to the Arrhenius relation .....	35
C.4.3	Calculated continuous operating temperature, CCOT .....	35
Annex D (informative) Guidelines for inspection and testing .....		36
D.1	Manufacturer's type test .....	36
D.2	Manufacturer's quality surveillance .....	36
D.3	External inspection .....	36
D.4	Manufacturer's responsibility .....	36
Annex E (informative) Change of blowing agent and influence on thermochemical and thermomechanical properties of polyurethane rigid foam (PUR) .....		39
Annex F (normative) Radial creep behaviour of the polyurethane foam (PUR) .....		40
Annex G (normative) Thermal conductivity of pre-insulated pipes - Test procedure .....		41
G.1	Scope .....	41
G.2	Requirements (EN ISO 8497:1994, Clause 5) .....	41
G.2.1	Test specimen (EN ISO 8497:1994, 5.1) .....	41
G.2.2	Operating temperature (EN ISO 8497:1994, 5.2) .....	41
G.2.3	Types of apparatus (EN ISO 8497:1994, 5.5) .....	41
G.3	Apparatus (EN ISO 8497:1994, Clause 7) .....	41
G.3.1	Guarded end apparatus .....	41
G.3.2	Calibrated end apparatus .....	42
G.3.3	Dimensions (EN ISO 8497:1994, 7.2) .....	42
G.3.4	Heater pipe surface temperature .....	42
G.4	Test specimens (EN ISO 8497:1994, Clause 8) .....	42
G.4.1	Conditioning (EN ISO 8497:1994, 8.4) .....	42
G.4.2	Dimension measurement (EN ISO 8497:1994, 8.5) .....	42
G.4.3	Surface temperature measurement .....	42

<b>G.5</b>	<b>Procedure (EN ISO 8497:1994, Clause 9)</b> .....	<b>42</b>
<b>G.5.1</b>	<b>Test length (EN ISO 8497:1994, 9.1.1)</b> .....	<b>42</b>
<b>G.5.2</b>	<b>Diameter (EN ISO 8497:1994, 8.5)</b> .....	<b>43</b>
<b>G.5.3</b>	<b>Thickness of casing</b> .....	<b>43</b>
<b>G.5.4</b>	<b>Ambient requirements (EN ISO 8497:1994, 9.2)</b> .....	<b>43</b>
<b>G.5.5</b>	<b>Test pipe temperature (EN ISO 8497:1994, 9.3)</b> .....	<b>43</b>
<b>G.5.6</b>	<b>Power supply (EN ISO 8497:1994, 7.9)</b> .....	<b>43</b>
<b>G.5.7</b>	<b>Axial heat loss (EN ISO 8497:1994, 5.7)</b> .....	<b>43</b>
<b>G.5.8</b>	<b>Test period and stability (EN ISO 8497:1994, 9.5.3)</b> .....	<b>43</b>
<b>G.6</b>	<b>Calculations (EN ISO 8497:1994, Clause 11)</b> .....	<b>43</b>
<b>G.6.1</b>	<b>Thermal conductivity (EN ISO 8497:1994, 3.5)</b> .....	<b>43</b>
<b>G.7</b>	<b>Symbols and units (EN ISO 8497:1994 Clause 4)</b> .....	<b>44</b>
<b>Annex H (informative) National A-deviations</b> .....		<b>46</b>
<b>H.1</b>	<b>Swedish national legislative deviations on steel service pipes</b> .....	<b>46</b>
<b>Bibliography</b> .....		<b>47</b>