

DIN EN 1434-2:2007-05 (E)

Heat meters - Part 2: Constructional requirements

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Temperature sensors | 5 |
| 3.1 | General | 5 |
| 3.2 | Mechanical design | 6 |
| 3.2.1 | General | 6 |
| 3.2.2 | Materials of temperature probe sheath and pocket | 6 |
| 3.2.3 | Dimensions of direct mounted short probes - Type DS | 6 |
| 3.2.4 | Dimensions of direct mounted long probes - Type DL | 6 |
| 3.2.5 | Dimensions of pocket mounted long probes - Type PL | 9 |
| 3.2.6 | Dimensions of temperature pocket | 9 |
| 3.2.7 | Design of short probes with respect to installation | 11 |
| 3.2.8 | Design of long probes with respect to installation | 11 |
| 3.3 | Platinum temperature sensor | 12 |
| 3.3.1 | Specialised definitions for 2 wire temperature probes | 12 |
| 3.3.2 | Resistance characteristics | 13 |
| 3.3.3 | Signal leads | 14 |
| 3.3.4 | Temperature sensors for the 2-wire method | 14 |
| 3.3.5 | Temperature sensors for the 4-wire method | 14 |
| 3.3.6 | Thermal response time | 15 |
| 3.4 | Other temperature sensors | 15 |
| 4 | Flow sensors | 15 |
| 4.1 | Maximum admissible working pressure, PS in bar | 15 |
| 4.2 | Sizes and dimensions | 15 |
| 4.3 | Test signal output | 17 |
| 4.4 | Adjusting device | 17 |
| 5 | Calculators | 17 |
| 5.1 | Mechanical dimensions for calculators for domestic use | 17 |
| 5.2 | Terminals - specification and identification | 18 |
| 5.2.1 | General | 18 |
| 5.2.2 | Terminals for signal leads | 18 |
| 5.2.3 | Terminals for connection to the mains supply | 19 |
| 5.3 | Batteries | 20 |
| 5.4 | Dynamic behaviour | 20 |
| 5.5 | Test signal output | 20 |
| 5.6 | 24 h interruption in supply voltage | 20 |
| 6 | Complete meter | 20 |
| 7 | Interfaces between sub-assemblies | 20 |
| 7.1 | Definitions for pulse device interfaces | 21 |
| 7.1.1 | General | 21 |
| 7.1.2 | Electrical connection | 21 |
| 7.1.3 | Classification of pulse output devices | 21 |
| 7.1.4 | Timing and electrical parameters for pulse output devices (other than test signals) | 22 |
| 7.1.5 | Classification of pulse input devices | 22 |

| | | |
|--|---|----|
| 7.1.6 | Timing and electrical parameter for pulse input devices | 23 |
| 7.1.7 | Compatibility | 23 |
| 8 | Marking and security seals | 24 |
| 8.1 | Marking | 24 |
| 8.1.1 | General | 24 |
| 8.1.2 | Temperature sensor pairs | 24 |
| 8.1.3 | Pockets | 24 |
| 8.1.4 | Flow sensor | 24 |
| 8.1.5 | Calculator | 25 |
| 8.1.6 | Complete meter | 25 |
| 8.2 | Sites for marking | 26 |
| 8.3 | Security seals | 26 |
| Annex A (informative) Examples of temperature sensors | | 27 |
| Annex B (normative) Input and output test signals | | 36 |
| Annex C (informative) Low voltage Power Supply for heat meters and their sub-assemblies | | 39 |
| C.1 | Remote supply | 39 |
| C.1.1 | Voltage (DC or AC) | 39 |
| C.1.2 | Current available | 39 |
| C.1.3 | Cabling requirements | 39 |
| C.2 | Local external DC supply | 39 |
| C.2.1 | Voltage | 39 |
| C.2.2 | Other data | 40 |
| C.3 | Power supply specifications | 40 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2004/22/EC, MID | | 41 |
| Bibliography | | 42 |