

DIN EN 88-2:2008-03 (E)

Pressure regulators and associated safety devices for gas appliances - Part 2: Pressure regulators for inlet pressures above 500 mbar up to and including 5 bar

Contents		Page
Foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
3.1	Pressure regulator	7
3.2	Components	7
3.3	Safety shut-off devices	9
3.4	Control variables	10
3.4.1	Reference values	10
3.4.2	Variables in the controlling process	11
3.4.3	Possible values of all variables	11
3.4.4	Terms pertinent to the controlled variable	12
3.5	Operating features in stable conditions	12
3.6	Features pertinent to accuracy	14
3.7	Features pertinent to lock-up behaviour	15
3.8	Further functional terminology	16
3.8.1	Pressures pertinent to design of gas pressure regulator	16
4	Classification	17
5	Units of measurement and test conditions	17
5.1	Units of measurement	17
5.2	Test conditions	17
6	Construction requirements	18
6.1	General	18
6.2	Construction	18
6.2.1	General	18
6.2.2	Breather holes	18
6.2.3	External visual Indication of the position of the closure member	18
6.2.4	Parts transmitting actuating forces	19
6.2.5	Pressure adjustment	19
6.3	Materials	19
6.3.1	General	19
6.3.2	Springs	19
6.3.3	Requirements for elastomers (including vulcanized rubbers)	19
6.4	Gas connections	19
6.4.1	General	19
6.4.2	Connection sizes	19
6.4.3	Threads	20
6.4.4	Pressure test nipples (applicable only for outlet connections operating at 7 Performance requirements	20
7.1	General	20
7.2	Strength of housings	20
7.2.1	Requirement	20

7.2.2	Performance test	21
7.3	External and internal leak tightness	21
3.8.2	nominal pressure	17
3.8.3	operating temperature range	17
500	mbar)	20
7.4	Torsion and bending	21
7.5	Control classification	21
7.5.1	General	21
7.5.2	Control classifications for pressure regulators	21
7.5.3	Safety shut-off device accuracy group for over-pressure	22
7.6	Safety devices	22
7.6.1	Over-pressure safety shut-off device	22
7.6.2	Under-pressure safety shut-off devices	23
7.6.3	Bypass	23
7.6.4	Response time	23
7.7	Durability of performance	23
7.7.1	Pressure regulator	23
7.7.2	Safety slam-shut device	23
8	Marking, installation and operating instructions	24
8.1	Marking	24
8.2	Installation, operating and servicing instructions	24
8.3	Warning notice	25
regulators	26
A.1	Main components of a pressure regulator	26
A.2	Main components of a gas safety shut-off device	27
6.4.3)	29
C.1	General	30
C.2	Apparatus and test rig	30
C.3	Performance tests under stable conditions	32
C.3.1	General	32
C.3.2	Determination of a performance curve	34
C.3.3	Determination of the lock-up pressure	35
C.3.4	Regulator accuracy class	36
C.4	Safety shut-off device accuracy group	37
C.4.1	General conditions and apparatus	37
C.4.2	Test at ambient temperature	39
C.4.3	Test at the limit temperatures between 0 °C and 60 °C	39
C.4.4	Verification of the upper limit of the highest set range	40
C.4.5	Response time	40
C.5	Durability of performance	41
C.5.1	General	41
C.5.2	Pressure regulator	41
C.5.3	Safety shut-off devices	42
Requirements of EU Directive 90/396/EEC	43
Bibliography	45
Annex A (informative) Main components for direct acting and pilot controlled pressure	Annex B	
(informative) Use of ISO 7-1 and EN ISO 228-1 threads for gas connections (see Annex	ZA	
ZA (informative) Relationship between this European Standard and the Essential Annex	C	
C (normative) Performance test methods		30