

# ISO/IEC 7811-8:2008-03 (E)

## Identification cards - Recording technique - Part 8: Magnetic stripe - Coercivity of 51,7 kA/m (650 Oe)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Conformance .....</b>	<b>1</b>
<b>3</b>	<b>Normative references .....</b>	<b>1</b>
<b>4</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>5</b>	<b>Physical characteristics of the identification card .....</b>	<b>3</b>
5.1	Magnetic stripe area warpage .....	3
5.2	Surface distortions .....	4
<b>6</b>	<b>Physical characteristics of the magnetic stripe .....</b>	<b>4</b>
6.1	Height and surface profile of the magnetic stripe area .....	4
6.2	Surface roughness .....	7
6.3	Adhesion of stripe to card .....	7
6.4	Wear of magnetic stripe from read/write head .....	7
6.5	Resistance to chemicals .....	7
<b>7</b>	<b>Performance characteristics for the magnetic material .....</b>	<b>7</b>
7.1	General .....	7
7.2	Testing and operating environment .....	7
7.3	Signal amplitude requirements for magnetic media .....	8
<b>8</b>	<b>Encoding technique .....</b>	<b>9</b>
<b>9</b>	<b>Encoding specification, general .....</b>	<b>9</b>
<b>10</b>	<b>Error detection .....</b>	<b>9</b>
<b>11</b>	<b>Location of encoded tracks .....</b>	<b>9</b>