ISO/IEC 18000-3:2008-09 (E)

Information technology - Radio frequency identification for item management - Par t 3: Parameters for air interface communications at 13,56 MHz

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Conformance 1
2.1 Claiming conformance 1

3 Normative references 1

4 Terms and definitions 2

5 Symbols and abbreviated terms 2

6 Requirements: Physical layer, collision management system and protocol values for 13,56 MHz systems 2
6.0 General and applicable to both Modes of this part of ISO/IEC 18000 2
6.0.1 Presentation as determined in ISO/IEC 18000-1 2
6.0.2 ISO/IEC 18000-3 Interoperability 2
6.0.3 ISO/IEC 18000-3 reader conformance/compliance 3
6.0.4 ISO/IEC 18000-3 tag compliance 3
6.0.5 Command structure and extensibility 3
6.0.6 Mandatory commands 3
6.0.7 Optional commands 3
6.0.8 Custom commands 3
6.0.9 Proprietary commands 3
6.1 Physical layer, collision management system and protocols for MODE 1 of this part of ISO/IEC 18000 4
6.1.1 Read/Write system 4
6.1.2 Normative Aspects 4
6.1.3 Conformance and performance measurement aspects 4
6.1.4 Physical Layer 4
6.1.5 Protocol and collision management operating method 4
6.1.6 Commands 4
6.1.7 Parameter tables for interrogator to tag link 4
6.1.8 Parameter tables for tag to interrogator link 4
6.2 MODE 2: Physical layer, collision management system and protocols for MODE 2 of this part of ISO/IEC 18000 4
6.2.1 Normative aspects: physical and media access control (MAC) parameters: interrogator to tag link 5
6.2.2 Tag to interrogator link 7
6.2.3 Description of operating method 10
6.2.4 Protocol parameters 16
6.2.5 Description of protocol operating method 16
6.2.6 Collision management parameters 33
6.2.7 Description of collision management parameters operating method (informative) 33
6.2.8 Tag order sequencing 41
6.2.9 Commands 41
6.2.10 Air interface application layer 41
6.2.11 Optional Functionality 41

7 Marking of equipment 44

8 Table of characteristic differences between the MODES specified in this part of ISO/IEC 18000 44

Annex A (normative) Phase jitter modulation (PJM) 45

Annex B (informative) Known possible interferences between the MODES determined in this part of ISO/IEC 18000 49

Annex C (informative) Interrogator pseudo-code for collision management (Mode 1) 50

Annex D (informative) Cyclic Redundancy Check (CRC) (16 bit) 51

D.1 The CRC error detection method 51

C.2 CRC calculation example 51

Annex E (informative) Cyclic redundancy check (CRC) mode 2 (32 bit) 53

E.1 The CRC 32 error detection method 53
E.2 CRC 32 calculation example 53
E.3 Practical example of CRC 32 calculation 55

Annex F (informative) Mode 1 IC reference 56

Annex G (informative) A description of Mode 1 based on the ISO/IEC 15693 protocol as used for Item Management 57

G.1 Parameter tables for interrogator to tag link 57
G.2 Parameter tables for tag to interrogator link 62
G.3 Description of operating method 66
G.3.1 Communications signal interface interrogator to tag 66
G.3.2 Modulation 66
G.3.3 Data rate and data coding 67
G.3.4 Interrogator to tag frames 70
G.3.5 Communications signal interface tag to interrogator 71
G.4 Protocol parameters 75
G.4.1 Table of protocol parameters 75
G.5 Description of protocol operating method 80
G.5.1 Definition of data elements 80
G.5.2 Data storage format identifier (DSFID) 82
G.5.3 CRC 82
G.5.4 Overall protocol description 83
G.5.5 Modes 84
G.5.6 Response format 86
G.5.7 RF tag states 88
G.6 Collision management 90
G.7 Description of collision management operating method (Informative) 95
G.7.1 Request parameters 95
G.7.2 Request processing by the RF tag 96
G.7.3 Explanation of a collision management sequence 98
G.7.4 Timing specifications 100
G.8 Commands 102
G.8.1 Command types 102
G.8.2 Command codes 103
G.8.3 Mandatory commands 104
G.8.4 Optional commands 105
G.8.5 Custom commands 120
G.8.6 Proprietary commands 121

Bibliography 122