# ISO/IEC 18000-4:2008-09 (E)

## Information technology - Radio frequency identification for item management - Part 4: Parameters for air interface communications at 2,45 GHz

## Contents

Page


Foreword ..... iv

Introduction ..... v

1 Scope ..... 1

2 Normative references ..... 1

3 Terms and definitions ..... 2

4 Symbols and abbreviated terms ..... 2

5 2,45 GHz RFID protocols that support this part of ISO/IEC 18000 ..... 3
5.1 General ..... 3
5.1.1 Protocols ..... 3
5.1.2 Frequency ..... 3
5.1.3 Tag identification number ..... 4
5.1.4 Potential interference ..... 4
5.2 MODE 1: Passive backscatter RFID system ..... 4
5.2.1 MODE 1: Physical and media access control (MAC) parameters ..... 5
5.2.2 Physical layer and data coding ..... 10
5.2.3 Protocol and collision arbitration ..... 20
5.3 MODE 2: Long range high data rate RFID system ..... 47
5.3.1 MODE 2: Physical and media access control (MAC) parameters ..... 47
5.3.2 Modulation and coding ..... 52
5.3.3 General system description ..... 55
5.3.4 Frame structure ..... 55
5.3.5 CCC 6.2.5 Channel coding and sequences ..... 77
5.3.6 Command set for the command slot channel: CS-CH (only for R/W-tag) ..... 78

6 Table of characteristic differences between the modes specified in this part of ISO/IEC 18000 ..... 82

Annex A (informative) Mode 1: Memory Map ..... 83

A.1 Tag memory map ..... 83
A.2 Unique identifier ..... 83
A.3 Manufacturer ID and tag hardware ..... 85
A.4 Tag Memory layout ..... 86
A.5 Application (USER) memory ..... 88

Annex B (informative) Mode 1: CRC ..... 89

B.1 Interrogator to tag and tag to interrogator CRC-16 ..... 89
B.2 CRC calculation examples ..... 90

Annex C (normative) Mode 2: Memory Map ..... 93

C.1 Tag Memory map ..... 93
C.2 Tag Serial number - UserTagID ..... 94
C.3 Tag manufacturer's identifiers - MfrTagID ..... 95

**Annex D (informative) Mode 2: CRC ..... 96**

**D.1 Cyclic redundancy check (CRC) ..... 96**
**D.2 CRC calculation example ..... 96**

**Bibliography ..... 98**