

ISO/IEC 25434:2008-12 (E)

Information technology - Data interchange on 120 mm and 80 mm optical disk using +R DL format - Capacity: 8,55 Gbytes and 2,66 Gbytes per side (recording speed up to 16X)

Contents		Page
Foreword		viii
Introduction		ix
1	Scope	1
2	Conformance	1
2.1	Optical Disk	1
2.2	Generating system	1
2.3	Receiving system	2
2.4	Compatibility statement	2
3	Normative references	2
4	Terms and definitions	2
5	Conventions and notations	5
5.1	Representation of numbers	5
5.2	Names	5
6	Abbreviated terms	6
7	General description of the optical disk	6
8	General Requirements	7
8.1	Environments	7
8.1.1	Test environment	7
8.1.2	Operating environment	8
8.1.3	Storage environment	8
8.1.4	Transportation	8
8.2	Safety requirements	8
8.3	Flammability	8
8.4	Light fastness	8
9	Reference Drive	9
9.1	Optical system	9
9.2	Optical beam	9
9.3	Read channel 1	10
9.4	Disk clamping	10
9.5	Rotation of the disk	11
9.6	Wobble channel (Read channel 2)	11
9.7	Tracking channel (Read channel 2)	11
9.8	Reference servo systems	11
9.8.1	Normalized servo transfer function	11
9.8.2	Reference Servo for Axial Tracking	12
9.8.3	Reference Servo for Radial Tracking	13
10	Dimensional characteristics	14
10.1	Reference Planes	15

10.2	Overall dimensions	16
10.3	First transition area	16
10.4	Second transition area	17
10.5	Clamping Zone	17
10.6	Third transition area	17
10.7	Information Zone	17
10.7.1	Sub-division of the Information Zone	18
10.7.2	Track mode	19
10.8	Rim area	19
10.9	Remark on tolerances	19
11	Mechanical characteristics	19
11.1	Mass	19
11.2	Moment of inertia	19
11.3	Dynamic imbalance	19
11.4	Axial runout	19
11.4.1	Tracking requirements at the Reference velocity (CLV)	20
11.4.2	Tracking requirements at 3 000 RPM (CAV)	20
11.5	Radial runout	20
11.5.1	Tracking requirements at the Reference velocity (CLV)	20
11.5.2	Tracking requirements at 3 000 RPM (CAV)	21
12	Optical characteristics in the Information Zone	21
12.1	Index of refraction	21
12.2	Thickness of the substrate	22
12.3	Reflectivity	22
12.4	Birefringence	22
12.5	Angular deviation	22
13	Data format	24
13.1	Data Frames	24
13.1.1	Identification Data (ID)	24
13.1.2	ID Error Detection Code (IED)	25
13.1.3	RSV	26
13.1.4	Error Detection Code (EDC)	26
13.2	Scrambled Frames	26
13.3	ECC Blocks	27
13.4	Recording Frames	28
13.5	Modulation and NRZI conversion	29
13.6	Physical Sectors	30
13.7	Layout of a Recording UNit (RUN)	31
13.7.1	Recording Unit position	32
13.8	d.c. component suppression control	32
14	Track format	33
14.1	Track shape	33
14.2	Track path	34
14.3	Track pitch	34
14.4	Track layout	34
14.4.1	ADIP information	34
14.4.2	Physical format information in ADIP	37
15	General description of the Information Zone	66
16	Layout of the Information Zone of a Single-session disk	67
16.1	Usage of the Data Zone	68
16.1.1	Additional Testing Zone on Layer 1 (optional)	69
16.2	Physical Sector Numbers (PSNs)	70
17	Inner Drive Areas	71
17.1	Initial Zone / Final Zone	71
17.2	Inner Disk Test Zones	72
17.3	Count Zone Run-in / Dummy Zone	72
17.4	Inner Disk Count Zones	72
17.5	Inner Disk Administration Zone	72
17.6	Table of Contents (TOC) Zone	73
17.6.1	Table of Contents Blocks	73
17.6.2	Recorded Area Indicators (optional)	77
18	Lead-in Zone	78

18.1	Guard Zone 1	79
18.2	Reserved Zone 1	79
18.3	Reserved Zone 2	79
18.4	Inner Disk Identification Zone	79
18.5	Reserved Zone 3	79
18.6	Reference Code Zone	80
18.7	Buffer Zone 1	80
18.8	Control Data Zone	80
18.8.1	Physical format information	80
18.8.2	Disk manufacturing information	83
18.8.3	Content provider information	83
18.9	Buffer Zone 2	83
19	Data Zone	83
20	Middle Zones	83
20.1	Buffer Zones 3	85
20.2	Reserved Zones	85
20.3	Guard Zones 2	85
21	Outer Drive Areas	85
21.1	Outer Disk Administration Zones	85
21.2	Outer Disk Count Zones	86
21.3	Dummy Zone / Count Zone Run-in	87
21.4	Outer Disk Test Zone	87
21.5	Guard Zones 3	87
22	Lead-out Zone	87
22.1	Lead-out Zone at finalization	87
22.2	Lead-out Zone at closing of first Session	88
23	Multi-session Layout	89
23.1	Intro	90
23.1.1	Buffer Zone A	90
23.1.2	Inner Session Identification Zone	90
23.1.3	Session Control Data Zone	90
23.1.4	Buffer Zone B	90
23.2	Data Zone	90
23.3	Closure	90
23.3.1	Buffer Zone C	90
23.3.2	Outer Session Identification Zone	90
24	Sequential recording in Fragments	91
24.1	Opening a Session	91
24.1.1	Incomplete Fragment	91
24.1.2	Reserved Fragments	91
24.1.3	Recording User Data in Fragments	92
24.1.4	Closing a Fragment	92
24.2	Closing a Session	93
24.2.1	Lead-in/Intro Zone	93
24.2.2	Closure Zone	94
24.3	Finalizing the disk	94
25	Assignment of Logical Sector Numbers (LSNs)	94
26	Disk Control Blocks	94
26.1	General format of Disk Control Blocks	94
26.2	Format of the Session DCB (SDCB)	96
26.2.1	Session Items	98
27	General	100
28	Method of testing	100
28.1	Environment	100
28.2	Reference Drive	100
28.2.1	Optics and mechanics	100
28.2.2	Read power	101
28.2.3	Read channels	101
28.2.4	Tracking	101
28.3	Definition of signals	101
29	Characteristics of the groove signals	102

29.1	Phase depth	102
29.2	Push-pull signal	102
29.3	Track Cross signal	102
29.4	Normalized wobble signal	102
29.5	Characteristics of the wobble	103
30	Method of testing	103
30.1	Environment	103
30.2	Reference Drive	103
30.2.1	Optics and mechanics	103
30.2.2	Read power	103
30.2.3	Read channels	104
30.2.4	Tracking	104
30.2.5	Scanning velocity	104
30.3	Write conditions	104
30.3.1	Write pulse waveform	104
30.3.2	Write power	105
30.3.3	Write power dependency on wavelength	105
30.3.4	Write power window	106
30.3.5	Write power shift for layer L1 due to recording on layer L0	107
30.4	Measurement conditions	107
31	Characteristics of the recorded signals	107
31.1	Channel bit length	107
31.2	Definition of signals	107
31.2.1	High frequency signals (HF)	107
31.2.2	Modulated amplitude	108
31.2.3	Signal asymmetry	108
31.2.4	Normalized Slicing Level jump	108
31.2.5	Jitter	109
31.2.6	Track Cross signal	109
31.3	Read stability	109
32	Additional testing conditions	109
32.1	Test environment	109
32.1.1	Optics	109
32.2	Definition of signals	110
32.2.1	Modulated amplitude	110
32.2.2	Signal asymmetry	110
32.2.3	Jitter	110
32.2.4	Track Cross signal	110
32.2.5	Differential phase tracking error signal	111
32.2.6	Tangential push-pull signal	112
33	Quality of the recording layer	112
33.1	Defects	112
33.2	Data errors	112
34	Method of testing	113
34.1	Environment	113
34.2	Reference Drive	113
34.2.1	Optics and mechanics	113
34.2.2	Read power	113
34.2.3	Read channels	113
34.2.4	Error correction	114
34.2.5	Tracking	114
35	Minimum quality of a Recording Unit	114
35.1	Tracking	114
35.2	User-written data	114
Annex A (normative) 80 mm +R DL disk		115
Annex B (normative) Structure for Extended format information in the Data Zone		119
Annex C (normative) Measurement of light reflectivity		122

Annex D (normative) Measurement of birefringence	124
Annex E (normative) Measuring conditions for operation signals	127
Annex F (normative) Measurement of the differential phase tracking error	130
Annex G (normative) The write pulse wave form for testing	134
Annex H (normative) 8-to-16 Modulation	140
Annex I (normative) Optimum Power Control and Recording Conditions	148
Annex J (informative) Running OPC	151
Annex K (informative) Wavelength dependency	152
Annex L (informative) Explanation about the usage of the reference servos	157
Annex M (informative) Measurement of the groove wobble amplitude	167
Annex N (informative) Light fastness of the disk	169
Annex O (informative) Transportation	170
Annex P (informative) Video Content Protection System	171
Annex Q (informative) How to use the Physical format information in ADIP	172
Annex R (informative) Values to be Implemented in Existing and Future Specifications	174
Bibliography	177