

ISO/IEC 22535:2009-04 (E)

Information technology - Telecommunications and information exchange between systems - Corporate telecommunication networks - Tunnelling of QSIG over SIP

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Abbreviated terms	3
5	Background and architecture	3
5.1	Architecture	3
5.2	Basic operation	4
5.3	QSIG connectionless transport	5
5.4	Late availability of SDP parameters at the egress gateway	5
6	Procedures	5
6.1	General	5
6.2	Encapsulation of QSIG messages in SIP messages	5
6.3	QSIG SETUP message handling at an ingress gateway	6
6.3.1	Sending a SIP INVITE request	6
6.3.2	Receipt of responses to the INVITE request	6
6.4	QSIG SETUP message handling at an egress gateway	7
6.4.1	Receiving a SIP INVITE request	7
6.4.2	Rejecting a QSIG message in an INVITE request	8
6.5	Subsequent QSIG messages	8
6.6	Terminating the SIP dialog	8
6.7	QSIG connectionless message handling at an ingress gateway	9
6.7.1	Sending a SIP INVITE request	9
6.7.2	Receipt of responses to the INVITE request	9
6.8	QSIG connectionless message handling at an egress gateway	10
7	Example message sequences	10
7.1	Call establishment	10
7.2	Call clearing	11
7.3	QSIG connectionless message	12
7.4	Call establishment with port=0 in first SDP answer	13
7.5	Backwards compatibility with early editions	14
8	Security considerations	16
Annex A (informative)	Changes from early editions	17
Bibliography		19