

ISO/IEC 17344:2009-06 (E)

Information technology - Data interchange on 120 mm and 80 mm optical disk using +R format - Capacity: 4,7 Gbytes and 1,46 Gbytes per side (recording speed up to 16X)

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | viii |
| Introduction | | ix |
| 1 | Scope | 1 |
| 2 | Conformance | 1 |
| 2.1 | Optical disk | 1 |
| 2.2 | Generating system | 1 |
| 2.3 | Receiving system | 2 |
| 2.4 | Compatibility statement | 2 |
| 3 | Normative references | 2 |
| 4 | Terms and definitions | 2 |
| 5 | Conventions and notations | 4 |
| 5.1 | Representation of numbers | 4 |
| 5.2 | Names | 5 |
| 6 | Abbreviated terms | 5 |
| 7 | General description of the optical disk | 6 |
| 8 | General Requirements | 7 |
| 8.1 | Environments | 7 |
| 8.1.1 | Test environment | 7 |
| 8.1.2 | Operating environment | 7 |
| 8.1.3 | Storage environment | 7 |
| 8.1.4 | Transportation | 7 |
| 8.2 | Safety requirements | 8 |
| 8.3 | Flammability | 8 |
| 8.4 | Light fastness | 8 |
| 9 | Reference Drive | 8 |
| 9.1 | Optical system | 8 |
| 9.2 | Optical beam | 9 |
| 9.3 | Read channel 1 | 9 |
| 9.4 | Disk clamping | 9 |
| 9.5 | Rotation of the disk | 10 |
| 9.6 | Wobble channel (Read channel 2) | 10 |
| 9.7 | Tracking channel (Read channel 2) | 11 |
| 9.8 | Reference servo systems | 11 |
| 9.8.1 | Normalized servo transfer function | 11 |
| 9.8.2 | Reference Servo for Axial Tracking | 11 |
| 9.8.3 | Reference Servo for Radial Tracking | 12 |
| 10 | Dimensional characteristics | 14 |
| 10.1 | Reference Planes | 14 |

| | | |
|--------|---|----|
| 10.2 | Overall dimensions | 15 |
| 10.3 | First transition area | 15 |
| 10.4 | Second transition area | 16 |
| 10.5 | Clamping Zone | 16 |
| 10.6 | Third transition area | 16 |
| 10.7 | Information Zone | 16 |
| 10.8 | Rim Area | 17 |
| 10.9 | Remark on tolerances | 17 |
| 11 | Mechanical characteristics | 17 |
| 11.1 | Mass | 17 |
| 11.2 | Moment of inertia | 17 |
| 11.3 | Dynamic imbalance | 17 |
| 11.4 | Axial runout | 17 |
| 11.4.1 | Tracking requirements at the Reference velocity (CLV) | 17 |
| 11.4.2 | Tracking requirements at 3 000 RPM (CAV) | 18 |
| 11.5 | Radial runout | 18 |
| 11.5.1 | Tracking requirements at the Reference velocity (CLV) | 18 |
| 11.5.2 | Tracking requirements at 3 000 RPM (CAV) | 19 |
| 12 | Optical characteristics in the Information Zone | 19 |
| 12.1 | Index of refraction | 19 |
| 12.2 | Thickness of the substrate | 19 |
| 12.3 | Reflectivity | 20 |
| 12.4 | Birefringence | 20 |
| 12.5 | Angular deviation | 20 |
| 13 | Data format | 21 |
| 13.1 | Data Frames | 21 |
| 13.1.1 | Identification Data (ID) | 22 |
| 13.1.2 | ID Error Detection Code (IED) | 22 |
| 13.1.3 | RSV | 23 |
| 13.1.4 | Error Detection Code (EDC) | 23 |
| 13.2 | Scrambled Frames | 23 |
| 13.3 | ECC Blocks | 24 |
| 13.4 | Recording Frames | 25 |
| 13.5 | Modulation and NRZI conversion | 26 |
| 13.6 | Physical Sectors | 27 |
| 13.7 | Layout of a Recording UNit (RUN) | 28 |
| 13.7.1 | Recording Unit position | 29 |
| 13.8 | d.c. component suppression control | 29 |
| 14 | Track format | 30 |
| 14.1 | Track shape | 30 |
| 14.2 | Track path | 31 |
| 14.3 | Track pitch | 31 |
| 14.4 | Track layout | 31 |
| 14.4.1 | ADIP information | 31 |
| 14.4.2 | Physical format information in ADIP | 34 |
| 15 | General description of the Information Zone | 56 |
| 16 | Layout of the Information Zone of a Single-session disk | 56 |
| 16.1 | Physical Sector Numbers (PSNs) | 56 |
| 17 | Inner Drive Area | 57 |
| 17.1 | Initial Zone | 58 |
| 17.2 | Inner Disk Test Zone | 58 |
| 17.3 | Count Zone Run-in | 58 |
| 17.4 | Inner Disk Count Zone | 58 |
| 17.5 | Inner Disk Administration Zone | 59 |
| 17.6 | Table of Contents (TOC) Zone | 59 |
| 17.6.1 | Table of Contents Blocks | 60 |
| 17.6.2 | Recorded Area Indicators (optional) | 62 |
| 18 | Lead-in Zone | 63 |
| 18.1 | Guard Zone 1 | 63 |
| 18.2 | Reserved Zone 1 | 63 |
| 18.3 | Reserved Zone 2 | 63 |
| 18.4 | Inner Disk Identification Zone | 64 |

| | | |
|--------|---|----|
| 18.5 | Reserved Zone 3 | 64 |
| 18.6 | Reference Code Zone | 64 |
| 18.7 | Buffer Zone 1 | 64 |
| 18.8 | Control Data Zone | 64 |
| 18.8.1 | Physical format information | 64 |
| 18.8.2 | Disk manufacturing information | 66 |
| 18.8.3 | Content provider information | 66 |
| 18.9 | Buffer Zone 2 | 66 |
| 19 | Data Zone | 67 |
| 20 | Lead-out Zone | 67 |
| 20.1 | Buffer Zone 3 | 67 |
| 20.2 | Outer Disk Identification Zone | 67 |
| 20.3 | Guard Zone 2 | 67 |
| 21 | Outer Drive Area | 68 |
| 21.1 | Outer Disk Administration Zone | 68 |
| 21.2 | Outer Disk Count Zone | 68 |
| 21.3 | Outer Disk Test Zone | 69 |
| 21.4 | Guard Zone 3 | 69 |
| 22 | Multi-session Layout | 69 |
| 22.1 | Intro | 70 |
| 22.1.1 | Buffer Zone A | 71 |
| 22.1.2 | Inner Session Identification Zone | 71 |
| 22.1.3 | Session Control Data Zone | 71 |
| 22.1.4 | Buffer Zone B | 71 |
| 22.2 | Data Zone | 71 |
| 22.3 | Closure | 71 |
| 22.3.1 | Buffer Zone C | 71 |
| 22.3.2 | Outer Session Identification Zone | 71 |
| 23 | Sequential recording in Fragments | 71 |
| 23.1 | Opening a Session | 72 |
| 23.1.1 | Incomplete Fragment | 72 |
| 23.1.2 | Reserved Fragments | 72 |
| 23.1.3 | Recording User Data in Fragments | 73 |
| 23.1.4 | Closing a Fragment | 73 |
| 23.2 | Closing a Session | 74 |
| 23.2.1 | Lead-in/Intro Zone | 74 |
| 23.2.2 | Closure Zone | 74 |
| 23.3 | Finalizing the disk | 75 |
| 24 | Assignment of Logical Sector Numbers (LSNs) | 75 |
| 25 | Disk Control Blocks | 75 |
| 25.1 | General format of Disk Control Blocks | 75 |
| 25.2 | Format of the Session DCB (SDCB) | 77 |
| 25.2.1 | Session Items | 79 |
| 26 | General | 80 |
| 27 | Method of testing | 81 |
| 27.1 | Environment | 81 |
| 27.2 | Reference Drive | 81 |
| 27.2.1 | Optics and mechanics | 81 |
| 27.2.2 | Read power | 81 |
| 27.2.3 | Read channels | 81 |
| 27.2.4 | Tracking | 81 |
| 27.3 | Definition of signals | 81 |
| 28 | Characteristics of the groove signals | 82 |
| 28.1 | Phase depth | 82 |
| 28.2 | Push-pull signal | 82 |
| 28.3 | Track Cross signal | 83 |
| 28.4 | Normalized wobble signal | 83 |
| 28.5 | Characteristics of the wobble | 83 |
| 29 | Method of testing | 83 |
| 29.1 | Environment | 83 |
| 29.2 | Reference Drive | 84 |

| | | |
|--|--|-----|
| 29.2.1 | Optics and mechanics | 84 |
| 29.2.2 | Read power | 84 |
| 29.2.3 | Read channels | 84 |
| 29.2.4 | Tracking | 84 |
| 29.2.5 | Scanning velocity | 84 |
| 29.3 | Write conditions | 84 |
| 29.3.1 | Write pulse waveform | 84 |
| 29.3.2 | Write power | 85 |
| 29.3.3 | Write power dependency on wavelength | 86 |
| 29.3.4 | Write power window | 86 |
| 29.4 | Measurement conditions | 87 |
| 30 | Characteristics of the recorded signals | 87 |
| 30.1 | Channel bit length | 87 |
| 30.2 | Definition of signals | 87 |
| 30.2.1 | High frequency signals (HF) | 87 |
| 30.2.2 | Modulated amplitude | 87 |
| 30.2.3 | Signal asymmetry | 88 |
| 30.2.4 | Normalized Slicing Level jump | 88 |
| 30.2.5 | Jitter | 88 |
| 30.2.6 | Track Cross signal | 89 |
| 30.3 | Read stability | 89 |
| 31 | Additional testing conditions | 89 |
| 31.1 | Test environment | 89 |
| 31.1.1 | Optics | 89 |
| 31.2 | Definition of signals | 89 |
| 31.2.1 | Modulated amplitude | 90 |
| 31.2.2 | Signal asymmetry | 90 |
| 31.2.3 | Jitter | 90 |
| 31.2.4 | Track Cross signal | 90 |
| 31.2.5 | Differential phase tracking error signal | 90 |
| 31.2.6 | Tangential push-pull signal | 91 |
| 32 | Quality of the recording layer | 92 |
| 32.1 | Defects | 92 |
| 32.2 | Data errors | 92 |
| 33 | Method of testing | 93 |
| 33.1 | Environment | 93 |
| 33.2 | Reference Drive | 93 |
| 33.2.1 | Optics and mechanics | 93 |
| 33.2.2 | Read power | 93 |
| 33.2.3 | Read channels | 93 |
| 33.2.4 | Error correction | 93 |
| 33.2.5 | Tracking | 93 |
| 34 | Minimum quality of a Recording Unit | 94 |
| 34.1 | Tracking | 94 |
| 34.2 | User-written data | 94 |
| Annex A (normative) 80 mm +R disk | | 95 |
| Annex B (normative) Structure for Extended format information in the Data Zone | | 98 |
| Annex C (normative) Measurement of light reflectivity | | 101 |
| Annex D (normative) Measurement of birefringence | | 103 |
| Annex E (normative) Measuring conditions for operation signals | | 106 |
| Annex F (normative) Measurement of the differential phase tracking error | | 109 |
| Annex G (normative) The write pulse wave form for testing | | 113 |
| Annex H (normative) 8-to-16 Modulation | | 121 |

| | |
|---|------------|
| Annex I (normative) Optimum Power Control and Recording Conditions | 130 |
| Annex J (informative) Running OPC | 133 |
| Annex K (informative) Wavelength dependency | 134 |
| Annex L (informative) Explanation about the usage of the reference servos | 138 |
| Annex M (informative) Measurement of the groove wobble amplitude | 145 |
| Annex N (informative) Light fastness of the disk | 147 |
| Annex O (informative) Transportation | 148 |
| Annex P (informative) Video Content Protection System | 149 |
| Annex Q (informative) How to use the Physical format information in ADIP | 150 |
| Annex R (informative) Values to be implemented in Existing and Future Specifications | 152 |
| Bibliography | 155 |