

# ISO/IEC 26907:2009-11 (E)

## Information technology - Telecommunications and information exchange between systems - High-rate ultra-wideband PHY and MAC standard

---

<b>Contents</b>		<b>Page</b>
Foreword .....		x
Introduction .....		xi
1	Scope .....	1
2	Conformance .....	1
3	Normative references .....	1
4	Terms and definitions .....	1
5	Notational conventions .....	4
6	Abbreviations and acronyms .....	4
7	General description .....	7
7.1	PHY general description .....	7
7.2	MAC general description .....	8
7.2.1	General description of the architecture .....	8
7.2.2	Device address .....	9
7.2.3	Features assumed from the PHY .....	9
7.2.4	Overview of MAC service functionality .....	9
7.2.5	MUX sublayer .....	13
7.2.6	MAC policies .....	13
7.2.7	Test vectors .....	13
8	PHY layer partitioning .....	13
8.1	PHY function .....	14
8.2	PLCP sublayer .....	14
8.3	PMD sublayer .....	14
8.4	PHY layer management entity (PLME) .....	14
9	Description of signal .....	14
9.1	Mathematical framework .....	14
9.2	Tone-Nulling .....	15
10	PLCP sublayer .....	16
10.1	PPDU .....	16
10.1.1	PSDU rate-dependent parameters .....	18
10.1.2	Timing-related parameters .....	18
10.1.3	Frame-related parameters .....	19
10.2	PLCP preamble .....	20
10.2.1	Standard PLCP preamble .....	20
10.2.2	Burst PLCP preamble .....	21
10.3	PLCP header .....	43
10.3.1	PHY header .....	44
10.3.2	Reed-Solomon outer code for the PLCP header .....	48
10.3.3	Header check sequence .....	50
10.4	PSDU .....	51
10.4.1	Pad bits .....	52

10.5	Data scrambler .....	53
10.6	Tail bits .....	54
10.7	Convolutional encoder .....	55
10.8	Bit interleaving .....	58
10.9	Constellation mapping .....	60
10.9.1	QPSK .....	60
10.9.2	Dual-carrier modulation (DCM) .....	61
10.10	OFDM modulation .....	63
10.10.1	Implementation considerations .....	67
10.10.2	Data subcarriers .....	67
10.10.3	Guard subcarriers .....	71
10.10.4	Pilot subcarriers .....	71
11	General requirements .....	73
11.1	Operating band frequencies .....	73
11.1.1	Operating frequency range .....	73
11.1.2	Band numbering .....	73
11.2	Channelization .....	74
11.3	PHY layer timing .....	78
11.3.1	Interframe spacing .....	78
11.3.2	Receive-to-transmit turnaround time .....	78
11.3.3	Transmit-to-receive turnaround time .....	79
11.3.4	Time between successive transmissions .....	79
11.3.5	Band frequency switch time .....	79
12	Transmitter specifications .....	79
12.1	Transmit PSD mask .....	79
12.2	Transmit centre frequency tolerance .....	80
12.3	Symbol clock frequency tolerance .....	80
12.4	Clock synchronization .....	80
12.5	Phase coherence .....	80
12.6	Transmit power control .....	80
12.7	Transmitter constellation error .....	81
13	Receiver specification .....	83
13.1	Receiver sensitivity .....	83
13.2	Receiver CCA performance .....	83
13.3	Link quality indicator .....	83
13.4	Receive Signal Strength Indicator .....	84
14	Ranging and location awareness .....	85
14.1	Ranging requirements .....	85
14.2	Ranging reference signal .....	85
14.3	PHY ranging resources .....	85
14.4	PHY ranging operation .....	85
14.5	Ranging calibration constants .....	85
14.6	Example range measurement (informative) .....	85
15	PHY and MAC service access points (informative) .....	86
15.1	Generic MIB management primitives .....	87
15.1.1	XX-GET.request .....	88
15.1.2	XX-GET.confirm .....	88
15.1.3	XX-SET.request .....	89
15.1.4	XX-SET.confirm .....	89
15.2	PHY SAP interface .....	90
15.2.1	Data transfer .....	90
15.2.2	PHY transmission control .....	91
15.2.3	PHY reception control .....	93
15.2.4	PHY CCA control .....	96
15.3	PLME SAP interface .....	97
15.3.1	PHY reset .....	99
15.3.2	PHY ranging timer control .....	100
15.4	MAC sublayer management primitives .....	101
15.5	MAC management information base (MIB) .....	101
15.6	MLME SAP interface .....	101
15.6.1	Reset .....	101
15.6.2	Scan .....	102

15.6.3	Beacon transmission and reception .....	104
15.6.4	IE management .....	109
15.6.5	PTK establishment .....	110
15.6.6	GTK solicitation/distribution .....	113
15.6.7	Temporal key update .....	116
15.6.8	Security violation report .....	118
15.6.9	Pseudo-random function (PRF) .....	119
15.6.10	Application-specific IE (ASIE) management .....	120
15.6.11	Multicast address binding .....	122
15.6.12	Link events .....	125
15.6.13	Probe .....	128
15.6.14	Hibernation and sleep cycle .....	131
15.6.15	Higher layer synchronization support .....	136
15.6.16	Reservation management .....	138
15.6.17	Connection configuration primitives .....	144
15.6.18	Range measurement .....	146
15.6.19	Application-specific command management .....	147
15.7	MAC SAP interface .....	149
15.7.1	MAC-DATA.request .....	151
15.7.2	MAC-DATA.indication .....	151
15.7.3	MAC-DATA.confirm .....	152
16	MAC frame formats .....	152
16.1	Frame format conventions .....	152
16.1.1	Figures .....	152
16.1.2	Octet order .....	152
16.1.3	Encoding .....	153
16.2	General MAC frame format .....	153
16.2.1	Frame control .....	154
16.2.2	DestAddr .....	155
16.2.3	SrcAddr .....	155
16.2.4	Sequence control .....	155
16.2.5	Access information .....	156
16.2.6	Frame payload .....	157
16.2.7	FCS .....	157
16.3	Beacon frames .....	158
16.4	Control frames .....	160
16.4.1	Immediate acknowledgement (Imm-ACK) .....	161
16.4.2	Block acknowledgement (B-ACK) .....	161
16.4.3	Request to send (RTS) .....	162
16.4.4	Clear to send (CTS) .....	162
16.4.5	Unused DRP reservation announcement (UDA) .....	162
16.4.6	Unused DRP reservation response (UDR) .....	162
16.4.7	Application-specific .....	162
16.5	Command frames .....	163
16.5.1	DRP reservation request .....	164
16.5.2	DRP reservation response .....	164
16.5.3	Probe .....	165
16.5.4	Pairwise temporal key (PTK) .....	165
16.5.5	Group temporal key (GTK) .....	166
16.5.6	Range measurement .....	167
16.5.7	Application-specific .....	168
16.6	Data frames .....	168
16.7	Aggregated data frames .....	169
16.8	Information elements .....	169
16.8.1	Application-specific IE (ASIE) .....	171
16.8.2	Application-specific probe IE .....	171
16.8.3	Beacon period occupancy IE (BPOIE) .....	172
16.8.4	BP switch IE .....	173
16.8.5	Channel change IE .....	173
16.8.6	Distributed reservation protocol (DRP) IE .....	173
16.8.7	DRP availability IE .....	175
16.8.8	Hibernation anchor IE .....	175

16.8.9	Hibernation mode IE .....	176
16.8.10	Identification IE .....	176
16.8.11	Link feedback IE .....	178
16.8.12	MAC capabilities IE .....	179
16.8.13	Master key identifier (MKID) IE .....	180
16.8.14	Multicast address binding (MAB) IE .....	180
16.8.15	PCA availability IE .....	181
16.8.16	PHY capabilities IE .....	181
16.8.17	Probe IE .....	184
16.8.18	Regulatory Domain IE .....	184
16.8.19	Relinquish request IE .....	185
16.8.20	Tone-nulling (TN) IE .....	186
16.8.21	Traffic indication map (TIM) IE .....	187
17	MAC sublayer functional description .....	187
17.1	Frame processing .....	187
17.1.1	Frame addresses .....	188
17.1.2	Frame reception .....	188
17.1.3	Frame transaction .....	188
17.1.4	Frame transfer .....	189
17.1.5	Frame retry .....	190
17.1.6	Inter-frame space (IFS) .....	190
17.1.7	Duplicate detection .....	190
17.1.8	RTS/CTS use .....	191
17.1.9	MAC header fields .....	191
17.1.10	Information elements .....	194
17.2	Beacon period .....	197
17.2.1	Beacon slot state .....	198
17.2.2	BP length .....	198
17.2.3	Beacon transmission and reception .....	199
17.2.4	Beacon slot collision detection .....	200
17.2.5	BP contraction .....	201
17.2.6	Merger of multiple BPs .....	201
17.3	Prioritized contention access (PCA) .....	204
17.3.1	PCA medium availability .....	205
17.3.2	NAV .....	205
17.3.3	Medium status .....	205
17.3.4	PCA parameters .....	205
17.3.5	Obtaining a TXOP .....	206
17.3.6	Using a TXOP .....	207
17.3.7	Invoking a backoff procedure .....	208
17.3.8	Decrementing a backoff counter .....	209
17.4	Distributed reservation protocol (DRP) .....	209
17.4.1	Reservation type .....	210
17.4.2	Medium access .....	211
17.4.3	DRP availability IE .....	211
17.4.4	DRP reservation negotiation .....	212
17.4.5	DRP reservation announcements .....	213
17.4.6	Resolution of DRP reservation conflicts .....	213
17.4.7	BPST realignment and existing DRP reservations .....	215
17.4.8	Modification and termination of existing DRP reservations .....	215
17.4.9	Release of hard or private DRP reservation blocks .....	215
17.4.10	Retransmit procedures in DRP reservations .....	216
17.5	Synchronization of devices .....	216
17.5.1	Clock accuracy .....	217
17.5.2	Synchronization for devices in hibernation mode .....	217
17.5.3	Guard times .....	217
17.6	Fragmentation and reassembly .....	218
17.7	Aggregation .....	219
17.8	Acknowledgement policies .....	219
17.8.1	No-ACK .....	219
17.8.2	Immediate ACK .....	219
17.8.3	Block ACK .....	219

17.9	Probe .....	221
17.10	Dynamic channel selection .....	222
17.11	Multi-rate support .....	222
17.12	Transmit power control .....	222
17.13	Power management mechanisms .....	223
17.13.1	Power management modes .....	223
17.13.2	Device power states .....	223
17.13.3	Power state transitions .....	223
17.13.4	Hibernation mode operation .....	224
17.13.5	Hibernation anchor operation .....	225
17.14	ASIE operation .....	226
17.15	Range measurement operation .....	226
17.16	MAC sublayer parameters .....	229
18	Security .....	230
18.1	Security mechanisms .....	231
18.1.1	Security operation .....	231
18.1.2	4-way handshake .....	231
18.1.3	Key transport .....	231
18.1.4	Freshness protection .....	231
18.1.5	Data encryption .....	231
18.1.6	Frame integrity protection .....	232
18.2	Security modes .....	232
18.2.1	Security mode 0 .....	234
18.2.2	Security mode 1 .....	234
18.2.3	Security mode 2 .....	234
18.3	Temporal keys .....	235
18.3.1	Mutual authentication and PTK derivation .....	235
18.3.2	GTK exchange .....	236
18.3.3	Pseudo-random function (PRF) definition .....	237
18.3.4	PTK and KCK derivation .....	237
18.3.5	PTK MIC generation .....	238
18.3.6	Random number generation .....	238
18.4	Frame reception steps and replay prevention measures .....	239
18.4.1	Frame reception .....	239
18.4.2	Replay prevention .....	239
18.4.3	Implications on GTKs .....	240
18.5	AES-128 CCM Inputs .....	240
18.5.1	Overview .....	240
18.5.2	Nonce .....	240
18.5.3	CCM blocks .....	241
Annex A (normative) MUX sublayer .....		243
Annex B (normative) MAC Policies .....		246
Annex C (normative) Assigned number document .....		249
Annex D (informative) MAC test vectors .....		250
Annex E (informative) Example encoding of a PHY packet .....		261
Annex F (informative) Recommended out-of-band emission limits .....		306
Annex G (informative) Range measurement calculations .....		307
Bibliography .....		311