

# ISO/IEC 13156:2009-11 (E)

## Information technology - Telecommunications and information exchange between systems - High rate 60 GHz PHY, MAC and HDMI PAL

---

| <b>Contents</b>    |  | <b>Page</b> |
|--------------------|--|-------------|
| Foreword .....     |  | xii         |
| Introduction ..... |  | xiii        |
| 1                  | Scope .....  | 1           |
| 2                  | Conformance .....  | 1           |
| 3                  | Normative references .....   | 1           |
| 4                  | Terms and definitions .....  | 1           |
| 5                  | Notational conventions .....   | 4           |
| 6                  | Abbreviations and acronyms .....   | 4           |
| 7                  | General description (informative) .....  | 7           |
| 7.1                | PHY general description .....  | 7           |
| 7.2                | MAC general description .....  | 8           |
| 7.2.1              | General description of the architecture .....  | 8           |
| 7.2.2              | Device address .....   | 8           |
| 7.2.3              | Features assumed from the PHY .....  | 8           |
| 7.2.4              | Overview of MAC service functionality .....  | 9           |
| 7.2.5              | MAC policies .....   | 12          |
| 7.2.6              | Support for higher-layer timer synchronization .....                                   | 12          |
| 7.3                | MUX general description .....  | 13          |
| 7.4                | HDMI PAL description .....   | 13          |
| 8                  | PHY layer (informative) .....  | 13          |
| 9                  | Description of signal .....  | 13          |
| 9.1                | Mathematical framework for SCBT, OFDM, DBPSK, DQPSK, UEP-QPSK, OOK and 4ASK ..         | 13          |
| 9.2                | Mathematical framework for the narrow band section of the discovery mode preamble .... | 14          |
| 9.3                | Mathematical framework for DAMI .....  | 14          |
| 10                 | PLCP sublayer .....  | 15          |
| 10.1               | General PPDU frame format .....  | 15          |
| 10.1.1             | PLCP preamble .....  | 17          |
| 10.1.2             | PLCP header .....  | 17          |
| 10.1.3             | PPDU payload .....   | 20          |
| 10.1.4             | Antenna training sequence .....  | 21          |
| 10.2               | Type A PPDU .....  | 21          |
| 10.2.1             | Mode dependent parameters .....  | 21          |
| 10.2.2             | SCBT .....   | 22          |
| 10.2.3             | OFDM .....   | 43          |
| 10.2.4             | Constellation mapping .....  | 61          |
| 10.2.5             | Discovery mode .....   | 70          |
| 10.3               | Type B PPDU .....  | 72          |
| 10.3.1             | Mode dependent parameters .....  | 72          |
| 10.3.2             | Single carrier (DBPSK, DQPSK, UEP-QPSK) .....  | 72          |
| 10.3.3             | Dual alternate mark inversion (DAMI) .....   | 80          |

|        |   |     |
|--------|---|-----|
| 10.3.4 | Channel bonding .....                       | 83  |
| 10.3.5 | Discovery mode .....                        | 83  |
| 10.4   | Type C PPDU .....                           | 83  |
| 10.4.1 | Mode dependent parameters .....             | 84  |
| 10.4.2 | Timing related parameters .....             | 84  |
| 10.4.3 | Frame related parameters .....              | 84  |
| 10.4.4 | PLCP preamble .....                         | 85  |
| 10.4.5 | PLCP header .....                           | 86  |
| 10.4.6 | PPDU payload .....                          | 87  |
| 11     | General requirements .....                  | 91  |
| 11.1   | Operating band frequencies .....            | 91  |
| 11.1.1 | Operating frequency range .....             | 91  |
| 11.1.2 | Channel numbering .....                     | 92  |
| 11.2   | PHY layer timing .....                      | 93  |
| 11.2.1 | Receive-to-transmit turnaround time .....   | 94  |
| 11.2.2 | Transmit-to-receive turnaround time .....   | 94  |
| 11.2.3 | Time between successive transmissions ..... | 94  |
| 12     | Transmitter specifications .....            | 94  |
| 12.1   | Transmit PSD mask .....                     | 94  |
| 12.1.1 | Transmit PSD: Type A and Type B .....       | 94  |
| 12.1.2 | Transmit PSD: Type C .....                  | 95  |
| 12.2   | Transmit centre frequency tolerance .....   | 96  |
| 12.3   | Symbol clock frequency tolerance .....      | 96  |
| 12.4   | Clock synchronization .....                 | 97  |
| 12.5   | Transmit power control .....                | 97  |
| 12.6   | Transmitter EVM .....                       | 97  |
| 12.6.1 | Type A .....                                | 97  |
| 12.6.2 | Type B .....                                | 100 |
| 12.6.3 | Type C .....                                | 100 |
| 13     | Receiver specification .....                | 101 |
| 13.1   | Type A device .....                         | 101 |
| 13.1.1 | SCBT receiver sensitivity .....             | 101 |
| 13.1.2 | OFDM receiver sensitivity .....             | 102 |
| 13.2   | Type B device receiver sensitivity .....    | 103 |
| 13.3   | Type C device receiver sensitivity .....    | 103 |
| 13.4   | Receiver CCA performance .....              | 103 |
| 14     | MAC frame formats .....                     | 103 |
| 14.1   | Frame format conventions .....              | 103 |
| 14.1.1 | Figures .....                               | 103 |
| 14.1.2 | Octet order .....                           | 104 |
| 14.1.3 | Encoding .....                              | 104 |
| 14.2   | General MAC frame format .....              | 104 |
| 14.2.1 | Unaggregated MAC frame .....                | 104 |
| 14.2.2 | Aggregated MAC frame .....                  | 105 |
| 14.2.3 | Frame control .....                         | 106 |
| 14.2.4 | DestAddr .....                              | 107 |
| 14.2.5 | SrcAddr .....                               | 107 |
| 14.2.6 | Sequence control .....                      | 107 |
| 14.2.7 | Access information .....                    | 108 |
| 14.2.8 | Frame payload .....                         | 108 |
| 14.2.9 | FCS .....                                   | 109 |
| 14.3   | Beacon frames .....                         | 110 |
| 14.4   | Control frames .....                        | 112 |
| 14.4.1 | Immediate acknowledgement (Imm-ACK) .....   | 113 |
| 14.4.2 | Block acknowledgement (B-ACK) .....         | 113 |
| 14.4.3 | Application-specific .....                  | 114 |
| 14.4.4 | B-Poll .....                                | 114 |
| 14.4.5 | B-Poll response frame .....                 | 115 |
| 14.4.6 | ATTP control frames .....                   | 115 |
| 14.5   | Command frames .....                        | 116 |
| 14.5.1 | DRP reservation request .....               | 117 |
| 14.5.2 | DRP reservation response .....              | 117 |

|         |  |     |
|---------|--|-----|
| 14.5.3  | Channel selection .....                              | 117 |
| 14.5.4  | Link feedback .....                                  | 119 |
| 14.5.5  | Probe .....  | 122 |
| 14.5.6  | Pairwise temporal key (PTK) .....                    | 122 |
| 14.5.7  | Group temporal key (GTK) .....                       | 123 |
| 14.5.8  | Application-specific .....                           | 124 |
| 14.5.9  | Relay .....  | 124 |
| 14.5.10 | Transmit switched diversity (TSD) request .....      | 124 |
| 14.5.11 | Transmit switched diversity (TSD) set response ..... | 125 |
| 14.5.12 | Transmit switched diversity (TSD) switch .....       | 126 |
| 14.5.13 | Fast uplink channel allocation (FUCA) .....          | 126 |
| 14.6    | Data frames .....                                    | 126 |
| 14.7    | Information elements .....                           | 126 |
| 14.7.1  | Application-specific IE (ASIE) .....                 | 128 |
| 14.7.2  | Application-specific probe IE .....                  | 129 |
| 14.7.3  | ATTP IE .....  | 129 |
| 14.7.4  | Beacon period occupancy IE (BPOIE) .....             | 131 |
| 14.7.5  | Channel bonding IE (CBOIE) .....                     | 133 |
| 14.7.6  | Channel change IE .....                              | 134 |
| 14.7.7  | CTR description IE .....                             | 134 |
| 14.7.8  | Distributed reservation protocol (DRP) IE .....      | 135 |
| 14.7.9  | DRP availability IE .....                            | 137 |
| 14.7.10 | Hibernation anchor IE .....                          | 137 |
| 14.7.11 | Hibernation mode IE .....                            | 138 |
| 14.7.12 | Identification IE .....                              | 138 |
| 14.7.13 | Link feedback IE .....                               | 139 |
| 14.7.14 | MAC capabilities IE .....                            | 141 |
| 14.7.15 | Master key identifier (MKID) IE .....                | 142 |
| 14.7.16 | MSP interval change IE .....                         | 142 |
| 14.7.17 | MSP timing IE .....                                  | 142 |
| 14.7.18 | Multicast address binding (MAB) IE .....             | 142 |
| 14.7.19 | PHY capabilities IE .....                            | 143 |
| 14.7.20 | Probe IE .....                                       | 146 |
| 14.7.21 | Relinquish request IE .....                          | 146 |
| 14.7.22 | Relay IE .....                                       | 147 |
| 14.7.23 | Scan Countdown IE .....                              | 149 |
| 14.7.24 | Scan Timing IE .....                                 | 150 |
| 14.7.25 | UEP information IE .....                             | 150 |
| 14.8    | Master-slave operation command .....                 | 151 |
| 14.8.1  | Type C poll .....                                    | 152 |
| 14.8.2  | Type C poll response .....                           | 153 |
| 14.8.3  | Association request command .....                    | 153 |
| 14.8.4  | Association response command .....                   | 154 |
| 14.8.5  | MSPr services command .....                          | 154 |
| 14.8.6  | Disassociation request command .....                 | 155 |
| 14.8.7  | Channel time request command .....                   | 155 |
| 14.8.8  | Channel time response command .....                  | 155 |
| 14.8.9  | Channel time termination command .....               | 156 |
| 14.8.10 | Channel time modify request .....                    | 156 |
| 14.8.11 | Channel time modification response command .....     | 157 |
| 14.8.12 | Remote scan request command .....                    | 157 |
| 14.8.13 | Remote scan response command .....                   | 158 |
| 14.8.14 | Channel release request command .....                | 158 |
| 14.8.15 | Application specific command .....                   | 159 |
| 15      | MAC sublayer functional description .....            | 159 |
| 15.1    | Frame processing .....                               | 159 |
| 15.1.1  | Frame addresses .....                                | 160 |
| 15.1.2  | Frame reception .....                                | 160 |
| 15.1.3  | Antenna training frame transaction .....             | 160 |
| 15.1.4  | Frame transfer .....                                 | 161 |
| 15.1.5  | Frame retry .....                                    | 161 |
| 15.1.6  | Inter-frame space (IFS) .....                        | 162 |

|         |   |     |
|---------|---|-----|
| 15.1.7  | Duplicate detection .....                                       | 162 |
| 15.1.8  | RTT/CTT use .....   | 162 |
| 15.1.9  | MAC header fields .....   | 162 |
| 15.1.10 | Information elements .....                                      | 164 |
| 15.2    | Distributed contention access (DCA) .....                       | 166 |
| 15.2.1  | DCA medium availability .....                                   | 167 |
| 15.2.2  | NAV .....   | 167 |
| 15.2.3  | Medium status .....   | 167 |
| 15.2.4  | Obtaining a TXOP .....  | 167 |
| 15.2.5  | Using a TXOP .....  | 168 |
| 15.2.6  | Invoking a backoff procedure .....                              | 169 |
| 15.2.7  | Decrementing a backoff counter .....                            | 169 |
| 15.3    | Device discovery .....  | 170 |
| 15.3.1  | Type A .....  | 170 |
| 15.3.2  | Type B .....  | 170 |
| 15.3.3  | Type C .....  | 171 |
| 15.4    | Channel selection .....   | 171 |
| 15.4.1  | Explicit channel selection .....                                | 172 |
| 15.4.2  | Implicit channel selection .....                                | 172 |
| 15.5    | Transmission and reception of beacons and poll frames .....     | 173 |
| 15.5.1  | Transmission of beacons in the discovery channel .....          | 173 |
| 15.5.2  | Transmission and reception of mode-A0 beacon frames .....       | 176 |
| 15.5.3  | Transmission and reception of mode-B0 beacon frames .....       | 177 |
| 15.5.4  | Transmission and reception of TypeC poll frames .....           | 177 |
| 15.5.5  | Superframe .....  | 178 |
| 15.6    | Distributed reservation protocol (DRP) .....                    | 182 |
| 15.6.1  | Reservation type .....  | 183 |
| 15.6.2  | Reservation waveform .....                                      | 184 |
| 15.6.3  | DRP availability IE .....                                       | 184 |
| 15.6.4  | DRP reservation negotiation .....                               | 184 |
| 15.6.5  | DRP reservation announcements .....                             | 186 |
| 15.6.6  | Resolution of DRP reservation conflicts .....                   | 186 |
| 15.6.7  | BPST realignment and existing DRP reservations .....            | 187 |
| 15.6.8  | Modification and termination of existing DRP reservations ..... | 187 |
| 15.6.9  | Retransmit procedures in DRP reservations .....                 | 188 |
| 15.7    | Coexistence and interoperability .....                          | 188 |
| 15.7.1  | Coexistence .....   | 188 |
| 15.7.2  | Interoperability .....  | 189 |
| 15.8    | Synchronization of devices .....                                | 190 |
| 15.8.1  | Clock accuracy .....  | 190 |
| 15.8.2  | Synchronization for devices in hibernation mode .....           | 191 |
| 15.8.3  | Guard times .....   | 191 |
| 15.9    | Fragmentation and reassembly .....                              | 192 |
| 15.10   | Aggregation .....   | 192 |
| 15.11   | Channel bonding .....   | 194 |
| 15.12   | Acknowledgement policies .....                                  | 195 |
| 15.12.1 | No-ACK .....  | 195 |
| 15.12.2 | Immediate ACK .....   | 195 |
| 15.12.3 | Block ACK .....   | 195 |
| 15.13   | Probe .....   | 197 |
| 15.14   | Multi-rate support .....  | 198 |
| 15.15   | Transmit power control (TPC) .....                              | 198 |
| 15.16   | Power management mechanisms .....                               | 198 |
| 15.16.1 | Power management modes .....                                    | 198 |
| 15.16.2 | Power state transitions at active mode .....                    | 199 |
| 15.16.3 | Hibernation mode operation for Type A/B devices .....           | 201 |
| 15.16.4 | Hibernation mode operation for Type C device .....              | 202 |
| 15.16.5 | Hibernation anchor operation in Type A/B devices .....          | 202 |
| 15.17   | ASIE operation .....  | 203 |
| 15.18   | The antenna training and tracking protocol (ATTP) .....         | 203 |
| 15.18.1 | ATTP functional description .....                               | 204 |
| 15.18.2 | Antenna training sequence transmission and frame type .....     | 206 |

|          |  |     |
|----------|--|-----|
| 15.18.3  | Antenna training feedback information .....                      | 206 |
| 15.18.4  | Training matrix in closed loop mode .....                        | 207 |
| 15.18.5  | Feedback method in closed loop mode .....                        | 208 |
| 15.18.6  | No feedback in open loop mode .....                              | 212 |
| 15.18.7  | Iterative antenna training .....                                 | 212 |
| 15.18.8  | Antenna tracking .....   | 214 |
| 15.19    | Master-slave operation .....                                     | 214 |
| 15.19.1  | Master-slave timing structure .....                              | 215 |
| 15.19.2  | Master-slave operation between Type A, Type B and Type C devices | 216 |
|          | 15.19.3 Channel scanning .....                                   | 217 |
| 15.19.4  | Starting a MSPr .....  | 218 |
| 15.19.5  | Terminating a MSPr .....   | 218 |
| 15.19.6  | Association and disassociation .....                             | 218 |
| 15.19.7  | Channel access .....   | 221 |
| 15.19.8  | Synchronization .....  | 225 |
| 15.19.9  | Fragmentation and de-fragmentation .....                         | 227 |
| 15.19.10 | Acknowledgment and retransmissions .....                         | 227 |
| 15.19.11 | Link check .....   | 227 |
| 15.19.12 | Changing MSP parameters .....                                    | 229 |
| 15.19.13 | Channel release .....  | 230 |
| 15.20    | Transmit switched diversity (TSD) operation .....                | 232 |
| 15.20.1  | TSD initiating procedure .....                                   | 232 |
| 15.20.2  | Antenna switching .....  | 232 |
| 15.21    | MAC sublayer parameters .....                                    | 233 |
| 16       | Security .....   | 235 |
| 16.1     | Security mechanisms .....  | 235 |
| 16.1.1   | Security operation .....   | 235 |
| 16.1.2   | 4-way handshake .....  | 235 |
| 16.1.3   | Key transport .....  | 236 |
| 16.1.4   | Freshness protection .....                                       | 236 |
| 16.1.5   | Data encryption .....  | 236 |
| 16.1.6   | Frame integrity protection .....                                 | 236 |
| 16.2     | Security modes .....   | 236 |
| 16.2.1   | Security mode 0 .....  | 238 |
| 16.2.2   | Security mode 1 .....  | 238 |
| 16.2.3   | Security mode 2 .....  | 238 |
| 16.3     | Temporal keys .....  | 238 |
| 16.3.1   | Mutual authentication and PTK derivation .....                   | 239 |
| 16.3.2   | GTK exchange .....   | 240 |
| 16.3.3   | Pseudo-random function (PRF) definition .....                    | 240 |
| 16.3.4   | PTK and KCK derivation .....                                     | 241 |
| 16.3.5   | PTK MIC generation .....   | 242 |
| 16.3.6   | Random number generation .....                                   | 242 |
| 16.4     | Frame reception steps and replay prevention measures .....       | 243 |
| 16.4.1   | Frame reception .....  | 243 |
| 16.4.2   | Replay prevention .....  | 243 |
| 16.4.3   | Implications on GTKs .....                                       | 244 |
| 16.5     | AES-128 CCM inputs .....   | 244 |
| 16.5.1   | Overview .....   | 244 |
| 16.5.2   | Nonce .....  | 244 |
| 16.5.3   | CCM blocks .....   | 245 |
| 16.6     | Token authentication .....                                       | 246 |
| 16.6.1   | Token issuance .....   | 246 |
| 16.6.2   | Token revoke .....   | 247 |
| 17       | HDMI PAL .....   | 247 |
| 17.1     | Introduction .....   | 247 |
| 17.2     | HDMI transmission .....  | 248 |
| 17.2.1   | Identification of video vs. data .....                           | 248 |
| 17.2.2   | TMDS removal .....   | 248 |
| 17.2.3   | Data type multiplexing .....                                     | 248 |
| 17.3     | HDMI reception .....   | 251 |
| 17.3.1   | TMDS encoding .....  | 251 |

|  |   |     |
|--|---|-----|
| 17.3.2   | Packet demultiplexing .....                                   | 251 |
| 17.4   | PAL header format .....                                       | 255 |
| 17.4.1   | Sub-packet header .....                                       | 256 |
| 17.5   | PAL payload format .....                                      | 257 |
| 17.6   | Block retransmission request .....                            | 257 |
| 17.7   | Type specific header fields .....                             | 258 |
| 17.7.1   | S-UEP .....   | 258 |
| 17.7.2   | P-UEP .....   | 261 |
| 17.8   | Video/audio format adaptation .....                           | 262 |
| 17.8.1   | Fast video format adaptation .....                            | 262 |
| 17.8.2   | Fast audio format adaptation .....                            | 265 |
| 17.8.3   | Control messages to support fast format adaptation .....      | 266 |
| 17.9   | Fast uplink channel allocation (FUCA) .....                   | 267 |
| 17.9.1   | FUCA operation .....  | 268 |
| 17.9.2   | The procedure of data exchange using FUCA .....               | 271 |
| 18   | Out-of-band control channel .....                             | 272 |
| 18.1   | OOB operation .....   | 273 |
| 18.1.1   | Ad hoc mode .....   | 273 |
| 18.1.2   | Infrastructure mode .....                                     | 275 |
| 18.1.3   | Other OOB functions .....                                     | 277 |
| 18.2   | OOB frame format .....  | 278 |
| 18.2.1   | General frame format .....                                    | 278 |
| 18.2.2   | OOB-beacon .....  | 278 |
| 18.2.3   | OOB-60GHz capability request .....                            | 279 |
| 18.2.4   | OOB-60GHz capability response .....                           | 279 |
| 18.2.5   | OOB-interference detection request .....                      | 280 |
| 18.2.6   | OOB-interference detection response .....                     | 280 |
| 18.2.7   | OOB-channel loss notification .....                           | 280 |
| 18.2.8   | OOB-block ACK .....   | 281 |
| 18.2.9   | OOB-probe request .....                                       | 281 |
| 18.2.10  | OOB-probe response .....                                      | 281 |
| 18.3   | Convergence MAC sublayer parameters .....                     | 282 |
| 19   | Relay operation .....   | 282 |
| 19.1   | Relay path setup .....  | 282 |
| 19.1.1   | Identification of relay capabilities .....                    | 282 |
| 19.1.2   | Association with a relay device .....                         | 282 |
| 19.1.3   | Antenna training between the source and the destination ..... | 282 |
| 19.1.4   | Antenna training between the source and the relay .....       | 282 |
| 19.1.5   | Antenna training between the relay and the destination .....  | 283 |
| 19.1.6   | Transition to data channel .....                              | 283 |
| 19.2   | Data transmission in relay operation .....                    | 285 |
| 19.2.1   | DRP reservation for relay operation in data channel .....     | 285 |
| 19.2.2   | Usage of relay device .....                                   | 285 |
| 19.2.3   | Frame transfer in relay operation .....                       | 285 |
| 19.2.4   | Frame reception in relay operation .....                      | 286 |
| 19.2.5   | Data exchange using relay device .....                        | 286 |
| 19.2.6   | Decision on path change .....                                 | 287 |
| 19.2.7   | Path Change .....   | 287 |
| 19.2.8   | Relay link feedback via relay device .....                    | 288 |
| 19.2.9   | Scan of idle path .....                                       | 289 |
| 19.2.10  | Operation of relay device .....                               | 289 |
| Annex A (normative) MUX sublayer .....                           |   | 291 |
| Annex B (normative) MAC Policies .....                           |   | 293 |
| Annex C (informative) Bibliography .....                         |   | 296 |
| Annex D (informative) Higher Layer Synchronization Support ..... |   | 297 |