ISO/IEC/IEEE 8802-15-4:2010-10 (E)

Information technology_- Telecommunications and information exchange between systems_- Local and metropolitan area networks_- Specific requirements

Contents

1. Overview ... 1

1.1 General ... 1
1.2 Scope ... 1
1.3 Purpose ... 2

2. Normative references ... 3

3. Definitions ... 5

4. Acronyms and abbreviations ... 9

5. General description ... 13

5.1 Introduction ... 13
5.2 Components of the IEEE 802.15.4 WPAN ... 13
5.3 Network topologies ... 14
5.3.1 Star network formation ... 14
5.3.2 Peer-to-peer network formation ... 15
5.4 Architecture ... 15
5.4.1 Physical layer (PHY) ... 17
5.4.2 MAC sublayer ... 17
5.5 Functional overview ... 17
5.5.1 Superframe structure ... 17
5.5.2 Data transfer model ... 18
5.5.2.1 Data transfer to a coordinator ... 19
5.5.2.2 Data transfer from a coordinator ... 20
5.5.2.3 Peer-to-peer data transfers ... 21
5.5.3 Frame structure ... 21
5.5.3.1 Beacon frame ... 21
5.5.3.2 Data frame ... 22
5.5.3.3 Acknowledgment frame ... 22
5.5.3.4 MAC command frame ... 23
5.5.4 Improving probability of successful delivery ... 23
5.5.4.1 CSMA-CA mechanism ... 23
5.5.4.2 Frame acknowledgment ... 24
5.5.4.3 Data verification ... 24
5.5.5 Power consumption considerations ... 24
5.5.6 Security ... 24
5.6 Concept of primitives ... 25

6. PHY specification ... 27

6.1 General requirements and definitions ... 27
6.1.1 Operating frequency range ... 27
6.1.2 Channel assignments ... 28
6.1.2.1 Channel numbering ... 29
6.1.2.2 Channel pages ... 29
6.1.3 Minimum long interframe spacing (LIFS) and short interframe spacing (SIFS) periods ... 30

6.1.4 RF power measurement 31
6.1.5 Transmit power 31
6.1.6 Out-of-band spurious emission 31
6.1.7 Receiver sensitivity definitions 31
6.2 PHY service specifications 31
6.2.1 PHY data service 32
6.2.1.1 PD-DATA.request 32
6.2.1.2 PD-DATA.confirm 33
6.2.1.3 PD-DATA.indication 34
6.2.2 PHY management service 34
6.2.2.1 PLME-CCA.request 35
6.2.2.2 PLME-CCA.confirm 35
6.2.2.3 PLME-ED.request 36
6.2.2.4 PLME-ED.confirm 36
6.2.2.5 PLME-GET.request 37
6.2.2.6 PLME-GET.confirm 38
6.2.2.7 PLME-SET-TRX-STATE.request 39
6.2.2.8 PLME-SET-TRX-STATE.confirm 40
6.2.2.9 PLME-SET.request 40
6.2.2.10 PLME-SET.confirm 41
6.2.3 PHY enumerations description 42
6.3 PPDU format 43
6.3.1 Preamble field 43
6.3.2 SFD field 44
6.3.3 Frame Length field 45
6.3.4 PSDU field 45
6.4 PHY constants and PIB attributes 45
6.4.1 PHY constants 45
6.4.2 PHY PIB attributes 45
6.5 2450 MHz PHY specifications 47
6.5.1 Data rate 47
6.5.2 Modulation and spreading 47
6.5.2.1 Reference modulator diagram 47
6.5.2.2 Bit-to-symbol mapping 47
6.5.2.3 Symbol-to-chip mapping 47
6.5.2.4 O-QPSK modulation 48
6.5.2.5 Pulse shape 49
6.5.2.6 Chip transmission order 49
6.5.3 2450 MHz band radio specification 49
6.5.3.1 Transmit power spectral density (PSD) mask 49
6.5.3.2 Symbol rate 49
6.5.3.3 Receiver sensitivity 49
6.5.3.4 Receiver jamming resistance 50
6.6 868/915 MHz band binary phase-shift keying (BPSK) PHY specifications 50
6.6.1 868/915 MHz band data rates 50
6.6.2 Modulation and spreading 50
6.6.2.1 Reference modulator diagram 50
6.6.2.2 Differential encoding 51
6.6.2.3 Bit-to-chip mapping 51
6.6.2.4 BPSK modulation 51
6.6.3 868/915 MHz band radio specification 52
6.6.3.1 Operating frequency range 52
6.6.3.2 915 MHz band transmit PSD mask 52
6.6.3.3 Symbol rate 52

6.6.3.4 Receiver sensitivity 52
6.6.3.5 Receiver jamming resistance 52
6.7 868/915 MHz band (optional) amplitude shift keying (ASK) PHY specifications 53
6.7.1 868/915 MHz band data rates 53
6.7.2 Modulation and spreading 53
6.7.2.1 Reference modulator diagram 53
6.7.2.2 Bit-to-symbol mapping 54
6.7.2.3 Symbol-to-chip mapping 54
6.7.2.4 ASK modulation 55
6.7.3 868/915 MHz band radio specification for the ASK PHY 57
6.7.3.1 Operating frequency range 57
6.7.3.2 915 MHz band transmit PSD mask 57
6.7.3.3 Symbol rate 57
6.7.3.4 Receiver sensitivity 57
6.7.3.5 Receiver jamming resistance 57
6.7.4 SHR for ASK PHY 58
6.7.4.1 Preamble for ASK PHY 58
6.7.4.2 SFD for ASK PHY 58
6.7.4.3 Example of PSSS encoding 58
6.8 868/915 MHz band (optional) O-QPSK PHY specifications 60
6.8.1 868/915 MHz band data rates 60
6.8.2 Modulation and spreading 60
6.8.2.1 Reference modulator diagram 60
6.8.2.2 Bit-to-symbol mapping 60
6.8.2.3 Symbol-to-chip mapping 60
6.8.2.4 O-QPSK modulation 61
6.8.2.5 Pulse shape 62
6.8.2.6 Chip transmission order 62
6.8.3 868/915 MHz band radio specification 62
6.8.3.1 Operating frequency range 62
6.8.3.2 Transmit PSD mask 62
6.8.3.3 Symbol rate 63
6.8.3.4 Receiver sensitivity 63
6.8.3.5 Receiver jamming resistance 63
6.9 General radio specifications 63
6.9.1 TX-to-RX turnaround time 63
6.9.2 RX-to-TX turnaround time 64
6.9.3 Error-vector magnitude (EVM) definition 64
6.9.4 Transmit center frequency tolerance 65
6.9.5 Transmit power 65
6.9.6 Receiver maximum input level of desired signal 65
6.9.7 Receiver ED 65
6.9.8 Link quality indicator (LQI) 65
6.9.9 Clear channel assessment (CCA) 66

7. MAC sublayer specification 67

7.1 MAC sublayer service specification 67
7.1.1 MAC data service 68
7.1.1.1 MCPS-DATA.request 68
7.1.1.2 MCPS-DATA.confirm 71
7.1.1.3 MCPS-DATA.indication 72
7.1.1.4 MCPS-PURGE.request 75
7.1.1.5 MCPS-PURGE.confirm 75

7.1.1.6 Data service message sequence chart 76
7.1.2 MAC management service 76
7.1.3 Association primitives 77
7.1.3.1 MLME-ASSOCIATE.request 78
7.1.3.2 MLME-ASSOCIATE.indication 80
7.1.3.3 MLME-ASSOCIATE.response 81
7.1.3.4 MLME-ASSOCIATE.confirm 83
7.1.3.5 Association message sequence charts 85
7.1.4 Disassociation primitives 86
7.1.4.1 MLME-DISASSOCIATE.request 86
7.1.4.2 MLME-DISASSOCIATE.indication 89
7.1.4.3 MLME-DISASSOCIATE.confirm 90
7.1.4.4 Disassociation message sequence charts 91
7.1.5 Beacon notification primitive 92
7.1.5.1 MLME-BEACON-NOTIFY.indication 92
7.1.6 Primitives for reading PIB attributes 94
7.1.6.1 MLME-GET.request 95
7.1.6.2 MLME-GET.confirm 96
7.1.7 GTS management primitives 97
7.1.7.1 MLME-GTS.request 97
7.1.7.2 MLME-GTS.confirm 99
7.1.7.3 MLME-GTS.indication 100
7.1.7.4 GTS management message sequence charts 102
7.1.8 Primitives for orphan notification 103
7.1.8.1 MLME-ORPHAN.indication 103
7.1.8.2 MLME-ORPHAN.response 104
7.1.8.3 Orphan notification message sequence chart 106
7.1.9 Primitives for resetting the MAC sublayer 106
7.1.9.1 MLME-RESET.request 106
7.1.9.2 MLME-RESET.confirm 107
7.1.10 Primitives for specifying the receiver enable time 108
7.1.10.1 MLME-RX-ENABLE.request 108
7.1.10.2 MLME-RX-ENABLE.confirm 110
7.1.10.3 Message sequence chart for changing the state of the receiver 110
7.1.11 Primitives for channel scanning 111
7.1.11.1 MLME-SCAN.request 111
7.1.11.2 MLME-SCAN.confirm 114
7.1.11.3 Channel scan message sequence charts 116
7.1.12 Communication status primitive 116
7.1.12.1 MLME-COMM-STATUS.indication 116
7.1.13 Primitives for writing PIB attributes 119
7.1.13.1 MLME-SET.request 119
7.1.13.2 MLME-SET.confirm 121
7.1.14 Primitives for updating the superframe configuration 122
7.1.14.1 MLME-START.request 122
7.1.14.2 MLME-START.confirm 126
7.1.14.3 Message sequence chart for updating the superframe configuration 126
7.1.15 Primitives for synchronizing with a coordinator 127
7.1.15.1 MLME-SYNC.request 127
7.1.15.2 MLME-SYNC-LOSS.indication 128
7.1.15.3 Message sequence chart for synchronizing with a coordinator 131
7.1.16 Primitives for requesting data from a coordinator 131
7.1.16.1 MLME-POLL.request 132
7.1.16.2 MLME-POLL.confirm 133

7.1.16.3 Message sequence chart for requesting data from a coordinator 134
7.1.17 MAC enumeration description 135
7.2 MAC frame formats 137
7.2.1 General MAC frame format 138
7.2.1.1 Frame Control field 138
7.2.1.2 Sequence Number field 140
7.2.1.3 Destination PAN Identifier field 140
7.2.1.4 Destination Address field 140
7.2.1.5 Source PAN Identifier field 141
7.2.1.6 Source Address field 141
7.2.1.7 Auxiliary Security Header field 141
7.2.1.8 Frame Payload field 141
7.2.1.9 FCS field 141
7.2.2 Format of individual frame types 142
7.2.2.1 Beacon frame format 142
7.2.2.2 Data frame format 146
7.2.2.3 Acknowledgment frame format 147
7.2.2.4 MAC command frame format 147
7.2.3 Frame compatibility 148
7.3 MAC command frames 149
7.3.1 Association request command 150
7.3.1.1 MHR fields 150
7.3.1.2 Capability Information field 150
7.3.2 Association response command 151
7.3.2.1 MHR fields 151
7.3.2.2 Short Address field 152
7.3.2.3 Association Status field 152
7.3.3 Disassociation notification command 152
7.3.3.1 MHR fields 153
7.3.3.2 Disassociation Reason field 153
7.3.4 Data request command 153
7.3.5 PAN ID conflict notification command 154
7.3.6 Orphan notification command 155
7.3.7 Beacon request command 156
7.3.8 Coordinator realignment command 156
7.3.8.1 MHR fields 157
7.3.8.2 PAN Identifier field 157
7.3.8.3 Coordinator Short Address field 157
7.3.8.4 Logical Channel field 157
7.3.8.5 Short Address field 157
7.3.8.6 Channel Page field 157
7.3.9 GTS request command 158
7.3.9.1 MHR fields 158
7.3.9.2 GTS Characteristics field 158
7.4 MAC constants and PIB attributes 159
7.4.1 MAC constants 159
7.4.2 MAC PIB attributes 160
7.5 MAC functional description 166
7.5.1 Channel access 167
7.5.1.1 Superframe structure 167
7.5.1.2 Incoming and outgoing superframe timing 169
7.5.1.3 Interframe spacing (IFS) 169
7.5.1.4 CSMA-CA algorithm 170
7.5.2 Starting and maintaining PANs 172

7.5.2.1 Scanning through channels ... 172
7.5.2.2 PAN identifier conflict resolution ... 176
7.5.2.3 Starting and realigning a PAN ... 177
7.5.2.4 Beacon generation ... 178
7.5.2.5 Device discovery ... 179
7.5.3 Association and disassociation ... 179
7.5.3.1 Association ... 179
7.5.3.2 Disassociation ... 181
7.5.4 Synchronization ... 182
7.5.4.1 Synchronization with beacons ... 182
7.5.4.2 Synchronization without beacons ... 183
7.5.4.3 Orphaned device realignment ... 183
7.5.5 Transaction handling ... 183
7.5.6 Transmission, reception, and acknowledgment ... 185
7.5.6.1 Transmission ... 185
7.5.6.2 Reception and rejection ... 186
7.5.6.3 Extracting pending data from a coordinator ... 187
7.5.6.4 Use of acknowledgments and retransmissions ... 189
7.5.6.5 Promiscuous mode ... 190
7.5.6.6 Transmission scenarios ... 191
7.5.7 GTS allocation and management ... 192
7.5.7.1 CAP maintenance ... 193
7.5.7.2 GTS allocation ... 193
7.5.7.3 GTS usage ... 194
7.5.7.4 GTS deallocation ... 195
7.5.7.5 GTS reallocation ... 196
7.5.7.6 GTS expiration ... 197
7.5.8 Frame security ... 197
7.5.8.1 Security-related MAC PIB attributes ... 197
7.5.8.2 Functional description ... 199
7.6 Security suite specifications ... 206
7.6.1 PIB security material ... 206
7.6.2 Auxiliary security header ... 210
7.6.2.1 Integer and octet representation ... 210
7.6.2.2 Security Control field ... 210
7.6.2.3 Frame Counter field ... 212
7.6.2.4 Key Identifier field ... 212
7.6.3 Security operations ... 213
7.6.3.1 Integer and octet representation ... 213
7.6.3.2 CCM* Nonce ... 213
7.6.3.3 CCM* prerequisites ... 213
7.6.3.4 CCM* transformation data representation ... 214
7.6.3.5 CCM* inverse transformation data representation ... 215
7.7 Message sequence charts illustrating MAC-PHY interaction ... 216

Annex A (normative) Service-specific convergence sublayer (SSCS) ... 227

A.1 IEEE 802.2 convergence sublayer ... 227
A.1.1 MA-UNITDATA.request ... 227
A.1.1.1 Semantics of the service primitive ... 227
A.1.1.2 Appropriate usage ... 228
A.1.1.3 Effect on receipt ... 228
A.1.2 MA-UNITDATA.indication ... 228
A.1.2.1 Semantics of the service primitive ... 228

A.1.2.2 When generated ... 228
A.1.2.3 Appropriate usage ... 228
A.1.3 MA-UNITDATA-STATUS.indication ... 229
A.1.3.1 Semantics of the service primitive ... 229
A.1.3.2 When generated ... 229
A.1.3.3 Appropriate usage ... 229

Annex B (normative) CCM* mode of operation ... 231

B.1 Introduction ... 231
B.2 Notation and representation ... 231
B.2.1 Strings and string operations ... 231
B.2.2 Integers, octets, and their representation ... 231
B.3 Symmetric-key cryptographic building blocks ... 231
B.3.1 Block cipher ... 231
B.3.2 Mode of operation ... 232
B.4 Specification of generic CCM* mode of operation ... 232
B.4.1 CCM* mode encryption and authentication transformation ... 232
B.4.1.1 Input transformation ... 233
B.4.1.2 Authentication transformation ... 233
B.4.1.3 Encryption transformation ... 234
B.4.2 CCM* mode decryption and authentication checking transformation ... 234
B.4.2.1 Decryption transformation ... 235
B.4.2.2 Authentication checking transformation ... 235
B.4.3 Restrictions ... 235

Annex C (informative) Test vectors for cryptographic building blocks ... 237

C.1 AES block cipher ... 237
C.2 Mode of operation ... 237
C.2.1 MAC beacon frame ... 237
C.2.1.1 Description ... 237
C.2.1.2 CCM* mode encryption and authentication transformation ... 238
C.2.1.3 CCM* mode decryption and authentication checking transformation ... 240
C.2.2 MAC data frame ... 241
C.2.2.1 Description ... 241
C.2.2.2 CCM* mode encryption and authentication transformation ... 241
C.2.2.3 CCM* mode decryption and authentication checking transformation ... 243
C.2.3 MAC command frame ... 245
C.2.3.1 Description ... 245
C.2.3.2 CCM* mode encryption and authentication transformation ... 245
C.2.3.3 CCM* mode decryption and authentication checking transformation ... 247

Annex D (normative) Protocol implementation conformance statement (PICS) proforma ... 251

D.1 Introduction ... 251
D.1.1 Scope ... 251
D.1.2 Purpose ... 251
D.2 Abbreviations and special symbols ... 251
D.3 Instructions for completing the PICS proforma ... 252
D.4 Identification of the implementation ... 252
D.5 Identification of the protocol ... 253
D.6 Global statement of conformance ... 253
D.7 PICS proforma tables ... 254

D.7.1 Major roles for devices compliant with IEEE Std 802.15.4-2006 ... 254
D.7.2 Major capabilities for the PHY ... 255
D.7.2.1 PHY functions ... 255
D.7.2.2 PHY packet ... 255
D.7.2.3 Radio frequency (RF) ... 256
D.7.3 Major capabilities for the MAC sublayer ... 256
D.7.3.1 MAC sublayer functions ... 256
D.7.3.2 MAC frames ... 258

Annex E (informative) Coexistence with other IEEE standards and proposed standards ... 261

E.1 Introduction ... 261
E.2 Standards and proposed standards characterized for coexistence ... 261
E.3 General coexistence issues ... 261
E.3.1 Clear channel assessment (CCA) ... 262
E.3.2 Modulation ... 262
E.3.2.1 2400 MHz band PHY ... 262
E.3.2.2 800/900 MHz band PHYs ... 262
E.3.3 ED and LQI ... 263
E.3.4 Low duty cycle ... 263
E.3.5 Low transmit power ... 263
E.3.5.1 2400 MHz band PHY ... 263
E.3.5.2 800 MHz band PHYs ... 263
E.3.5.3 900 MHz band PHYs ... 264
E.3.6 Channel alignment ... 264
E.3.7 Dynamic channel selection ... 264
E.3.8 Neighbor piconet capability ... 264
E.4 2400 MHz band coexistence performance ... 265
E.4.1 Assumptions for coexistence quantification ... 265
E.4.1.1 Channel model ... 265
E.4.1.2 Receiver sensitivity ... 266
E.4.1.3 Transmit power ... 266
E.4.1.4 Receiver bandwidth ... 266
E.4.1.5 Transmit spectral masks ... 266
E.4.1.6 IEEE 802.11b transmit PSD ... 267
E.4.1.7 Interference characteristics ... 267
E.4.1.8 Bit error rate (BER) calculations ... 267
E.4.1.9 Packet error rate (PER) ... 268
E.4.2 BER model ... 268
E.4.3 Coexistence simulation results ... 268
E.5 800/900 MHz bands coexistence performance ... 273
E.5.1 Victims and assailants ... 273
E.5.2 Bandwidth ... 273
E.5.3 Path loss model ... 273
E.5.4 Temporal model ... 274
E.5.5 Coexistence assurance results ... 275
E.5.5.1 868 MHz BPSK PHY ... 275
E.5.5.2 868 MHz O-QPSK PHY ... 276
E.5.5.3 868 MHz PSSS PHY ... 278
E.5.5.4 915 MHz BPSK PHY ... 279
E.5.5.5 915 MHz O-QPSK PHY ... 280
E.5.5.6 915 MHz PSSS PHY ... 281
E.6 Notes on the calculations ... 282

Annex F (informative) IEEE 802.15.4 regulatory requirements 283

F.1 Introduction 283
F.2 Applicable U.S. (FCC) rules 285
F.2.1 Section 15.35 of FCC CFR47 285
F.2.2 Section 15.209 of FCC CFR47 287
F.2.3 Section 15.205 of FCC CFR47 287
F.2.4 Section 15.247 of FCC CFR47 288
F.2.5 Section 15.249 of FCC CFR47 289
F.3 Applicable European rules 290
F.3.1 European 2400 MHz band rules 291
F.3.2 European 868–870 MHz band rules 292
F.4 Applicable Japanese rules 294
F.5 Emissions specification analysis with respect to known worldwide regulations 295
F.5.1 General analysis and impact of detector bandwidth and averaging rules 295
F.5.2 Frequency spreading and averaging effects specific to IEEE Std 802.15.4 297
F.6 Summary of out-of-band spurious emissions limits 299
F.7 Phase noise requirements inferred from regulatory limits 300
F.8 Summary of transmission power levels 301

Annex G (informative) Bibliography 303

G.1 General 303
G.2 Regulatory documents 304

Annex H (informative) IEEE list of participants 306