

ISO/IEC 19784-4:2011-03 (E)

Information technology - Biometric application programming interface - Part 4: Biometric sensor function provider interface

| Contents | | Page |
|---------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Conformance | 1 |
| 3 | Normative references | 1 |
| 4 | Terms and definitions | 1 |
| 5 | Symbols, abbreviated terms, data structure definitions and error codes | 2 |
| 5.1 | Symbols and abbreviated terms | 2 |
| 5.2 | Data structure definitions and error codes | 2 |
| 6 | Interface architecture | 3 |
| 7 | Selecting and loading BFPs and BioAPI_Units | 4 |
| 7.1 | Obtaining information about BFPs and BioAPI_Units | 4 |
| 7.2 | Loading BFPs | 5 |
| 7.2.1 | Loading BFPs when attaching to an unspecified BioAPI_Unit | 5 |
| 7.2.2 | Loading BFPs when attaching to a specific BioAPI_Unit | 5 |
| 8 | BSFPI Definition | 5 |
| 8.1 | BSFPI data structures | 5 |
| 8.1.1 | Control codes | 5 |
| 8.1.2 | BioSFPI_EventHandler | 6 |
| 8.1.3 | BioSFPI_GUI_RESPONSE | 6 |
| 8.1.4 | BioSFPI_GUI_PROGRESS_EVENT_HANDLER | 6 |
| 8.2 | BSFP Functions | 7 |
| 8.2.1 | BioSFPI_BSFPLoad | 7 |
| 8.2.2 | BioSFPI_UnitAttach | 8 |
| 8.2.3 | BioSFPI_UnitDetach | 9 |
| 8.2.4 | BioSFPI_QueryUnits | 9 |
| 8.2.5 | BioSFPI_Free | 10 |
| 8.2.6 | BioSFPI_ControlUnit | 11 |
| 8.2.7 | BioSFPI_Cancel | 11 |
| 8.2.8 | BioSFPI_SetPowerMode | 12 |
| 8.2.9 | BioSFPI_SetGUICallbacks | 13 |
| 8.2.10 | BioSFPI_QueryFormatInfo | 13 |
| 8.2.11 | BioSFPI_GetPackets | 14 |
| 8.2.12 | BioSFPI_DataTransfer | 15 |
| 8.2.13 | BioSFPI_SetIndicatorStatus | 16 |
| 8.2.14 | BioSFPI_GetIndicatorStatus | 16 |
| 8.2.15 | BioSFPI_CalibrateSensor | 17 |
| 8.2.16 | BioSFPI_SubscribeToGUIEvents | 17 |
| 8.2.17 | BioSFPI_UnsubscribeFromGUIEvents | 18 |
| Annex A (normative) | Imaging biometric sensor units | 20 |

| | | |
|--|--|-----------|
| A.1 | General | 20 |
| A.1.1 | Bit and Byte ordering | 20 |
| A.1.2 | Scan sequence | 20 |
| A.1.3 | Pixel aspect ratio | 20 |
| A.1.4 | Greyscale pixel depth | 20 |
| A.1.5 | Colour space | 20 |
| A.1.6 | Video interlacing | 21 |
| A.2 | BioSFPI_BSFPIImagePropertyID | 21 |
| A.3 | BioSFPI_BSFPIImagePropertySchema | 21 |
| A.4 | BioSFPI_UnitImagePropertyID | 22 |
| A.5 | BioSFPI_UnitImagePropertySchema | 22 |
| A.6 | Image sensor functions | 23 |
| A.6.1 | BioSFPI_GetImageParameters | 23 |
| A.6.2 | BioSFPI_SetImageParameters | 24 |
| A.6.3 | BioSFPI_Pause | 25 |
| A.6.4 | BioSFPI_Play | 25 |
| Annex B (normative) Signature sensor units | | 27 |
| B.1 | General | 27 |
| B.1.1 | Bit and byte ordering | 27 |
| B.1.2 | Coordinate system | 27 |
| B.1.3 | Channel inclusion field | 28 |
| B.1.4 | Sequence of sample points | 29 |
| B.1.5 | Sample Rate | 29 |
| B.1.6 | ChannelDescriptions | 29 |
| B.2 | BioSFPI_BSFPSignaturePropertyID | 29 |
| B.3 | BioSFPI_BSFPSignaturePropertySchema | 30 |
| B.4 | BioSFPI_UnitSignaturePropertyID | 30 |
| B.5 | BioSFPI_UnitSignaturePropertySchema | 31 |
| B.6 | Signature Sensor Functions | 32 |
| B.6.1 | BioSFPI_GetSignatureParameters | 32 |
| B.6.2 | BioSFPI_SetSignatureParameters | 33 |
| Annex C (informative) Obtaining biometric sensor data across the SFPI | | 35 |
| C.1 | Overall functionality | 35 |
| C.2 | Fundamentals of the data transfer interfaces | 36 |
| C.3 | Memory management | 36 |
| C.4 | Components forming the interface | 36 |
| C.5 | Implementation options for use of the data transfer interface | 36 |
| Bibliography | | 38 |