

# ISO/IEC TR 16167:2011-09 (E)

## Information technology - Telecommunications and information exchange between systems - Next Generation Corporate Networks (NGCN) - Emergency calls

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>2</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>3.1</b>	<b>External definitions .....</b>	<b>2</b>
<b>3.2</b>	<b>Other definitions .....</b>	<b>2</b>
<b>4</b>	<b>Abbreviations .....</b>	<b>3</b>
<b>5</b>	<b>Background .....</b>	<b>5</b>
<b>6</b>	<b>Technical aspects of emergency calls in enterprise networks .....</b>	<b>8</b>
<b>6.1</b>	<b>Identifying a call as an emergency call .....</b>	<b>8</b>
<b>6.1.1</b>	<b>User actions .....</b>	<b>8</b>
<b>6.1.2</b>	<b>Signalling impact .....</b>	<b>10</b>
<b>6.1.3</b>	<b>Unauthenticated access .....</b>	<b>12</b>
<b>6.2</b>	<b>Obtaining and delivering the location of the caller .....</b>	<b>12</b>
<b>6.2.1</b>	<b>Format of location information .....</b>	<b>13</b>
<b>6.2.2</b>	<b>Obtaining location information for delivery .....</b>	<b>13</b>
<b>6.2.3</b>	<b>Location conveyance in SIP .....</b>	<b>18</b>
<b>6.3</b>	<b>Routing an emergency call to the appropriate SAP .....</b>	<b>18</b>
<b>6.3.1</b>	<b>Routing by the calling device .....</b>	<b>19</b>
<b>6.3.2</b>	<b>Routing by enterprise SIP intermediary .....</b>	<b>20</b>
<b>6.4</b>	<b>Delivering information to the SAP to allow a return call or verification call to be made .....</b>	<b>21</b>
<b>6.4.1</b>	<b>Delivery of caller identification .....</b>	<b>21</b>
<b>6.4.2</b>	<b>Delivery of device identification .....</b>	<b>21</b>
<b>6.4.3</b>	<b>Identifying a return call or verification call .....</b>	<b>22</b>
<b>6.5</b>	<b>Ensuring appropriate resources are available for an emergency call, return call or verification call .....</b>	<b>22</b>
<b>6.6</b>	<b>Ensuring appropriate media quality during an emergency call .....</b>	<b>23</b>
<b>6.7</b>	<b>Security considerations .....</b>	<b>24</b>
<b>6.8</b>	<b>Other aspects .....</b>	<b>25</b>
<b>6.8.1</b>	<b>Hosted users .....</b>	<b>25</b>
<b>6.8.2</b>	<b>Guest users .....</b>	<b>25</b>
<b>7</b>	<b>NGN considerations .....</b>	<b>25</b>
<b>8</b>	<b>Device considerations .....</b>	<b>27</b>
<b>9</b>	<b>Alternatives for roaming mobile and nomadic users .....</b>	<b>28</b>
<b>9.1</b>	<b>Establishing an emergency call when already signalling via a visited public network .....</b>	<b>28</b>
<b>9.2</b>	<b>Establishing an emergency call via a visited public network when other traffic is signalled directly via the enterprise network .....</b>	<b>29</b>
<b>9.3</b>	<b>Establishing an emergency call directly to a PSAP .....</b>	<b>29</b>
<b>10</b>	<b>Enterprise responsibilities .....</b>	<b>29</b>

<b>11</b>	<b>Summary of requirements and standardisation gaps .....</b>	<b>30</b>
<b>11.1</b>	<b>Requirements on NGNs .....</b>	<b>30</b>
<b>11.2</b>	<b>Recommendations on enterprise networks .....</b>	<b>30</b>
<b>11.3</b>	<b>Standardisation gaps .....</b>	<b>31</b>
<b>Bibliography .....</b>		<b>32</b>