

ISO/IEC 16504:2011-11 (E)

Information technology - Telecommunications and information exchange between systems - MAC and PHY for operation in TV white space

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | vii |
| Introduction | | viii |
| 1 | Scope | 1 |
| 2 | Conformance | 1 |
| 3 | Normative references | 1 |
| 4 | Terms and definitions | 1 |
| 5 | Abbreviations and Acronyms | 4 |
| 6 | General description | 7 |
| 6.1 | Network components | 7 |
| 6.2 | Network formation | 7 |
| 6.3 | Protocol architecture | 8 |
| 6.4 | Addressing | 9 |
| 6.5 | PHY features | 9 |
| 6.6 | Overview of MAC service functionality | 10 |
| 6.6.1 | Logical groups | 11 |
| 6.6.2 | Control algorithms | 11 |
| 6.6.3 | Channel selection | 11 |
| 6.6.4 | The superframe | 11 |
| 6.6.5 | Beaconing | 12 |
| 6.6.6 | Medium access | 13 |
| 6.6.7 | Data communication between devices | 13 |
| 6.6.8 | MAC frame data rates | 13 |
| 6.6.9 | Security | 13 |
| 6.6.10 | Information discovery | 14 |
| 6.6.11 | Support for higher-layer timer synchronization | 14 |
| 6.6.12 | Protection of incumbent users | 14 |
| 6.6.13 | Self-coexistence | 14 |
| 6.6.14 | Rate adaptation | 15 |
| 6.6.15 | Power management | 15 |
| 7 | MAC common part sublayer | 15 |
| 7.1 | MAC Frame Format | 15 |
| 7.1.1 | Frame format conventions | 16 |
| 7.1.2 | General MAC frame format | 16 |
| 7.1.3 | Beacon frames | 22 |
| 7.1.4 | Control frames | 24 |
| 7.1.5 | Command frames | 27 |
| 7.1.6 | Data frames | 35 |
| 7.1.7 | Aggregated data frames | 35 |
| 7.1.8 | Information elements | 35 |
| 7.2 | Frame processing | 63 |
| 7.2.1 | Frame addresses | 63 |
| 7.2.2 | Frame reception | 64 |
| 7.2.3 | Frame transaction | 64 |

| | | |
|--------|---|-----|
| 7.2.4 | Frame transfer | 65 |
| 7.2.5 | Frame retry | 65 |
| 7.2.6 | Inter-frame space (IFS) | 65 |
| 7.2.7 | Duplicate detection | 66 |
| 7.2.8 | RTS/CTS use | 66 |
| 7.2.9 | MAC header fields | 67 |
| 7.2.10 | Information elements | 69 |
| 7.3 | MAC Structure and Beaconing | 73 |
| 7.3.1 | Beacon Period | 74 |
| 7.3.2 | Beacon slot state | 74 |
| 7.3.3 | BP length | 74 |
| 7.3.4 | Beacon transmission and reception | 75 |
| 7.3.5 | Beacon collision detection | 76 |
| 7.3.6 | BP contraction | 76 |
| 7.3.7 | Merger of multiple beacon groups | 77 |
| 7.3.8 | Signalling window | 79 |
| 7.4 | Device Synchronization | 80 |
| 7.4.1 | Clock accuracy | 80 |
| 7.4.2 | Synchronization for devices in hibernation mode | 80 |
| 7.4.3 | Guard times | 80 |
| 7.5 | Data Transfer Period | 82 |
| 7.5.1 | Prioritized Contention Access (PCA) | 83 |
| 7.5.2 | Channel Reservation Access (CRA) | 89 |
| 7.6 | Fragmentation and Aggregation | 96 |
| 7.6.1 | Fragmentation and reassembly | 96 |
| 7.6.2 | Aggregation | 97 |
| 7.7 | ARQ, Multirate Support and Power Control | 98 |
| 7.7.1 | ARQ Policies | 98 |
| 7.7.2 | Multi-rate Support | 100 |
| 7.7.3 | Transmit Power Control | 100 |
| 7.8 | Dynamic Channel Selection | 100 |
| 7.9 | Power Management Mechanisms | 101 |
| 7.9.1 | Power management modes | 101 |
| 7.9.2 | Device power states | 101 |
| 7.9.3 | Power state transitions | 101 |
| 7.9.4 | Hibernation mode operation | 103 |
| 7.9.5 | Hibernation anchor operation | 103 |
| 7.10 | Probe | 104 |
| 7.11 | Protection of incumbents | 104 |
| 7.11.1 | Channel Measurement | 104 |
| 7.11.2 | Channel Classification | 107 |
| 7.11.3 | Channel Evacuation | 108 |
| 7.12 | Self-coexistence | 109 |
| 7.12.1 | Self-coexistence scenarios | 109 |
| 7.12.2 | Distributed self-coexistence mechanisms | 109 |
| 7.12.3 | Centralized self-coexistence mechanisms | 110 |
| 7.13 | Network Entry and Initialization | 111 |
| 7.13.1 | Initial Channel SCAN and Device Discovery | 113 |
| 7.13.2 | Master-Slave Association | 114 |
| 7.13.3 | Pair discovery | 115 |
| 7.13.4 | Create/join a beacon group | 116 |
| 7.13.5 | Pairing | 116 |
| 7.13.6 | Setup connections | 117 |
| 7.14 | MAC sublayer parameters | 118 |
| 8 | Security | 120 |
| 8.1 | Security mechanisms | 120 |
| 8.1.1 | Security operation | 120 |
| 8.1.2 | 4-way handshake | 121 |
| 8.1.3 | Key transport | 121 |
| 8.1.4 | Freshness protection | 121 |
| 8.1.5 | Data encryption | 121 |

| | | |
|--------|--|-----|
| 8.1.6 | Frame integrity protection | 121 |
| 8.2 | Security modes | 121 |
| 8.2.1 | Security mode 0 | 123 |
| 8.2.2 | Security mode 1 | 123 |
| 8.2.3 | Security mode 2 | 123 |
| 8.3 | Temporal keys | 123 |
| 8.3.1 | Mutual authentication and PTK derivation | 124 |
| 8.3.2 | GTK exchange | 125 |
| 8.3.3 | Pseudo-random function (PRF) definition | 126 |
| 8.3.4 | PTK and KCK derivation | 127 |
| 8.3.5 | PTK MIC generation | 127 |
| 8.3.6 | Random number generation | 128 |
| 8.4 | Frame reception steps and replay prevention measures | 128 |
| 8.4.1 | Frame reception | 128 |
| 8.4.2 | Replay prevention | 129 |
| 8.4.3 | Implications on GTKs | 129 |
| 8.5 | AES-128 CCM Inputs | 129 |
| 8.5.1 | Overview | 129 |
| 8.5.2 | Nonce | 130 |
| 8.5.3 | CCM blocks | 130 |
| 9 | PHY | 132 |
| 9.1 | Introduction | 132 |
| 9.2 | Symbol description | 132 |
| 9.2.1 | OFDM symbol description | 132 |
| 9.2.2 | Symbol parameters | 134 |
| 9.3 | PPDU | 134 |
| 9.3.1 | PLCP preamble | 135 |
| 9.3.2 | PLCP header | 137 |
| 9.3.3 | PSDU | 142 |
| 9.4 | Constellation mapping and modulation | 148 |
| 9.4.1 | Data modulation | 148 |
| 9.4.2 | Pilot modulation | 150 |
| 9.5 | OFDM modulation | 150 |
| 9.5.1 | Data subcarriers | 151 |
| 9.5.2 | Pilot subcarriers | 151 |
| 9.5.3 | Null subcarriers | 153 |
| 9.5.4 | Implementation of Fourier transform | 153 |
| 9.6 | General block diagram for the OFDM PHY | 154 |
| 9.7 | General requirements | 154 |
| 9.7.1 | Operating frequency range | 154 |
| 9.7.2 | Channel bandwidth and numbering | 155 |
| 9.7.3 | PHY layer timing | 155 |
| 9.8 | Transmitter requirements | 155 |
| 9.8.1 | Transmit center frequency tolerance | 155 |
| 9.8.2 | Symbol clock frequency tolerance | 155 |
| 9.8.3 | Clock synchronization | 155 |
| 9.8.4 | Transmitter constellation error | 156 |
| 9.9 | Receiver requirements | 157 |
| 9.9.1 | Receiver sensitivity | 157 |
| 9.9.2 | Maximum received signal level | 158 |
| 9.9.3 | Center frequency and symbol clock frequency tolerance | 158 |
| 9.9.4 | Link quality estimate | 158 |
| 9.10 | Control mechanisms | 159 |
| 9.10.1 | Device synchronization | 159 |
| 9.10.2 | Transmit power control | 159 |
| 9.11 | Multiple antennae (optional) | 160 |
| 9.11.1 | Multiple antennae normal preamble and burst preamble specification | 160 |
| 9.11.2 | Multiple antennae PLCP header specification | 161 |
| 9.11.3 | Pilot subcarriers for all multiple antennae modes | 163 |
| 9.11.4 | Frequency interleaved transmit diversity (FITD) | 163 |
| 9.11.5 | Alamouti space time block coding (STBC) | 163 |

| | |
|---|------------|
| 9.11.6 Spatial multiplexing (SM) mode | 164 |
| Annex A (normative) MUX sublayer | 165 |
| Annex B (normative) OFDM parameters for 7 MHz and 8 MHz channel bandwidths | 167 |
| Annex C (normative) Data rates for 7 MHz and 8 MHz channel bandwidths | 169 |
| Annex D (normative) MAC policies | 170 |
| Annex E (informative) FFT-based pilot sensing algorithms | 173 |
| Annex F (informative) An example of TPC algorithm | 175 |
| Bibliography | 178 |