

ISO/IEC 17417:2011-12 (E)

Information technology - Telecommunications and information exchange between systems - Short Distance Visible Light Communication (SDVLC)

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Conformance	1
3	Normative references	1
4	Terms, definitions and abbreviations	2
5	Conventions and notations	6
6	General	6
7	Physical Layer	6
8	Transmitter and Receiver Block Diagram	7
8.1	Transmitter to Receiver Link	7
8.2	Data Encoding	7
8.2.1	8B10 Data Encoding	8
8.2.2	2B4B Data Encoding	8
8.3	Modulation	8
8.4	Bit Order	8
9	Frame Formats	8
9.1	Frame Structure overview	9
9.2	Frame Structure Detail	10
9.2.1	Start Indicator Structure	10
9.2.2	Control Header Structure	11
9.3	MAC PDU Structure	13
9.3.1	MAC Header	13
9.3.2	Payload	14
9.3.3	Payload CRC	15
9.4	Visible Frame	15
9.4.1	Visible Pattern	15
9.5	Cyclic Redundancy Check (CRC)	16
10	Connection Procedure	16
11	Association Operation Messages	17
11.1	Association Request (AS-REQ)	17
11.2	Association Response (AS-RSP)	18
11.3	Association Acknowledge (AS-ACK)	18
11.4	Disassociation Request (DAS-REQ)	19
11.5	Disassociation Response (DAS-RSP)	19
11.6	Disassociation Acknowledge (DAS-ACK)	20
12	Data Burst Modes Operation	20
12.1	Periodic Burst Mode	20

12.1.1	Burst Request Message (BR-REQ)	21
12.1.2	Burst Response Message (BR-RSP)	23
12.2	Aperiodic Burst Mode	24
12.2.1	Aperiodic Burst Request Message (ABR-REQ)	25
12.2.2	Aperiodic Burst Response Message (ABR-RSP)	26
13	Data Encoding Change	28
13.1	ENC-REQ (Data Encoding Change Request)	28
13.2	ENC-RSP (Data Encoding Change Response)	28