ISO/IEC/IEEE 21451-7:2012-02 (E)

Information technology - Smart transducer interface for sensors and actuators - Part 7: Transducer to radio frequency identification (RFID) systems communication protocols and Transducer Electronic Data Sheet (TEDS) formats

Contents

Page

Foreword vi

Introduction vii

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Terms and definitions 2

5 Abbreviated terms 2

6 Transducer and RFID system interface specification 3

7 Air interface applicability (RFID and RTLS) 4
7.1 General 4
7.2 Overview 4
7.3 Sensor security system basic operations 5
7.3.1 Air interface security system support 5
7.3.2 Direct sensor security support 5
7.4 Sensor identifier 7
7.5 Sensor characteristics TEDS (Type 1) 8
7.5.1 TEDS type 10
7.5.2 Sensor type 10
7.5.3 Units extension 10
7.5.4 Sensor map of supported measurement codes 10
7.5.5 Data resolution 11
7.5.6 Scale factors for transmitted data 12
7.5.7 Data uncertainty 13
7.5.8 Sensor reconfiguration 13
7.5.9 Memory rollover capability 13
7.5.10 Air interface security capability 17
7.5.11 Sensor security capability 17
7.5.12 Sensor authentication encryption capability map 17
7.5.13 Sensor data encryption capability map 18
7.5.14 Random number size 18
7.5.15 Continuing authentication capability field 18
7.5.16 Sensor authentication password/key size 19
7.5.17 Sensor data encryption key size 19
7.5.18 Data encryption capability field 19
7.6 Sample and configuration record 20
7.6.1 UTC timestamp at configuration and beginning of mission 20
7.6.2 Sample interval 21
7.6.3 Monitor delay 21
7.6.4 Alarm values set 21
7.6.5 Memory rollover enabled 21
7.6.6 Air interface tag security status code 22

7.6.7 Sensor command classes 22
7.6.8 Air interface security function code 23
7.6.9 Sensor security function code 24
7.6.10 Sensor authentication encryption function code 25
7.6.11 Sensor data encryption function code 25
7.6.12 Security timer duration 25
7.6.13 Secure session timer 25
7.6.14 Upper alarm threshold value 26
7.6.15 Lower alarm threshold value 26
7.7 Event administration record 26
7.7.1 Code 10 sample capacity (C10SC) 27
7.7.2 Code 11 sample capacity (C11SC) 27
7.7.3 Code 12 sample capacity (C12SC) 28
7.7.4 Code 13 sample capacity (C13SC) 28
7.7.5 Sample count 28
7.7.6 Alarms triggered 28
7.7.7 Sample count at a predetermined time 28
7.7.8 Sample count and data following alarm event 29
7.7.9 Sample count of events outside either threshold 29
7.7.10 Sample count at the first threshold event 29
7.7.11 Mission in progress 29
7.8 Event records 29
7.8.1 Single event record 30
7.8.2 Single event with timestamp 30
7.8.3 Event counts 30
7.8.4 Data log of all sampled events 30
7.8.5 Data log plus time tick 31
7.8.6 Data log of all observations after initial alarm 31

8 Command overview 31
8.1 General 31
8.2 Read sensor identifier 34
8.3 Read primary characteristics TEDS 35
8.4 Write sample and configuration 36
8.5 Read sample and configuration 39
8.6 Read alarm status 41
8.7 Read single memory record 43
8.8 Read event administration record 45
8.9 Read event record segments 47
8.10 Read partial event record segment 50
8.11 Write event administration field 7 51
8.12 Read any field 53
8.13 Erase event administration record 54
8.14 Erase event records 55
8.15 Erase sample and configuration record 56
8.16 Begin end mission 57
8.17 Challenge 60
8.18 Reader authenticate 63
8.19 ReadWriteLock keys 65
8.20 Request RN 67
8.21 Encryption on/off 69
8.22 Close secure session 70

9 RFID communications 71
9.1 Support for commands 71
9.2 Addressing and sub-addressing of sensors 71

Annex A (normative) Sensor types 73

Annex B (normative) Extension codes 74

Annex C (informative) Physical interfaces 75

C.1 Interface - Serial Bus 75
C.2 1-Wire 75
C.3 SPI (Serial Peripheral Interface) 75
C.4 I2 C (I Squared C) 76

Annex E (informative) Sensor authentication and encryption 79

E.1 Need for authentication and encryption 79
E.2 Use of a stream cipher for encryption 79
E.3 Authentication using a stream cipher 80
E.4 Recommendations 81

Bibliography 82