

# ISO/IEC 18000-61:2012-07 (E)

## Information technology - Radio frequency identification for item management - Part 61: Parameters for air interface communications at 860 MHz to 960 MHz Type A

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Conformance .....</b>	<b>2</b>
2.1	Claiming conformance .....	2
2.2	Interrogator conformance and obligations .....	2
2.3	Tag conformance and obligations .....	2
<b>3</b>	<b>Normative references .....</b>	<b>3</b>
<b>4</b>	<b>Terms, definitions, symbols and abbreviated terms .....</b>	<b>3</b>
4.1	Terms and definitions .....	3
4.2	Symbols .....	4
4.3	Abbreviated terms .....	4
<b>5</b>	<b>Overview .....</b>	<b>5</b>
5.1	Parameter tables .....	5
<b>6</b>	<b>Type A .....</b>	<b>9</b>
6.1	Physical layer and data coding .....	9
6.1.1	Interrogator power-up waveform .....	9
6.1.2	Interrogator power-down .....	10
6.1.3	Frequency hopping carrier rise and fall times .....	11
6.1.4	FM0 return link .....	12
6.1.5	PIE (Pulse interval encoding) forward link .....	15
6.2	Data elements .....	20
6.2.1	Unique identifier (Tag ID) .....	20
6.2.2	Sub-UID .....	20
6.2.3	Application family identifier .....	21
6.2.4	Data storage format identifier (DSFID) .....	21
6.3	Protocol elements .....	22
6.3.1	Tag memory organisation .....	22
6.3.2	Support of battery assisted passive (BAP) tags .....	22
6.3.3	Block lock status .....	22
6.3.4	Tag signature .....	23
6.4	Protocol description .....	23
6.4.1	Protocol concept .....	23
6.4.2	Command format .....	24
6.4.3	Command flags .....	25
6.4.4	Round size .....	26
6.4.5	Command code definition and structure .....	26
6.4.6	Command classes .....	26
6.4.7	Command codes and CRC .....	28
6.4.8	Response format .....	31
6.4.9	Tag states .....	33
6.4.10	Collision arbitration .....	34
6.4.11	General explanation of the collision arbitration mechanism .....	34
6.5	Timing specifications .....	36

6.5.1	Timing specifications general .....	36
6.5.2	Tag state storage .....	36
6.5.3	Forward link to return link handover .....	37
6.5.4	Return link to forward link handover .....	37
6.5.5	Acknowledgement time window .....	37
6.6	Command format examples .....	39
6.7	Mandatory commands .....	39
6.7.1	Mandatory commands general .....	39
6.7.2	Next_slot .....	39
6.7.3	Standby_round .....	41
6.7.4	Reset_to_ready .....	42
6.7.5	Init_round_all .....	43
6.8	Optional commands .....	45
6.8.1	Optional commands general .....	45
6.8.2	Init_round .....	46
6.8.3	Close_slot .....	47
6.8.4	New_round .....	48
6.8.5	Select (by SUID) .....	50
6.8.6	Read_blocks .....	51
6.8.7	Get_system_information .....	55
6.8.8	Begin_round .....	58
6.8.9	Write_single_block .....	60
6.8.10	Write_multiple_blocks .....	62
6.8.11	Lock_blocks .....	64
6.8.12	Write_AFI .....	66
6.8.13	Lock_AFI .....	68
6.8.14	Write_DSFD command .....	70
6.8.15	Lock_DSFD .....	72
6.8.16	Get_blocks_lock_status .....	74
6.8.17	Init_Fast_Slots .....	76
6.9	Custom commands .....	79
6.10	Proprietary commands .....	80
Annex A (informative) Calculation of 5-bit and 16-bit cyclic redundancy checks .....		81
A.1	Example CRC-5 encoder/decoder .....	81
A.2	Example CRC-16 encoder/decoder .....	82
Bibliography .....		83