

# ISO/IEC 18000-64:2012-07 (E)

## Information technology - Radio frequency identification for item management - Part 64: Parameters for air interface communications at 860 MHz to 960 MHz Type D

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Conformance .....</b>	<b>1</b>
2.1	Claiming conformance .....	1
2.2	Interrogator conformance and obligations .....	2
2.3	Tag conformance and obligations .....	2
<b>3</b>	<b>Normative references .....</b>	<b>2</b>
<b>4</b>	<b>Terms, definitions, symbols and abbreviated terms .....</b>	<b>3</b>
4.1	Terms and definitions .....	3
4.2	Symbols .....	3
4.3	Abbreviated terms .....	4
<b>5</b>	<b>Overview .....</b>	<b>5</b>
5.1	Parameter tables .....	5
<b>6</b>	<b>Type D .....</b>	<b>8</b>
6.1	Physical layer .....	8
6.1.1	Interrogator power-up waveform .....	8
6.1.2	Interrogator power-down .....	9
6.1.3	Frequency hopping carrier rise and fall times .....	10
6.2	Protocol overview .....	11
6.2.1	General .....	11
6.2.2	Protocol parameter values .....	12
6.2.3	Tag arbitration .....	12
6.2.4	Operating procedure .....	13
6.2.5	TagMsg .....	15
6.2.6	CW control .....	16
6.2.7	Message encoding .....	16
6.2.8	Symbol modulation .....	17
6.2.9	Page modulation .....	17
6.2.10	Interrogator modulation detection .....	20
6.3	Type D Data .....	20
6.3.1	General .....	20
6.3.2	TID .....	21
6.3.3	Structured data encoding .....	23
6.3.4	Tag configuration .....	26
6.4	Encoding and decoding TID-S Tags .....	26
6.4.1	Encoding rules .....	26
6.4.2	Decoding rules .....	27
<b>7</b>	<b>Sensor support .....</b>	<b>28</b>
7.1	Applicability .....	28
7.2	Overview .....	28
7.3	Simple Sensors .....	28

<b>Annex A (informative) Calculation of 5-bit and 16-bit cyclic redundancy checks .....</b>	<b>29</b>
<b>A.1 Example CRC-5 encoder/decoder .....</b>	<b>29</b>
<b>A.2 Example TID-S CRC-16 encoder/decoder .....</b>	<b>30</b>
<b>A.3 Example TID-U CRC-16 encoder/decoder .....</b>	<b>31</b>
<b>Annex B (normative) Simple Sensors Data Block .....</b>	<b>32</b>
<b>B.1 Simple sensor types .....</b>	<b>32</b>
<b>B.2 General bit-based rules .....</b>	<b>33</b>
<b>B.3 Temperature sensor with 14° C span .....</b>	<b>33</b>
<b>B.3.1 Monitored measurement span .....</b>	<b>33</b>
<b>B.3.2 Accuracy .....</b>	<b>33</b>
<b>B.3.3 Sampling regime .....</b>	<b>34</b>
<b>B.3.4 High in-range limit level .....</b>	<b>34</b>
<b>B.3.5 Low in-range limit level .....</b>	<b>35</b>
<b>B.3.6 Monitor delay .....</b>	<b>35</b>
<b>B.3.7 High out-of-range alarm delay .....</b>	<b>36</b>
<b>B.3.8 Low out-of-range alarm delay .....</b>	<b>36</b>
<b>B.3.9 Alarms .....</b>	<b>37</b>
<b>B.4 Temperature sensor with 28° C span .....</b>	<b>38</b>
<b>B.4.1 Monitored measurement span .....</b>	<b>38</b>
<b>B.4.2 Accuracy .....</b>	<b>38</b>
<b>B.4.3 Sampling regime .....</b>	<b>38</b>
<b>B.4.4 High in-range limit .....</b>	<b>38</b>
<b>B.4.5 Low in-range limit .....</b>	<b>38</b>
<b>B.4.6 Monitor delay .....</b>	<b>39</b>
<b>B.4.7 High out-of-range alarm delay .....</b>	<b>39</b>
<b>B.4.8 Low out-of-range alarm delay .....</b>	<b>39</b>
<b>B.4.9 Alarms .....</b>	<b>39</b>
<b>B.5 Relative humidity .....</b>	<b>39</b>
<b>B.5.1 Monitored measurement span .....</b>	<b>39</b>
<b>B.5.2 Accuracy .....</b>	<b>39</b>
<b>B.5.3 Sampling regime .....</b>	<b>40</b>
<b>B.5.4 High in-range limit level .....</b>	<b>40</b>
<b>B.5.5 Low in-range limit level .....</b>	<b>40</b>
<b>B.5.6 Monitor delay .....</b>	<b>40</b>
<b>B.5.7 High out-of-range alarm delay .....</b>	<b>40</b>
<b>B.5.8 Low out-of-range alarm delay .....</b>	<b>40</b>
<b>B.5.9 Alarms .....</b>	<b>40</b>
<b>B.6 Impact .....</b>	<b>41</b>
<b>B.6.1 Monitored measurement span .....</b>	<b>41</b>
<b>B.6.2 Accuracy .....</b>	<b>41</b>
<b>B.6.3 Sampling regime .....</b>	<b>41</b>
<b>B.6.4 High in-range limit .....</b>	<b>41</b>
<b>B.6.5 Low in-range limit .....</b>	<b>41</b>
<b>B.6.6 Monitor delay .....</b>	<b>41</b>
<b>B.6.7 High out-of-range alarm delay .....</b>	<b>41</b>
<b>B.6.8 Low out-of-range alarm delay .....</b>	<b>42</b>
<b>B.6.9 Alarms .....</b>	<b>42</b>
<b>B.7 Tilt .....</b>	<b>42</b>
<b>B.7.1 Monitored measurement span .....</b>	<b>42</b>
<b>B.7.2 Accuracy .....</b>	<b>42</b>
<b>B.7.3 Sampling regime .....</b>	<b>42</b>
<b>B.7.4 High in-range limit .....</b>	<b>42</b>
<b>B.7.5 Low in-range limit .....</b>	<b>42</b>
<b>B.7.6 Monitor delay .....</b>	<b>42</b>
<b>B.7.7 High out-of-range alarm delay .....</b>	<b>43</b>
<b>B.7.8 Low out-of-range alarm delay .....</b>	<b>43</b>
<b>B.7.9 Alarms .....</b>	<b>43</b>