ISO/IEC 18000-64:2012-07 (E)

Information technology - Radio frequency identification for item management - Part 64: Parameters for air interface communications at 860 MHz to 960 MHz Type D

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Conformance 1
2.1 Claiming conformance 1
2.2 Interrogator conformance and obligations 2
2.3 Tag conformance and obligations 2

3 Normative references 2

4 Terms, definitions, symbols and abbreviated terms 3
4.1 Terms and definitions 3
4.2 Symbols 3
4.3 Abbreviated terms 4

5 Overview 5
5.1 Parameter tables 5

6 Type D 8
6.1 Physical layer 8
6.1.1 Interrogator power-up waveform 8
6.1.2 Interrogator power-down 9
6.1.3 Frequency hopping carrier rise and fall times 10
6.2 Protocol overview 11
6.2.1 General 11
6.2.2 Protocol parameter values 12
6.2.3 Tag arbitration 12
6.2.4 Operating procedure 13
6.2.5 TagMsg 15
6.2.6 CW control 16
6.2.7 Message encoding 16
6.2.8 Symbol modulation 17
6.2.9 Page modulation 17
6.2.10 Interrogator modulation detection 20
6.3 Type D Data 20
6.3.1 General 20
6.3.2 TID 21
6.3.3 Structured data encoding 23
6.3.4 Tag configuration 26
6.4 Encoding and decoding TID-S Tags 26
6.4.1 Encoding rules 26
6.4.2 Decoding rules 27

7 Sensor support 28
7.1 Applicability 28
7.2 Overview 28
7.3 Simple Sensors 28

Annex A (informative) Calculation of 5-bit and 16-bit cyclic redundancy checks 29

A.1 Example CRC-5 encoder/decoder 29
A.2 Example TID-S CRC-16 encoder/decoder 30
A.3 Example TID-U CRC-16 encoder/decoder 31

Annex B (normative) Simple Sensors Data Block 32

B.1 Simple sensor types 32
B.2 General bit-based rules 33
B.3 Temperature sensor with 14° C span 33
B.3.1 Monitored measurement span 33
B.3.2 Accuracy 33
B.3.3 Sampling regime 34
B.3.4 High in-range limit level 34
B.3.5 Low in-range limit level 35
B.3.6 Monitor delay 35
B.3.7 High out-of-range alarm delay 36
B.3.8 Low out-of-range alarm delay 36
B.3.9 Alarms 37
B.4 Temperature sensor with 28° C span 38
B.4.1 Monitored measurement span 38
B.4.2 Accuracy 38
B.4.3 Sampling regime 38
B.4.4 High in-range limit 38
B.4.5 Low in-range limit 38
B.4.6 Monitor delay 39
B.4.7 High out-of-range alarm delay 39
B.4.8 Low out-of-range alarm delay 39
B.4.9 Alarms 39
B.5 Relative humidity 39
B.5.1 Monitored measurement span 39
B.5.2 Accuracy 39
B.5.3 Sampling regime 40
B.5.4 High in-range limit level 40
B.5.5 Low in-range limit level 40
B.5.6 Monitor delay 40
B.5.7 High out-of-range alarm delay 40
B.5.8 Low out-of-range alarm delay 40
B.5.9 Alarms 40
B.6 Impact 41
B.6.1 Monitored measurement span 41
B.6.2 Accuracy 41
B.6.3 Sampling regime 41
B.6.4 High in-range limit 41
B.6.5 Low in-range limit 41
B.6.6 Monitor delay 41
B.6.7 High out-of-range alarm delay 41
B.6.8 Low out-of-range alarm delay 42
B.6.9 Alarms 42
B.7 Tilt 42
B.7.1 Monitored measurement span 42
B.7.2 Accuracy 42
B.7.3 Sampling regime 42
B.7.4 High in-range limit 42
B.7.5 Low in-range limit 42
B.7.6 Monitor delay 42
B.7.7 High out-of-range alarm delay 43
B.7.8 Low out-of-range alarm delay 43
B.7.9 Alarms 43