

ISO/IEC 18000-64:2012-07 (E)

Information technology - Radio frequency identification for item management - Part 64: Parameters for air interface communications at 860 MHz to 960 MHz Type D

Contents	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Conformance	1
2.1 Claiming conformance	1
2.2 Interrogator conformance and obligations	2
2.3 Tag conformance and obligations	2
3 Normative references	2
4 Terms, definitions, symbols and abbreviated terms	3
4.1 Terms and definitions	3
4.2 Symbols	3
4.3 Abbreviated terms	4
5 Overview	5
5.1 Parameter tables	5
6 Type D	8
6.1 Physical layer	8
6.1.1 Interrogator power-up waveform	8
6.1.2 Interrogator power-down	9
6.1.3 Frequency hopping carrier rise and fall times	10
6.2 Protocol overview	11
6.2.1 General	11
6.2.2 Protocol parameter values	12
6.2.3 Tag arbitration	12
6.2.4 Operating procedure	13
6.2.5 TagMsg	15
6.2.6 CW control	16
6.2.7 Message encoding	16
6.2.8 Symbol modulation	17
6.2.9 Page modulation	17
6.2.10 Interrogator modulation detection	20
6.3 Type D Data	20
6.3.1 General	20
6.3.2 TID	21
6.3.3 Structured data encoding	23
6.3.4 Tag configuration	26
6.4 Encoding and decoding TID-S Tags	26
6.4.1 Encoding rules	26
6.4.2 Decoding rules	27
7 Sensor support	28
7.1 Applicability	28
7.2 Overview	28
7.3 Simple Sensors	28

Annex A (informative) Calculation of 5-bit and 16-bit cyclic redundancy checks	29
A.1 Example CRC-5 encoder/decoder	29
A.2 Example TID-S CRC-16 encoder/decoder	30
A.3 Example TID-U CRC-16 encoder/decoder	31
Annex B (normative) Simple Sensors Data Block	32
B.1 Simple sensor types	32
B.2 General bit-based rules	33
B.3 Temperature sensor with 14° C span	33
B.3.1 Monitored measurement span	33
B.3.2 Accuracy	33
B.3.3 Sampling regime	34
B.3.4 High in-range limit level	34
B.3.5 Low in-range limit level	35
B.3.6 Monitor delay	35
B.3.7 High out-of-range alarm delay	36
B.3.8 Low out-of-range alarm delay	36
B.3.9 Alarms	37
B.4 Temperature sensor with 28° C span	38
B.4.1 Monitored measurement span	38
B.4.2 Accuracy	38
B.4.3 Sampling regime	38
B.4.4 High in-range limit	38
B.4.5 Low in-range limit	38
B.4.6 Monitor delay	39
B.4.7 High out-of-range alarm delay	39
B.4.8 Low out-of-range alarm delay	39
B.4.9 Alarms	39
B.5 Relative humidity	39
B.5.1 Monitored measurement span	39
B.5.2 Accuracy	39
B.5.3 Sampling regime	40
B.5.4 High in-range limit level	40
B.5.5 Low in-range limit level	40
B.5.6 Monitor delay	40
B.5.7 High out-of-range alarm delay	40
B.5.8 Low out-of-range alarm delay	40
B.5.9 Alarms	40
B.6 Impact	41
B.6.1 Monitored measurement span	41
B.6.2 Accuracy	41
B.6.3 Sampling regime	41
B.6.4 High in-range limit	41
B.6.5 Low in-range limit	41
B.6.6 Monitor delay	41
B.6.7 High out-of-range alarm delay	41
B.6.8 Low out-of-range alarm delay	42
B.6.9 Alarms	42
B.7 Tilt	42
B.7.1 Monitored measurement span	42
B.7.2 Accuracy	42
B.7.3 Sampling regime	42
B.7.4 High in-range limit	42
B.7.5 Low in-range limit	42
B.7.6 Monitor delay	42
B.7.7 High out-of-range alarm delay	43
B.7.8 Low out-of-range alarm delay	43
B.7.9 Alarms	43