ISO/IEC 24730-61:2013-08 (E)

Information technology - Real time locating systems (RTLS) - Part 61: Low rate pulse repetition freque ncy Ultra Wide Band (UWB) air interface

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms, definitions, and abbreviated terms 1
3.1 Terms and definitions 1
3.2 Symbols (and abbreviated terms) 2

4 General description 3
4.1 Introduction 3
4.3 Architecture 4
4.4 Functional overview 5
4.4.1 Data transfer from tag to infrastructure reader 5
4.4.2 Frame structure 5
4.4.3 Data verification 5
4.4.4 Overview of UWB options 6

5 PHY specification 6
5.1 General requirements and definitions 6
5.2 Modulation and data rates 6
5.3 LRP UWB PHY channel numbering 7
5.4 LRP UWB PHY symbol structure 7
5.4.1 Base mode OOK PHY symbol structure 8
5.4.2 Extended mode OOK PHY symbol structure 8
5.4.3 Long range mode PPM PHY symbol structure 10
5.4.4 LRP UWB SHR 11
5.4.5 LRP UWB PHY header (PHR) 12
5.4.6 LRP UWB data field 14
5.4.7 LRP UWB location enhancing information postamble 14
5.4.8 LRP UWB transmitter specification 15
5.4.9 LRP UWB reader specification 16

6 Tag management layer 16
6.1 Overview 17
6.2 Frame control 17
6.2.1 Frame type 17
6.2.2 Long frame control 17
6.2.3 Destination address mode 18
6.2.4 Source address mode 18
6.3 Sequence number 18
6.4 Tag ID (EUI-64) 18
6.5 Encoding header 18
6.6.1 Allocation class 19
6.6.2 Manufacturer ID 20
6.6.3 Tag ID 20
6.7 Temperature sensor data 20
6.8 Optional extended ID 20

6.8.1 Ex-ID source 20
6.8.2 Ex-ID length 20
6.8.3 ExID 21
6.9 Optional extended data 21
6.10 Frame check sequence 21

Bibliography 33