

ISO/IEC 24730-62:2013-09 (E)

Information technology - Real time locating systems (RTLS) - Part 62: High rate pulse repetition frequency Ultra Wide Band (UWB) air interface

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions, and abbreviated terms | 2 |
| 3.1 | Terms and definitions | 2 |
| 3.2 | Abbreviated terms | 3 |
| 4 | Overview | 4 |
| 4.1 | Components | 4 |
| 4.2 | Not covered by the standard | 5 |
| 4.3 | System | 5 |
| 4.4 | Document structure | 5 |
| 5 | Physical (PHY) layer specification | 5 |
| 5.1 | General | 5 |
| 5.2 | Default operating mode for a HRP UWB tag | 6 |
| 5.3 | PPDU format | 7 |
| 5.3.1 | PPDU encoding process | 7 |
| 5.3.2 | Symbol structure | 9 |
| 5.3.3 | PSDU timing parameters | 10 |
| 5.3.4 | Preamble timing parameters | 12 |
| 5.3.5 | SHR preamble | 13 |
| 5.3.6 | PHY header (PHR) | 16 |
| 5.3.7 | Data field | 18 |
| 5.4 | UWB PHY modulation | 19 |
| 5.4.1 | Modulation mathematical framework | 19 |
| 5.4.2 | Spreading | 19 |
| 5.4.3 | Forward error correction (FEC) | 21 |
| 5.5 | UWB PHY RF requirements | 23 |
| 5.5.1 | Operating frequency bands | 23 |
| 5.5.2 | Channel assignments | 23 |
| 5.5.3 | Transmitter specification | 23 |
| 5.6 | Timestamps and time units | 26 |
| 5.6.1 | Time units | 26 |
| 5.6.2 | Antenna delays | 26 |
| 6 | Basic message format | 26 |
| 6.1 | Message structure and processing rules | 26 |
| 6.1.1 | Time of arrival / Time of sending | 27 |
| 6.2 | Frame Check Sequence (FCS) | 27 |
| 7 | One-way communication - blink message | 28 |
| 7.1.1 | Sub-fields of the blink frame with ISO ID | 29 |
| 7.2 | Encoding of blink frames with IEEE EUI-64 tag ID | 31 |
| 7.2.1 | Sub-fields of the blink frame with IEEE ID | 31 |

| | | |
|--------------|---|-----------|
| 8 | Two-way communication - data messages | 35 |
| 8.1 | Data Messages | 35 |
| 8.1.1 | Data frame sub-fields | 35 |
| 8.2 | Operation of two-way communication | 36 |
| 8.2.1 | The mechanics of two-way Communication | 37 |
| 8.2.2 | Activity Control | 38 |
| 8.2.3 | Read Tag Capabilities | 39 |
| 8.2.4 | Read Tag Configuration | 40 |
| 8.2.5 | Set Tag Configuration | 42 |
| 8.2.6 | Perform two-way ranging | 43 |
| | Bibliography | 57 |