

ISO/IEC/IEEE 8802-1AS:2014-02 (E)

Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Part 1AS: Timing and synchronization for time-sensitive applications in bridged local area networks

Contents	Page
1. Overview.....	1
1.1 Scope.....	1
1.2 Purpose.....	2
2. Normative references.....	3
3. Definitions.....	5
4. Acronyms and abbreviations.....	9
5. Conformance.....	11
5.1 Requirements terminology.....	11
5.2 Protocol Implementation Conformance Statement (PICS).....	11
5.3 Time-aware Bridge and end station requirements.....	11
5.4 MAC-specific timing and synchronization methods for IEEE 802.3 full-duplex links.....	12
5.5 MAC-specific timing and synchronization methods for IEEE Std 802.11-2007.....	12
5.6 MAC-specific timing and synchronization methods for IEEE 802.3 EPON.....	12
5.7 MAC-specific timing and synchronization methods for coordinated shared network (CSN).....	13
6. Conventions.....	15
6.1 General.....	15
6.2 Service specification method and notation.....	15
6.3 Data types and on-the-wire formats.....	15
7. Time synchronization model for a bridged local area network.....	19
7.1 General.....	19
7.2 Architecture of a time-aware bridged local area network.....	19
7.3 Time synchronization.....	21
7.4 Time-aware system architecture.....	24
7.5 Differences between gPTP and PTP.....	25
8. IEEE 802.1AS concepts and terminology.....	27
8.1 gPTP domain.....	27
8.2 Timescale.....	27
8.3 Communication path asymmetry.....	28
8.4 Messages.....	29
8.5 Ports.....	30
8.6 Time-aware system characterization.....	32
9. Application interfaces.....	37
9.1 Overview of the interfaces.....	37
9.2 ClockSourceTime interface.....	38
9.3 ClockTargetEventCapture interface.....	38
9.4 ClockTargetTriggerGenerate interface.....	39
9.5 ClockTargetClockGenerator interface.....	40
9.6 ClockTargetPhaseDiscontinuity interface.....	41

10.	Media-independent layer specification	43
	10.1 Overview	43
	10.2 Time-synchronization state machines	44
	10.3 Best master clock selection and announce interval setting state machines	67
	10.4 Message attributes	85
	10.5 Message formats	87
	10.6 Protocol timing characterization	95
11.	Media-dependent layer specification for full-duplex, point-to-point links	99
	11.1 Overview	99
	11.2 State machines for MD entity specific to full-duplex, point-to-point links	105
	11.3 Message attributes	122
	11.4 Message formats	124
	11.5 Protocol timing characterization	131
12.	Media-dependent layer specification for IEEE 802.11 links	133
	12.1 Overview	133
	12.2 Messages	135
	12.3 Determination of asCapable	135
	12.4 State machines	136
	12.5 Format of VendorSpecific information element	143
	12.6 Synchronization message interval	144
13.	Media-dependent layer specification for interface to IEEE 802.3 Ethernet passive optical network link	145
	13.1 Overview	145
	13.2 Message attributes	149
	13.3 Message format	149
	13.4 Determination of asCapable	151
	13.5 Layering for IEEE 802.3 EPON links	151
	13.6 Service interface definitions	152
	13.7 MD entity global variables	154
	13.8 State machines	154
	13.9 Message transmission intervals	158
14.	Timing and synchronization management	159
	14.1 General	159
	14.2 Default Parameter Data Set	159
	14.3 Current Parameter Data Set	161
	14.4 Parent Parameter Data Set	164
	14.5 Time Properties Parameter Data Set	165
	14.6 Port Parameter Data Set	166
	14.7 Port Parameter Statistics	170
	14.8 Acceptable Master Table Parameter Data Set	173
15.	Managed object definitions	175
	15.1 Internet Standard Management Framework	175
	15.2 Structure of the MIB	175
	15.3 Security considerations	175
	15.4 Textual conventions defined in this MIB	179
	15.5 IEEE 802.1AS MIB module	179

List of figures

Figure 7-1—Time-aware network example.....	20
Figure 7-2—Time-aware network of Figure 7-1 after an access network link failure	21
Figure 7-3— Example delay measurement	22
Figure 7-4—Time-aware system model	24
Figure 8-1—Propagation asymmetry.....	28
Figure 8-2—Definition of message timestamp point, reference plane, timestamp measurement plane, and latency constants	30
Figure 9-1—Application interfaces	37
Figure 10-1—Model for media-independent layer of time-aware system.....	44
Figure 10-2—Time-synchronization state machines—overview and interrelationships.....	46
Figure 10-3—SiteSyncSync state machine.....	56
Figure 10-4—PortSyncSyncReceive state machine	58
Figure 10-5—ClockMasterSyncSend state machine	60
Figure 10-6—ClockMasterSyncOffset state machine	61
Figure 10-7—ClockMasterSyncReceive state machine	63
Figure 10-8—PortSyncSyncSend state machine	65
Figure 10-9—ClockSlaveSync state machine	67
Figure 10-10—Example master/slave hierarchy of time-aware systems	69
Figure 10-11—Best master clock selection state machines—overview and interrelationships	74
Figure 10-12—PortAnnounceReceive state machine.....	79
Figure 10-13—PortAnnounceInformation state machine.....	80
Figure 10-14—PortRoleSelection state machine.....	83
Figure 10-15—PortAnnounceTransmit state machine	84
Figure 10-16—AnnounceIntervalSetting state machine.....	85
Figure 11-1—Propagation delay measurement using peer delay mechanism	100
Figure 11-2—Transport of time-synchronization information.....	102
Figure 11-3—Model for time-aware system with full-duplex, point-to-point links.....	105
Figure 11-4—Detail of MD entity time-synchronization state machines for full-duplex, point-to-point links	106
Figure 11-5—Peer delay mechanism state machines—overview and interrelationships.....	106
Figure 11-6—MDSyncReceiveSM state machine.....	111
Figure 11-7—MDSyncSendSM state machine.....	114
Figure 11-8—MDPdelayReq state machine	118
Figure 11-9—MDPdelayResp state machine	120
Figure 11-10—LinkDelaySyncIntervalSetting state machine.....	121
Figure 12-1—Timing measurement procedure for IEEE 802.11 links	134
Figure 12-2—Media-dependent and lower entities in stations with IEEE 802.11 links	135
Figure 12-3—Master state machine.....	137
Figure 12-4—Slave state machine	141
Figure 12-5—Format of VendorSpecific information element when Type = 0	143
Figure 13-1—IEEE 802.3 EPON time-synchronization interfaces	148
Figure 13-2—IEEE 802.3 EPON interface model.....	152
Figure 13-3—State machine for IEEE 802.3 EPON requester.....	156
Figure 13-4—State machine for IEEE 802.3 EPON responder.....	157
Figure B.1—Wander generation (TDEV) requirement for LocalClock entity.....	247
Figure B.2—ADEV limit corresponding to wander generation requirement of Figure B.1	248
Figure B.3—PTPDEV limit corresponding to wander generation requirement of Figure B.1	249
Figure B.4—MTIE masks met for maximum endpoint filter bandwidths of Table B.4	251
Figure E.1—Example of CSN backbone in an AVB LAN	260
Figure E.2—Media-dependent and lower entities in CSN nodes	261
Figure E.3—Path types over CSN as IEEE 802.1AS backbone.....	262
Figure E.4—Propagation delay and residence time over a CSN Backbone	262
Figure E.5—CSN node-to-node path delay measurement.....	263
Figure E.6—IEEE 802.1AS Sync Message Propagation over the CSN backbone	265

List of tables

Table 6-1—Primitive data types	15
Table 8-1—Illustration of formation of clockIdentity from EUI-48	31
Table 8-2—Default values for priority1, for the respective media	33
Table 8-3—timeSource enumeration	36
Table 10-1—Port role definitions	68
Table 10-2—Destination address for Announce and Signaling messages	86
Table 10-3—Ethertype for Announce and Signaling messages	86
Table 10-4—PTP message header	88
Table 10-5—Values for messageType field	88
Table 10-6—Values of flag bits	89
Table 10-7—Announce message fields	90
Table 10-8—Path trace TLV	91
Table 10-9—Signaling message fields	92
Table 10-10—Message interval request TLV	93
Table 10-11—Interpretation of special values of linkDelayInterval	94
Table 10-12—Interpretation of special values of timeSyncInterval	94
Table 10-14—Definitions of bits of flags field of message interval request TLV	95
Table 10-13—Interpretation of special values of announceInterval	95
Table 11-1—Destination address for Sync, Follow_Up, Pdelay_Req, Pdelay_Resp, and Pdelay_Resp_Follow_Up messages	123
Table 11-2—Ethertype for Sync, Follow_Up, Pdelay_Req, Pdelay_Resp, and Pdelay_Resp_Follow_Up messages	123
Table 11-4—Values of flag bits	125
Table 11-3—Values for messageType field	125
Table 11-6—References for sequenceId value exceptions	126
Table 11-7—Value of control field	126
Table 11-5—Value of correction field	126
Table 11-8—Sync message fields	127
Table 11-9—Follow_Up message fields	127
Table 11-10—Follow_Up information TLV	128
Table 11-11—Pdelay_Req message fields	129
Table 11-12—Pdelay_Resp message fields	130
Table 11-13—Pdelay_Resp_Follow_Up message fields	130
Table 12-1—Parameters of MLME-TIMINGMSMT.request	139
Table 12-2—Parameters of MLME-TIMINGMSMST.confirm	140
Table 12-3—Parameters of MLME-TIMINGMSMT.indication	143
Table 12-4—Values of the Type field in the VendorSpecific information element	144
Table 13-1—TIMESYNC message fields	150
Table 14-1—Default Parameter Data Set Table	162
Table 14-2—Current Parameter Data Set Table	163
Table 14-3—Parent Parameter Data Set Table	165
Table 14-4—Time Properties Parameter Data Set Table	166
Table 14-5—portRole enumeration	167
Table 14-6—Port Parameter Data Set Table	170
Table 14-7—Port Parameter Statistics Table	173
Table 14-8—Acceptable Master Table Parameter Data Set Table	174
Table 15-1—IEEE8021-AS MIB structure and object cross reference	177
Table B.1—Wander generation TDEV requirement for LocalClock entity	246
Table B.2—ADEV limit corresponding to wander generation requirement of Table B.1	247
Table B.3—PTPDEV limit corresponding to wander generation requirement of Table B.1	248
Table B.4—Maximum endpoint filter bandwidths needed to meet respective MTIE masks and peak-to-peak jitter limits	250
Table B.5—Breakpoints for Mask 1	251
Table B.6—Breakpoints for Mask 2	251
Table B.7—Breakpoints for Mask 3	251
Table C.1—Time-scale parameters	253
Table C.2—Time-scale conversions	255
Table D.1—State machine symbols	258
Table E.1—CSN TLV	267
Table E.2—Definitions and option selections per link technology	268