

ISO/IEC 18000-4:2015-02 (E)

Information technology - Radio frequency identification for item management - Part 4 : Parameters for air interface communications at 2,45 GHz

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and abbreviated terms	3
5.1	Protocols	5
5.2	Frequency	5
5.2.1	Interface definitions	5
5.3	Tag identification number	6
5.4	Potential interference	6
6	MODE 1: Passive backscatter RFID system	6
6.1	MODE 1: General	6
6.2	Physical layer and data coding	7
6.2.1	Interrogator power-up waveform	7
6.2.2	Interrogator power-down	8
6.2.3	Frequency hopping carrier rise and fall times	9
6.2.4	Forward link	9
6.2.5	FM0 return link	11
6.2.6	Cyclic redundancy check (CRC)	12
6.2.7	Protocol concept	13
6.2.8	Command format	14
6.2.9	Response format	15
6.2.10	WAIT	15
6.2.11	Communication sequences at packet level	16
6.3	Protocol and collision arbitration	17
6.3.1	Definition of data elements, bit and byte ordering	17
6.3.2	Tag memory organisation	18
6.3.3	Block security status	18
6.3.4	Overall protocol description	19
6.3.5	Collision arbitration	23
6.3.6	Commands	24
6.3.7	Transmission errors	43
7	MODE 2: Long range high data rate RFID system	43
7.1	MODE 2: General	43
7.2	Modulation and coding	43
7.2.1	Forward link (only for R/W-tag)	43
7.2.2	Return link for notification (for both types of the tag)	44
7.2.3	Return link for communication (only for R/W-tag)	44
7.3	General system description	45
7.4	Frame structure	46
7.4.1	Hierarchical structure	46
7.4.2	Logical channels	47

7.4.3	Physical channels	53
7.5	Channel coding and sequences	68
7.5.1	Synchronisation and CRC patterns	68
7.6	Command set for the command slot channel: CS-CH (only for R/W-tag)	68
7.6.1	Command types	68
7.6.2	Command set	69
7.6.3	Command codes	70
8	MODE 3: Active RFID ITF network	72
8.1	General	72
8.2	Operational Requirements	72
8.3	Network Physical Layer Description	73
8.4	Network Description	73
8.4.1	General	73
8.4.2	Network Topology	73
8.5	Star Topology	76
8.5.1	General	76
8.5.2	Star Topology Data Flow	76
8.6	Trunk Topology	76
8.6.1	Trunk Coordinator Requirements	76
8.6.2	Data Flow in a Trunk Topology	77
8.7	Peer-to-Peer Topology	77
8.8	Mesh Topology	78
8.8.1	Establishing a Mesh Network	78
8.9	Message Types	81
8.9.1	Network Discovery Beacon (NDB)	83
8.9.2	Network Status Message (NSM)	87
8.9.3	Acknowledgement Message	91
8.9.4	Command Message	94
8.9.5	Data Message	95
8.9.6	Mesh Request	96
8.9.7	Mesh Data	97
8.10	Network Discovery	97
8.10.1	Methods of Network Discovery	98
8.10.2	Transmitting Network Discovery Beacons	98
8.10.3	Connectionless Network	99
8.10.4	Associated Network Connection (ANC)	100
8.11	Link Encryption Methods	102
9	Table of characteristic differences between the modes specified in this part of ISO/ IEC 18000	103
	Annex A (informative) Mode 1: Memory Map	104
	Annex B (informative) Mode 1: CRC	110
	Annex C (normative) Mode 2: Memory Map	113
	Annex D (informative) Mode 2: CRC	115
	Bibliography	117